



This is to certify that: **Smart Systems Limited** 

**Incorporating Smart Extrusions** 

**Arnolds Way** Yatton **BS49 4QN** United Kingdom

Holds Certificate Number: KM 81543

In respect of:

#### **BS 4873**

### **Aluminium Window System Supplier**

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI: Gary Fenton, Global Product Certification Director

Latest Issue: 18/05/2016 First Issued: 03/02/2005



...making excellence a habit.™

Page: 1 of 13

No. KM 81543

### BS 4873:2009 - Aluminium alloy windows and doorsets.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### **Alitherm 300 System Aluminium Alloy Window system**

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Alitherm 300 Windows Manual

**System description:** The windows are thermally broken, double glazed only, internally or externally

beaded, multipoint locking only with mechanically fixed transoms/mullions.

**Ventilation:** None

Window Types: Casement windows

Fixed windows

Multilight windows comprising opening light(s) with or without fixed light(s)

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 2 of 13

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated online.

No. KM 81543

### **Size Limitations and Performance Characteristics**

## **Alitherm 300 Aluminium Alloy Window System**

Window Type	Length (mm) Maximum	Height (mm) - Maximum	Perimeter (mm) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for windows	with app	roved sas	h profiles:					
Projecting top hungs Internally Beaded	1400	1400	-	-	4	7A	AE2400	2000+
Projecting top hungs Externally Beaded	1400	1400	-	-	4	5A	AE2400	2000+
Projecting side hungs Internally Beaded	600	1400	-	-	4	7A	AE2400	2000+
Projecting side hungs Externally Beaded	600	1400	ı	ı	4	5A	AE2400	2000+
Overall dimensions for windo	ws with ap	oproved o	uter frame	e profiles:				
Fixeds Internally Beaded	2100	2100	8400	-	4	7A	AE2400	2000+
Fixeds Externally Beaded	2100	2100	8400	-	4	5A	AE2400	2000+
Overall dimensions for windows with approved outer frame & transom/mullion profiles:								
Multilights, ETC335 T/M Internally Beaded	2100	2100	7100	1450	4	7A	AE2400	2000+
Multilights, ETC 335 T/M Externally Beaded	2100	2100	7100	1450	4	5A	AE2400	2000+

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 3 of 13

No. KM 81543

### BS 4873:2009 - Aluminium alloy windows and doorsets.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### Alitherm 600 System Aluminium Alloy Window system

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Alitherm 600 Windows & Doors Manual

**System description:** The windows are thermally broken, double glazed only, internally or externally

beaded, multipoint locking only, with mechanically fixed transoms/mullions

**Ventilation:** None

Window Types: Casement windows

Fixed windows

Multilight windows comprising opening light(s) with or without fixed light(s)

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 4 of 13

No. KM 81543

### **Size Limitations and Performance Characteristics**

## **Alitherm 600 Aluminium Alloy Window System**

Window Type	Length (mm) Maximum	Height (mm) - Maximum	Perimeter (mm) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for window	ws with ap	proved sa	sh profile	s:				
Projecting top hungs Internally beaded	1400	1500	-	-	4	7A	AE2400	2000+
Projecting top hungs Externally beaded	1400	1500	-	-	4	5A	AE2400	2000+
Projecting side hungs Internally beaded	1000	1400	-	-	4	7A	AE2400	2000+
Projecting side hungs Externally beaded	1000	1400	-	-	4	5A	AE2400	2000+
Overall dimensions for wind	dows with	approved	outer fran	me profiles:				
Fixeds Internally beaded	2100	2100	8400	-	4	7A	AE2400	2000+
Fixeds Externally beaded	2100	2100	8400		4	5A	AE2400	2000+
Overall dimensions for windows with approved outer frame & transom/mullion profiles:								
Multilights, ETC335 T/M Internally beaded	2100	2100	7100	1450	4	7A	AE2400	2000+
Multilights ETC335 T/M Externally beaded	2100	2100	7100	1450	4	5A	AE2400	2000+

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 5 of 13

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated online.

No. KM 81543

### BS 4873:2009 - Aluminium alloy windows and doorsets.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### **Alitherm 700 System Aluminium Alloy Window system**

**Fabrication and** Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Alitherm 700 Windows Manual

The windows are thermally broken, double glazed only, internally beaded, multipoint **System description:** 

locking only, with mechanically fixed transoms/mullions

**Ventilation:** None

**Window Types:** Casement windows

> Parallel opening windows Fully reversible windows

Fixed windows

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 6 of 13

No. KM 81543

### **Size Limitations and Performance Characteristics**

### **Alitherm 700 Aluminium Alloy Window System**

Window Type	Length (mm) Maximum	Height (mm) - Maximum	Perimeter (mm) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for windo	ws with	approved	d sash pro	files:			-	
Projecting Top Hungs	1600	1600			4	9A	AE2400	2000+
Projecting Side Hungs	840	1500		1	4	9A	AE2400	2000+
Parallel	1800	2100	7200	-	4	9A	AE2400	2000+
Reversible	1500	1558	6116	-	4	9A	AE2400	2000+
Fixeds	2100	2100	7800		4	9A	AE2400	2000+

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 7 of 13

No. KM 81543

### BS 4873:2009 - Aluminium alloy windows and doorsets.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### Alitherm 800 System Aluminium Alloy Window system

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Alitherm 800 Windows & Doors Manual

**System description:** The windows are thermally broken, double glazed only, internally or externally

beaded, multipoint locking only, with mechanically fixed transoms/mullions

**Ventilation:** None

Window Types: Casement windows

Fixed windows

Multilight windows comprising opening light(s) with or without fixed light(s)

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 8 of 13

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated online.

No. KM 81543

### **Size Limitations and Performance Characteristics**

## **Alitherm 800 Aluminium Alloy Window System**

Window Type	Length (mm) Maximum	Height (mm) - Maximum	Perimeter (mm) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009	
Sash dimensions for window	vs with ap	proved sas	h profiles:						
Projecting top hungs	1400	1300	-	-	3	8A	A2	800	
Projecting side hungs	800	1400	-	1	3	E1050	AE	2000	
Overall dimensions for wind	ows with	approved o	uter frame	e profiles:					
Fixeds	2100	2100	4800	-	3	E1050	AE	2000	
Overall dimensions for windows with approved outer frame & transom/mullion profiles:									
Multilights, ETC831 T/M reinforcement	2100	2100	7100	1450	3	E1050	AE	2000	

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 9 of 13

No. KM 81543

### BS 4873:2009 - Aluminium alloy windows and doorsets.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### **Eco Futural System Aluminium Alloy Window system**

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Eco Futural Windows & Doors Manual

**System description:** The windows are thermally broken, double glazed only, internally or externally

beaded, multipoint locking only, with mechanically fixed transoms/mullions

**Ventilation:** None

Window Types: Casement windows

Tilt/Turn windows Fixed windows

Multilight windows comprising opening light(s) with or without fixed light(s)

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 10 of 13

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated online.

No. KM 81543

### **Size Limitations and Performance Characteristics**

## **EcoFutural Aluminium Alloy Window System**

Window Type	Length (mm) Maximum	Height (mm) - Maximum	Perimeter (mm) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009	
Sash dimensions for windov	vs with ap	proved sas	h profiles:						
Projecting top hungs	1440	2500	-	-	3	8A	A5	2000	
Projecting side hungs	840	1440	ı		4	E1050	AE2400	2000+	
Overall dimensions for wind	ows with	approved o	uter frame	e profiles:					
Fixeds	2100	2100	4800	-	4	E1050	AE	2000	
Tilt/Turns	1600*	2400	-	-	4	E900	AE	2400	
Overall dimensions for wind	Overall dimensions for windows with approved outer frame & transom/mullion profiles:								
Multilights	2400	2100	7680	1345	4	E1050	AE	2000	

<sup>\*</sup>Width of the Tilt/Turn Sash must not exceed 1½ times the height.

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 11 of 13

No. KM 81543

### BS 4873:2009 - Aluminium alloy windows and doorsets.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### **Alitherm Heritage System Aluminium Alloy Window system**

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Smart Systems Limited controlled manual(s):

Smart Systems Alitherm Heritage Windows Manual

**System description:** The windows are thermally broken, double glazed only, internally or externally

beaded, multipoint locking only, with mechanically fixed transoms/mullions

**Ventilation:** None

Window Types: Casement windows

Fixed windows

Multilight windows comprising opening light(s) with or without fixed light(s)

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 12 of 13

No. KM 81543

## **Size Limitations and Performance Characteristics**

### **Alitherm Heritage Aluminium Alloy Window System**

Window Type	Length (mm) Maximum	Height (mm) - Maximum	Perimeter (mm) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for windows	with app	roved sas	h profiles:					
Projecting top hungs Internally Beaded	1400	1400	-	-	4	9A	AE2400	2000+
Projecting top hungs Externally Beaded	1400	1400	-	-	4	9A	AE2400	2000+
Projecting side hungs Internally Beaded	600	1400	-	-	4	9A	AE2400	2000+
Projecting side hungs Externally Beaded	600	1400	-	ı	4	9A	AE2400	2000+
Overall dimensions for windo	ws with a <sub>l</sub>	oproved o	uter frame	e profiles:				
Fixeds Internally Beaded	2100	2100	8400	-	4	9A	AE2400	2000+
Fixeds Externally Beaded	2100	2100	8400	-	4	9A	AE2400	2000+
Overall dimensions for windows with approved outer frame & transom/mullion profiles:								
Multilights, W2035 T/M Internally Beaded	2100	2100	7100	1450	4	9A	AE2400	2000+
Multilights, W2035 T/M Externally Beaded	2100	2100	7100	1450	4	9A	AE2400	2000+

First Issued: 03/02/2005 Latest Issue: 18/05/2016

Page: 13 of 13