


Main Index



Index.....	A01 - A02
Updates.....	A03




Profiles

Specification Pages.....	A05 - A08
Technical Information.....	A09 - A18
Scale Profile Drawings.....	A19 - A52



Accessories

Photos & Drawings.....	B03 - B64
------------------------	-----------



Sections

Slide - Scale Elevations.....	C03 - C41
Lift and Slide - Scale Elevations.....	C42 - C69



Statics.....

D03 - D10



Construction Drawings

Punch Tool Details.....	E03 - E04
Drainage Details.....	E05 - E08
Sash Transom Details.....	E09
Roller Preparation & Fixing.....	E10 - E11
Multi-Point Lock Preparation & Installation.....	E12 - E14
BT Lock Preparation & Installation.....	E15 - E17
Lock & Handle Overview.....	E18 - E20
Interlock Details.....	E21 - E27
Sash to Sash Locking Stile.....	E28 - E32
VG632 Locking Detail.....	E33
Sash Installation.....	E34
ACVG528 Position Details.....	E35
Fixed Sash Installation.....	E36
ACUG830 Fixing Detail.....	E37
VG514 & VG515 Cutting & Fitting.....	E38
VG519 Assembly.....	E39 - E40
Sobinco Lift & Slide Hardware Overview.....	E41
Sobinco Lift & Slide Lock & Handle Preparation.....	E42 - E47
Hautau Lift & Slide Hardware Overview.....	E48
Hautau Lift & Slide Lock & Handle Preparation.....	E49 - E52
Hautau Soft Close Mechanism.....	E53 - E55
Lift & Slide Slim Interlock Preparation.....	E56

Main Index

VG516/VG518 Details & Installation.....	E57 - E59
Monorail Assembly.....	E60 - E62
Head Extension Fitting Details.....	E63
Glazing Chart.....	E64 - E68
PAS24:2016 Overview.....	E69
ACUN348 Buffer.....	E70
Floating Corner Assembly.....	E71 - E74
VG651 - VG655 Bay Pole Apapters.....	E75

F VG+

Sawing Tables

Sliding Doors.....	F03 - F14
Sobinco Lift and Slide Doors.....	F15 - F22
Hautau Lift and Slide Doors.....	F23 - F27
Vanishing Corner.....	F28

Updates

DATE	PAGE	DESCRIPTION
28/03/18	All Sections	<ul style="list-style-type: none">-Added revised method of assembly for slim interlocks-New VG534 internal reinforced interlock-New VG552N co-extruded interlock with VG586 weather strip carrier-New VG575 & ACVG575 cill infill-New ACVG534 Drainage Spout-ACVG528 Positioning Detail-Vanishing Corner Sections VG580 & VG581 added-Vanishing Corner Accessories ACSZ015, ACDV313 & ACDV326 added
05/11/18	E24 & E26	Instructions added regarding glazing sash with VG534 to both jambs.
29/11/18	E14 E72 B07 E55	<ul style="list-style-type: none">Added routing detail for ACVG752 shootbolt.Added details for Bay Pole Adapters VG651 - VG655.Added ACET478 Cast Cill End CapsAdded ACUG123 Fixing Detail
05/12/18	Various	Added VG549 Meeting Stile and accessories for BT Lock
28/01/19	Various	<ul style="list-style-type: none">Updated Kitemark (PAS24) information.ACUN3523 to replace ACET133 for fixing ACSZ750/751 handles.
07/02/19	Various	ACVG281 replaced by ACVG281N and added fixing detail.
15/07/19	E73	Updated ACDV326 shootbolt position to avoid clashes with keeps.



Specification

GENERAL DESCRIPTION

Visoglide Plus is a patio door system which can be operated by sliding or lift & slide hardware. The system achieves excellent U values inline with the current Building Regulations.

The system is suitable for replacement windows/doors in existing buildings and for installation into new buildings.

Visoglide Plus provides the option of multi-point locking with standard lever handles or off-set 'D' handles. Or for additional security, reinforced lever handles are available.

Assembly of the outerframe and the sashes is with mechanical cleats for which the holes are prepped using punch tools ACVG900 or ACVG905 . See Pages E03 & E04 for details.

Sashes are internally beaded allowing glazing to be completed after installation.

PROFILE SPECIFICATION

The frames are constructed of aluminium alloy extrusion to BS EN 755-9 and BS EN 12020, extruded from 6060 T6 alloy. The internal and external extrusions are separated with a polyamide thermal break.

The external aluminium alloy extrusion is pre-treated and finished either:-

- a) Anodised to BS 3987: 1987, grade AA25 to a natural self colour.
- b) Polyester powder organic coating to BS 6496. Dual colour is available.

GENERAL MANUFACTURING

Outer frames are made by cutting the frame profiles with accurate 45° mitred ends using Tungsten Carbide Tipped Saw Blades, operating at approximately 3000 rpm.

The corner joints can be made using mechanically fixed corner cleats by punching the corners using the relevant punch tooling shown in section E of this manual. All joints should be sealed using ACSIL04 sealant

On polyester powder coated finishes, great care should be taken to avoid getting gap sealer on visible surfaces and should be removed as soon as possible with a clean cloth.

Care should be exercised when using products not supplied by Smart Systems Ltd as no responsibility can be accepted.

Specification

DRAINAGE

As with all dry glazed systems, it is recommended that the profiles are adequately drained and ventilated. Refer to drainage details in section E of this manual, if in doubt, ask the Technical Department.

In order to get maximum performance and weather resistance it is recommended that drips are used over all vents.

OUTER FRAME & VENT MANUFACTURING INFORMATION

The outer frame members are cut with 45° mitred ends to the overall size required, measured to the longest point of the metal.

Corners are formed by coating the cut faces to be joined with ACSIL04 small gap sealer and by applying ACSIL013 cleat glue into the cleat chamber. Into the mitred corner insert the required corner cleats and, where required, the aluminium corner chevrons. The two mitred ends are then brought together and mechanically joined. The small gap sealer ensures a permanent joint and guards against the ingress of moisture and joint movement. After joining the corners, special care should be taken to ensure any excess sealer is removed from painted surfaces.

LOCKING

The vertical members should be prepped for the locking mechanism prior to fabrication and fitted before assembly. Stainless steel fixings shall be used for securing the locking mechanism and keeps in position.

GLAZING

Glazing can be 8-12mm, 24-26mm, 28-30mm or 36-38mm by selecting the relevant bead & gasket.

For advise on window sizes outside of the recommended design limitations, please contact the Technical Department at Smart Systems Ltd Tel: 01934 876100

Specification

RECOMMENDED DESIGN LIMITATIONS

Sliding Sashes

Maximum Sash Weight:	250kg
Minimum Sash Height:	800mm (NB. Lock will have two locking points where sash is below 1400mm) 1885mm for PAS24:2016
Maximum Sash Height:	2500mm
Maximum Sash Width:	Providing sashes are within above limitations there is no maximum width.

Lift & Slide Sashes

	<u>Sobinco Gearing</u>	<u>Hautau Gearing</u>
Maximum Sash Weight:	200kg	300kg
Minimum Sash Height:	1718mm	1877mm
Maximum Sash Height:	2500mm	2500mm
Minimum Sash Width:	702mm	650mm
Maximum Sash Width:	3294mm	3235mm

Please see pages D01-D09 for more guidance on vent sizes & limitations.

The below is a summary of the sliding door testing under Kitemark Licence Number: KM530838. The full details may be downloaded from www.smartsystems.co.uk

Visoglide Plus Operational Performance (BS6375-2:2009)

Visoglide Plus has passed the operational & strength requirements of BS6375-2
(Test Report 8247857)

Visoglide Plus Security (PAS24:2016)

Visoglide Plus has been successfully tested to PAS24:2016
(Test Report 8247857)

Visoglide Plus U Values

Please refer to the Smart Systems' Document L White Paper or contact the Technical Department.

Specification

Kitemark™ Certificate

No. KM 530838

Visoglide Plus Aluminium Alloy Patio Door System

BS 4873:2016 / PAS 24:2016 - General and enhanced security performance requirements for door assemblies.

Profiles	Outer Frame: VG510/511N/512/513N/516/518/519/610/612/618/620/621 Leaf: VG520/521N Interlocks: VG534/535/536/539 Frame Filler: VG514/515
Multipoint Hardware	Locking: ACSZ024/025/026 Shootbolt: ACVG752 Keep: ACSZ122/124/126/128/130/132 Handle: ACSZ882/883 Cylinder + Cover: ACIM442/ACCY4040S1
BT Hardware	Locking: ACSZ040/041/042 Keep: ACSZ046 Handle: ACSZ750/751 Cylinder + Cover: ACCY3030S1

Size Limitations And Performance Characteristics

Door Type	Leaf Width (mm) - Maximum	Leaf Height (mm) - Maximum	Air Permeability Classification	Watertightness Classification	Resistance To Wind Classification	Exposure Category As Given In Table 1 Of BS6375-1:2009
2 pane sliding doorset	2000	2400	3	7A	AE2400	2000+
3 pane (2 sliding) doorset	2000	2400	3	3A	1200	1200
Active/Fixed leaf	2000	2400	3	7A	AE2400	2000+

⚠ Important! ⚠

The size parameters shown against Kitemark are the maximum allowed without the need for further testing. Please note these are not necessarily the system parameters which may be smaller or larger. Please refer to fabrication parameters in this manual.










First Issued: 29/09/2008

Latest Issue: 27/09/2018

Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm ⁴) wx(cm ³)	Iy(cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
VG12		A49	110	26	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
VG52		A48	25	-	- ---- -	- ---- -	7	1	✓				
VG53		A48	106	-	- ---- -	- ---- -	6.5	1	✓				
VG408		A42	69	28	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
VG416		A42	77	37	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
VG430		A42	106	51	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
VG510		A19	491	137	94.28 ---- 19.05	20.80 ---- 8.81	7 5	1	✓	✓	✓	✓	
VG511N		A19	580	270	150.33 ---- 24.48	24.05 ---- 10.15	7 5	1	✓	✓	✓	✓	
VG512		A20	729	140	348.86 ---- 41.36	30.01 ---- 13.62	7	1	✓	✓	✓	✓	

A = Outside
B = Inside

MF = Mill Finish
SA = Silver Anodised
KL = Basic Colour
HP = Special Colour
M = Dual Colour










Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm ⁴) wx(cm ³)	Iy(cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
VG513N	A  B	A20	817	128	33.32 ----- 11.18	489.43 ----- 52.29	7	1	✓	✓	✓	✓	✓
VG514		A25	210	62	- ----- -	- ----- -	6.5	1	✓	✓	✓	✓	
VG515		A25	277	73	1.14 ----- 0.44	10.20 ----- 3.38	7	1	✓	✓	✓	✓	
VG516	A  B	A21	429	96	81.9 --- 12.6	9.1 --- 4.0	7 3.5	1	✓	✓	✓	✓	✓
VG518	A  B	A21	521	78	123.5 --- 21.0	22.1 --- 7.7	7 5	1	✓	✓	✓	✓	✓
VG519		A22	501	15	20.40 ----- 4.71	9.26 ----- 5.05	6.5	1	✓	✓	✓	✓	
VG520	A  B	A26	449	141	20.40 ----- 7.47	13.83 ----- 3.96	6.5	1	✓	✓	✓	✓	✓
VG521N	A  B	A26	534	173	27.85 --- 6.00	24.23 --- 10.07	6.5 - 5	1	✓	✓	✓	✓	✓
VG530		A29	195	72	5.97 ----- 1.71	0.36 ----- 0.94	6.5	1	✓	✓	✓	✓	

A = Outside
B = Inside

MF = Mill Finish
SA = Silver Anodised
KL = Basic Colour
HP = Special Colour
M = Dual Colour

Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm ⁴) wx(cm ³)	Iy(cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
VG532		A29	188	-	6.40 ----- 3.30	3.60 ----- 1.50	6.5	1	✓				
VG533		A29	267	124	4.74 ----- 1.66	6.19 ----- 2.90	6.5	1	✓	✓	✓	✓	
VG534		A29	249	51	30.6 ----- 7.57	4.11 ----- 2.38	6.5	1	✓	✓	✓	✓	✓
VG535		A30	249	51	9.18 ----- 3.33	1.03 ----- 0.97	6.5	1	✓	✓	✓	✓	✓
VG536		A30	316	109	26.83 ----- 6.33	3.97 ----- 2.42	6.5	1	✓	✓	✓	✓	✓
VG537		A30	175	68	4.95 ----- 1.45	0.10 ----- 0.45	6.5	1	✓	✓	✓	✓	
VG538		A27	367	109	17.13 ----- 5.87	8.49 ----- 2.43	6.5	1	✓	✓	✓	✓	✓
VG539		A30	388	188	112.65 ----- 15.56	10.36 ----- 6.13	6.5	1	✓	✓	✓	✓	✓
VG540		A31	295	48	6.40 ----- 2.95	7.74 ----- 3.64	6.5	1	✓	✓	✓	✓	✓

A = Outside	MF = Mill Finish
B = Inside	SA = Silver Anodised
	KL = Basic Colour
	HP = Special Colour
	M = Dual Colour








Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm ⁴) wx(cm ³)	Iy(cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
VG541	A  B	A31	477	201	69.99 ----- 15.29	17.62 ----- 7.47	6.5	1	✓	✓	✓	✓	✓
VG542	A  B	A32	406	150	17.3 --- 6.0	6.6 --- 2.7	6.5	1	✓	✓	✓	✓	✓
VG549	A  B	A32	300	153.3	16.74 --- 5.83	5.21 --- 2.32	6.5	1	✓	✓	✓	✓	✓
VG551R	 Polyamide	A37	161	-	- ----- -	- ----- -	6.5	1	✓				
VG552N	 PVC	A30	108	-	- ----- -	- ----- -	6.5	1	✓				
VG553N	 PVC	A37	181	-	- --- -	- --- -	6.5	1	✓				
VG554	 PVC	A38	455.4	-	3.457 --- 2.548	55.152 --- 18.541	7 3.5	1	✓				
VG555		A22	94	-	- ----- -	- ----- -	6.5	1	✓				
VG556	A  B	A39	329	25	32.43 ----- 6.82	0.34 ----- 0.50	6.5	1	✓	✓	✓	✓	✓

A = Outside
 B = Inside
 MF = Mill Finish
 SA = Silver Anodised
 KL = Basic Colour
 HP = Special Colour
 M = Dual Colour

Number	Picture	Page	Perim. mm	Mec. mm	lx(cm4) wx(cm3)	ly(cm4) wy(cm3)	Length	Pack pr.	MF	SA	KL	HP	M
VG557		A39	127	25	0.16 ---- 0.19	0.55 ---- 0.50	6.5	1	✓	✓	✓	✓	
VG558		A40	464	85	58.53 ---- 11.82	6.91 ---- 5.12	7	1	✓	✓	✓	✓	
VG559		A40	597	85	192.84 ---- 23.28	8.35 ---- 7.82	7	1	✓	✓	✓	✓	
VG560		A42	99	32	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
VG561		A43	68	23	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
VG565		A30	83	24	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
VG566		A30	52	15	- ---- -	- ---- -	5	1	✓	✓	✓	✓	
VG572		A41	531	85	8.05 ---- 2.42	88.08 ---- 16.34	7	1	✓	✓	✓	✓	
VG573		A41	631	85	9.08 ---- 2.59	247.35 ---- 26.86	6.5	1	✓	✓	✓	✓	

 A = Outside
 B = Inside

 MF = Mill Finish
 SA = Silver Anodised
 KL = Basic Colour
 HP = Special Colour
 M = Dual Colour

Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm ⁴) wx(cm ³)	Iy(cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
VG575		A27	140	-	- ----- -	- ----- -	6.5	1	✓				
VG580		A33	327	99	11.4 ----- 4.1	13.5 ----- 6	6.5	1	✓	✓	✓	✓	✓
VG581		A33	331	128	33.1 ----- 9.2	21.8 ----- 8.9	6.5	1	✓	✓	✓	✓	✓
VG586		A37	33	-	- ----- -	- ----- -	6.5	1	✓				
VG610		A24	626	210	145.4 ----- 19.1	20.3 ----- 6.5	6.5	1	✓	✓	✓	✓	✓
VG612		A23	772	161	414.8 ----- 44.2	31.5 ----- 10.4	7	1	✓	✓	✓	✓	✓
VG615		A36	299	123	2.756 — 1.486	21.357 — 5.309	6.5	1	✓	✓	✓	✓	
VG616		A36	329	118.6	2.814 — 1.160	2.468 — 6.223	6.5	1	✓	✓	✓	✓	
VG618		A24	644	244	163.4 — 20.6	20.8 — 6.6	6.5	1	✓	✓	✓	✓	✓

A = Outside
B = Inside

MF = Mill Finish
SA = Silver Anodised
KL = Basic Colour
HP = Special Colour
M = Dual Colour

Number	Picture	Page	Perim. mm	Mec. mm	I _x (cm ⁴) wx(cm ³)	I _y (cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
VG620		A28	485	128	50.8 — 12.6	12.6 — 3.1	7	1	✓	✓	✓	✓	✓
VG621		A28	550	167	60.7 — 15.1	26.5 — 5.5	7	1	✓	✓	✓	✓	✓
VG630		A34	242	96	15.32 — 3.98	0.39 — 0.26	6.5	1	✓	✓	✓	✓	
VG632		A34	249	166	15.7 — 4.6	5.1 — 1.6	6.5	1	✓	✓	✓	✓	
VG651		A44	482	120	66.3 — 11.8	33.1 — 5	6.5	1	✓	✓	✓	✓	✓
VG652		A44	515	115	58.5 — 10.2	33.9 — 5.5	6.5	1	✓	✓	✓	✓	✓
VG653		A45	406	82	62.3 — 11.7	8.9 — 2	6.5	1	✓	✓	✓	✓	✓
VG654		A45	441	78	55.9 — 10.3	9.6 — 2.3	6.5	1	✓	✓	✓	✓	✓
VG655		A46	484	162	57.9 — 9.8	33.2 — 5.5	6.5	1	✓	✓	✓	✓	✓

A = Outside
 B = Inside
 MF = Mill Finish
 SA = Silver Anodised
 KL = Basic Colour
 HP = Special Colour
 M = Dual Colour

Number	Picture	Page	Perim. mm	Mec. mm	I _x (cm ⁴) wx(cm ³)	I _y (cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
VG660		A43	45	-	- ---- -	- ---- -	6.5	1	✓				
VG670		A47	346	61	60.6 ---- 12.1	5.7 ---- 3.8	6.5	1	✓	✓	✓	✓	✓
VG671		A47	383	98	93.0 ---- 15.8	6.9 ---- 4.6	6.5	1	✓	✓	✓	✓	✓
VG674		A52	603	236	208.2 ---- 32.8	208.2 ---- 32.8	6.5	1	✓	✓	✓	✓	✓
VG681		A47	431	145	154.7 ---- 21.5	8.9 ---- 6.0	6.5	1	✓	✓	✓	✓	✓
ETC478		A52	736	314	1410.7 ---- 87.7	26.8 ---- 12.8	5	1	✓	✓	✓	✓	✓
GL724		A50	186	49	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
GL728		A50	198	63	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	
GL732		A50	216	57	- ---- -	- ---- -	6.5	1	✓	✓	✓	✓	

A = Outside
B = Inside

MF = Mill Finish
SA = Silver Anodised
KL = Basic Colour
HP = Special Colour
M = Dual Colour


Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm ⁴) wx(cm ³)	Iy(cm ⁴) wy(cm ³)	Length	Pack pr.	MF	SA	KL	HP	M
GL736		A50	224	61	- ----- -	- ----- -	-	1	✓	✓	✓	✓	
GL740		A50	155	65	- ----- -	- ----- -	-	1	✓	✓	✓	✓	
SR014		A22	110	71	- ----- -	- ----- -	-	1	✓	✓	✓	✓	
UG050		A19	256	-	- ----- -	- ----- -	7	1	✓				
UG054		A38	161	-	- ----- -	- ----- -	7	1	✓				
UG852		A37	44	-	- ----- -	- ----- -	6.5	1	✓				
UN010		A49	111	44	- ----- -	- ----- -	6.5	1	✓	✓	✓	✓	
UN500		A35	137	52	0.06 ----- 0.08	1.68 ----- 0.84	6.5	1	✓	✓	✓	✓	
UN510		A35	374	160	12.14 ----- 3.72	9.47 ----- 4.73	6.5	1	✓	✓	✓	✓	

A = Outside	MF = Mill Finish
B = Inside	SA = Silver Anodised
	KL = Basic Colour
	HP = Special Colour
	M = Dual Colour


Primary Visible Side

Secondary Visible Side

VG510
Two Track
Outer Frame




VG511N
Two Track
Outer Frame
with Upstand




Primary Visible Side

Secondary Visible Side

VG512
Three Track
Outer Frame




VG513N
Three Track
Outer Frame
with Upstand




Primary Visible Side

Secondary Visible Side

VG516
Mono Rail Threshold
NOT Weather Tested




VG518
Two Track
Stepped Outer Frame





Primary Visible Side

Secondary Visible Side

VG519
Frame Add On




VG555
VG519 Locator



Primary Visible Side

Secondary Visible Side

VG612
Three Track
Stepped Outerframe




Primary Visible Side

Secondary Visible Side


VG610

Mono Track
Outerframe



VG618



Mono Track
Stepped Outerframe





Primary Visible Side

Secondary Visible Side

VG514
Two Track Cover





VG515
Three Track Cover



Primary Visible Side


Secondary Visible Side





Primary Visible Side

Secondary Visible Side

VG538
Sash Transom




VG575
PVC Infill for UG050




Primary Visible Side

Secondary Visible Side

VG620
Mono Rail Fixed Light
for Sliding Door




VG621
Mono Rail Fixed Light
for Lift & Slide Door





Primary Visible Side

Secondary Visible Side


VG530
Interlock Cover



VG533
VG532 Cover Cap



VG532
Reinforcing Section




VG534
Reinforced Internal
Slim Interlock

Primary Visible Side

Secondary Visible Side


VG535

Internal Slim Interlock




VG537

Slim Interlock Cover Cap




VG536

External Slim Interlock




VG539

External Slim
Reinforced Interlock




VG565

28-30mm Glazing
Narrow Bead




VG566

36-38mm Glazing
Narrow Bead



VG552N

Narrow PVC Interlock




Primary Visible Side

Secondary Visible Side


VG540

Meeting Stile Adaptor
NOT For Lift & Slide



VG541


Reinforced Meeting Stile Adaptor
NOT For Lift & Slide





Primary Visible Side

Secondary Visible Side

VG542
Rebated Meeting
Stile Adaptor




VG549
Rebated Meeting
Stile Adaptor for BT Lock




Primary Visible Side

Secondary Visible Side



VG581
Floating Corner Post
90° Meeting Stile




Primary Visible Side

Secondary Visible Side

VG630

Monorail Slide Interlock
Cover Cap



VG630 VG620


VG551R

VG520

VG530

VG520

VG632




VG520

VG530


Primary Visible Side

Secondary Visible Side

UN500
Cover Cap




UN510
Reinforcement Profile





Primary Visible Side

Secondary Visible Side




VG615

Internal Jamb/Head Cover



VG616

Internal Threshold Cover




Primary Visible Side

Secondary Visible Side



VG586

Polyamide Weather Strip Carrier





VG551R

Polyamide Interlock




UG852

Infill Channel



VG553N



Lift & Slide PVC Interlock





Primary Visible Side

Secondary Visible Side

UG054
Mono Rail Infill




VG554
Mono Rail Fixed Light Holder




Primary Visible Side

Secondary Visible Side

VG556
Drainage Tray




VG557
Frame Extension




Primary Visible Side

Secondary Visible Side

VG558
VG510 Track
Head Extension



VG559
VG512 Track
Head Extension




P

Primary Visible Side


S

Secondary Visible Side

VG572
VG511N/VG518 Track
Head Extension



VG573
VG513N/VG612 Track
Head Extension




Primary Visible Side

Secondary Visible Side


VG430

Single Glazing Bead




VG416

Glazing Bead




VG560

Glazing Bead




VG408

Glazing Bead





Primary Visible Side

Secondary Visible Side



VG660
Lift & Slide Gasket Carrier




Primary Visible Side

Secondary Visible Side

VG651

Variable Angle Coupler



99



VG652

Variable Angle Coupler

99



See page E74 for details


Primary Visible Side

Secondary Visible Side

VG653

Variable Angle Coupler



99



VG654

Variable Angle Coupler


99




See page E74 for details

Primary Visible Side

Secondary Visible Side



VG655
Variable Angle Coupler




See page E74 for details


Primary Visible Side

Secondary Visible Side


VG670
Coupler



VG671
Coupler



VG681
Coupler



Scale 1:1


Primary Visible Side

Secondary Visible Side


VG52
PVC Infill




VG53
Stainless Steel Track




VL72
Weather Drip




UTL027
Jamb Insert



VL75
Coupling Piece



VL76
Weather Drip




Scale 1:1



Primary Visible Side

Secondary Visible Side

VG12
Frame Surround



UN010
Frame Upstand




Scale 1:1


Primary Visible Side

Secondary Visible Side


GL724
Mono Rail
38mm - 40mm Glazing Bead




GL728
Mono Rail
36mm - 37mm Glazing Bead




GL732
Mono Rail
32mm - 34mm Glazing Bead



GL736
Mono Rail
28mm - 30mm Glazing Bead



GL740
Mono Rail
24mm - 26mm Glazing Bead




Scale 1:1

Primary Visible Side

Secondary Visible Side


VL155
90° Corner Post



Primary Visible Side

Secondary Visible Side

VG674
90° Corner Post



ETC478

300mm cill
(Scale 1:2)


186.5

10

End Caps:
ETC478

300

25



Section B

Accessories

Photos & Drawings

Section B

Image	Part Code	Pack	Unit	Application	Colour
	ACCY3030S1 High Security 30/30 Europrofile Cylinder Anti-Bump, Anti-Pick, Anti-Screw & Anti-Drill protection. Nickel Finish Keyed Alike Unavailable	1	Each	ACSZ750 ACSZ751	MF SA KL HP SSC SMC W Z PC
	ACCY4040S1 High Security 40/40 Europrofile Cylinder Anti-Bump, Anti-Pick, Anti-Screw & Anti-Drill protection. Nickel Finish Keyed Alike Unavailable	1	Each	ACSZ400 ACSZ839	MF SA KL HP SSC SMC W Z PC
	ACDR052 No.10 x 50 S/S Self Tapping Pan Head	200	Pack		MF SA KL HP SSC SMC W Z PC
	ACDV264 M4 x 35 CSK S/S Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACDV265 M4 x 60 CSK S/S Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
	ACDV313 Shootbolt End Piece	1	Each	ACDV326	MF SA KL HP SSC SMC W Z PC
	ACDV326 Flush Bolt	1	Each		MF SA KL HP SSC SMC W Z PC
	ACEF010B Crimp Corner Cleat	24	Pack	VG610 VG618	MF SA KL HP SSC SMC W Z PC
	ACET060 No.7 x 25mm CSK S/S Self Tapping Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET062 No.10 x 50mm CSK S/S Self Tapping Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
 ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACET064 No.8 x 16 CSK S/S Self Tapping Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET066 No.7 x 38 CSK S/S Self Tapping Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET067 No.7 x 12.5 CSK S/S Self Tapping Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET076 No.10 x 2.5" CSK S/S Self Tapper Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET133 M5 x 50 CSK S/S Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	100	Pack		MF SA KL HP SSC SMC W Z PC
	Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			







Image	Part Code	Pack	Unit	Application	Colour
	ACET190 4.3 x 45mm Polyamide Screw	1000	Pack	ACVG530	MF SA KL HP SSC SMC W Z PC
	ACET220 M5 x 60 CSK S/S Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET235 M6 x 60 CSK S/S Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET237 M6 x 70 CSK S/S Screw	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACET390 4.3 x 25mm Polyamide Screw	200	Pack	ACVG558	MF SA KL HP SSC SMC W Z PC
 	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm		MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 

Image	Part Code	Pack	Unit	Application	Colour
	ACET431 Drainage Cover Cap	8	Pack		MF SA KL ✓ HP ✓ SSC SMC W Z PC
	ACET478 Cast Cill End Caps	1	Pair	ETC478	MF ✓ SA KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACET490 4.3 x 16mm Polyamide Screw	1000	Pack	ACUG030	MF SA KL HP SSC SMC W Z PC
	ACET840 5mm Low Line Wedge Gasket	150	m		MF SA KL HP SSC SMC W Z ✓ PC
	ACET841 4mm External Low Line Gasket	200	m		MF SA KL HP SSC SMC W Z ✓ PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACET842 3mm Low Line External Gasket	200	m		MF SA KL HP SSC SMC W Z ✓ PC
	ACET843 2mm Low Line External Gasket	200	m		MF SA KL HP SSC SMC W Z ✓ PC
	ACFT075 Linking Gasket	50	m		MF SA KL HP SSC SMC W Z PC
	ACFT076 Linking Gasket	100	m		MF SA KL HP SSC SMC W Z PC
	ACFT171 Clip for VG615 & VG616	200	Pack	VG610 VG615 VG616 VG618	MF SA KL HP SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			 	

Image	Part Code	Pack	Unit	Application	Colour
	ACGSL045 Drainage Cover Cap	100	Pack		MF SA KL HP SSC SMC W ✓ Z ✓ PC
	ACGSL057 Valve Cap (PVC)	10	Pack		MF SA KL HP SSC SMC W Z PC
	ACIM062 No.10 x 32 S/S Self Tapping CSK	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACIM442 40/40 Standard Cylinder For keyed alike order ACIM442SL	1	Each		MF SA KL HP SSC SMC W Z PC
	ACIM445 40/40 Standard Cylinder with Thumb Turn	1	Each		MF SA KL HP SSC SMC W Z PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
	ACMX0040 Profile Half Cylinder 40mm For keyed alike order ACMX0040SL	1	Each		MF SA KL HP SSC SMC W Z PC
	ACMX008 60 x 8 x 8mm Spindle	1	Each		MF SA KL HP SSC SMC W Z PC
	ACMX01615 35/35 Standard Cylinder For keyed alike order ACMX1615SL	1	Each	ACSZ400 ACSZ839	MF SA KL HP SSC SMC W Z PC
	ACMX01615T 35/35 Standard Cylinder with Thumb Turn	1	Each	ACSZ400 ACSZ839	MF SA KL HP SSC SMC W Z PC
	ACMX1070 70 x 10 x 10 Lift and Slide Half Spindle	1	each	Sobinco Gearing	MF SA KL HP SSC SMC W Z PC
	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome				

Image	Part Code	Pack	Unit	Application	Colour
	ACMX1075 75 x 10 x 10 Lift and Slide Half Spindle (Rounded)	1	each	Hautau Gearing	MF SA KL HP SSC SMC W Z PC
	ACMX1130 130 x 10 x 10mm Lift & Slide Spindle (Rounded)	1	Each	Hautau Gearing	MF SA KL HP SSC SMC W Z PC
	ACMX1138 138 x 10 x 10mm Lift & Slide Spindle	1	Each	Sobinco Gearing	MF SA KL HP SSC SMC W Z PC
	ACMX209 120 x 8 x 8mm Spindle	1	Each		MF SA KL HP SSC SMC W Z PC
	ACMX853 Cleat Tensioning Block 11mm	48	Pack	VG510 VG511 VG512 VG513 VG518 VG610 VG612 VG618	MF SA KL HP SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	 Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACMX854 Cleat Tensioning Block 8mm	48	Pack	VG520 VG521N	MF SA KL HP SSC SMC W Z PC
	ACMX867 M5 Rivnuts	10	Pack		MF SA KL HP SSC SMC W Z PC
	ACSG012 Mechanical Cleat	1	Each	VG520	MF SA KL HP SSC SMC W Z PC
	ACSG070 M5 x 65 CSK S/S Screw	1	Each		MF SA KL HP SSC SMC W Z PC
	ACSG611B Mechanical Corner Cleat	24	Pack	VG610 VG618	MF SA KL HP SSC SMC W Z PC
 	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome				

Image	Part Code	Pack	Unit	Application	Colour
	ACSG631 Gasket	100	m	VG610 VG615 VG616	MF SA KL HP SSC SMC W Z PC
	ACSM016 Straight Sliding Lever Door Handle	1	Pair		MF SA KL HP SSC SMC W Z PC
	ACSM017 Lift and Slide Door Handle and Flush Pull	1	Each		MF SA KL HP SSC SMC W Z PC
	ACSM018 Lift and Slide Door Handle Back to Back	1	Pair		MF SA KL HP SSC SMC W Z PC
	ACSM019 Patio Door Handles	1	Pair		MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACSM020 600mm Off-Set T Bar Back to Back	1	Pair		MF SA KL HP SSC SMC W Z PC
	ACSM021 1200mm Off-Set T Bar Back to Back	1	Pair		MF SA KL HP SSC SMC W Z PC
	ACSM024 Dummy Patio Handle to match ACSM019	1	Pair		MF SA KL HP SSC SMC W Z PC
	ACSP057 Glass Support	100 1000	Pack Pack	VG610 VG618	MF SA KL HP SSC SMC W Z PC
	ACSR011 Wool Pile H = 12mm	100	m		MF SA KL HP SSC SMC W Z PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
<p>34.2</p> <p>18</p> <p>6</p> <p>24</p> <p>15.5</p>	ACSZ007 2170mm Multi-Point Lock Requires: 1 x ACSZ100 Ctr Keep 4 x ACSZ101 Keeps -----OR----- 1 x ACSZ103 F/Height Keep -----OR----- 1 x ACSZ105 F/H Keep + 600mm -----OR----- 1 x ACVG550 ACSZ008 1970mm Multi-Point Lock Requires: 1 x ACSZ100 Ctr Keep 4 x ACSZ101 Keeps -----OR----- 1 x ACSZ107 F/Height Keep -----OR----- 1 x ACSZ109 + 600mm ACSZ009 2370mm Multi-Point Lock Requires: 1 x ACSZ100 Ctr Keep 4 x ACSZ101 Keeps -----OR----- 1 x ACSZ111 F/Height Keep -----OR----- 1 x ACSZ113 F/H Keep + 600mm	1	Each	VG520 ACSZ100 ACSZ101	MF SA KL HP SSC SMC W Z PC
	ACSZ010 280mm Single Point Lock Requires: 1 x ACSZ100 Ctr Keep	1	Each	VG520 ACSZ100	MF SA KL HP SSC SMC W Z PC
<p>T-BARS ACVG66=2.5mm ACVG66=3.0mm ACVL150=4.0mm</p> <p>Screw (Grub)</p>	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome				

Image	Part Code	Pack	Unit	Application	Colour																		
	ACSZ015 2170mm Multi-Point Lock Requires: 1 x ACSZ100 Ctr Keep 4 x ACSZ101 Keeps			VG580 ACSZ100 ACSZ101	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td></td></tr> <tr><td>KL</td><td></td></tr> <tr><td>HP</td><td></td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td></td></tr> <tr><td>Z</td><td></td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA		KL		HP		SSC		SMC		W		Z		PC	
MF																							
SA																							
KL																							
HP																							
SSC																							
SMC																							
W																							
Z																							
PC																							
					<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td></td></tr> <tr><td>KL</td><td></td></tr> <tr><td>HP</td><td></td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td></td></tr> <tr><td>Z</td><td></td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA		KL		HP		SSC		SMC		W		Z		PC	
MF																							
SA																							
KL																							
HP																							
SSC																							
SMC																							
W																							
Z																							
PC																							
 	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome																					

Image	Part Code	Pack	Unit	Application	Colour
 	PAS24 Multi-Point Locks ACSZ024 2170mm Multi-Point Lock Requires: 1 x ACSZ122 F/Height Keep -----OR----- 1 x ACSZ124 F/H Keep + 600mm ACSZ025 1970mm Multi-Point Lock Requires: 1 x ACSZ126 F/Height Keep -----OR----- 1 x ACSZ128 F/H Keep + 600mm ACSZ026 2370mm Multi-Point Lock Requires: 1 x ACSZ130 F/Height Keep -----OR----- 1 x ACSZ132 F/H Keep + 600mm	1	Each	VG520	MF SA KL HP SSC SMC W Z PC
					MF SA KL HP SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome				MF SA KL HP SSC SMC W Z PC

Image	Part Code	Pack	Unit	Application	Colour																		
	BT Lock (Cylinder operated) Lock Sash height ACSZ040 ≤2366 mm. ACSZ041 ≤2700 mm. ACSZ042 ≤3100 mm. Only to lock into outerframe			VG544 VG520	<table border="1" style="float: right;"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td></td></tr> <tr><td>KL</td><td></td></tr> <tr><td>HP</td><td></td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td></td></tr> <tr><td>Z</td><td></td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA		KL		HP		SSC		SMC		W		Z		PC	
MF																							
SA																							
KL																							
HP																							
SSC																							
SMC																							
W																							
Z																							
PC																							
	ACSZ046 Fixing kit and keeps for ACSZ040 to ACSZ042.	1	Pack	ACSZ040 ACSZ041 ACSZ042	<table border="1" style="float: right;"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td></td></tr> <tr><td>KL</td><td></td></tr> <tr><td>HP</td><td></td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td></td></tr> <tr><td>Z</td><td></td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA		KL		HP		SSC		SMC		W		Z		PC	
MF																							
SA																							
KL																							
HP																							
SSC																							
SMC																							
W																							
Z																							
PC																							
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome																						

Image	Part Code	Pack	Unit	Application	Colour
	ACSZ100 Centre Keep	1 20	Each Pack	ACSZ007 ACSZ008 ACSZ009 ACSZ010	MF SA KL HP SSC SMC W Z PC
	ACSZ101 Mushroom Keep	1 20	Each Pack	ACSZ007 ACSZ008 ACSZ009	MF SA KL HP SSC SMC W Z PC
					MF SA KL HP SSC SMC W Z PC
 Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour																		
	ACSZ103 2170mm Full Height Keep for ACSZ007	1	Each	VG520 ACSZ100 ACSZ101	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
	ACSZ105 2770mm Full Height Keep for ACSZ007																						
	ACSZ107 1970mm Full Height Keep for ACSZ008																						
	ACSZ109 2570mm Full Height Keep for ACSZ008																						
	ACSZ111 2370mm Full Height Keep for ACSZ009																						
	ACSZ113 2970mm Full Height Keep for ACSZ009																						
					<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td></td></tr> <tr><td>KL</td><td></td></tr> <tr><td>HP</td><td></td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td></td></tr> <tr><td>Z</td><td></td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA		KL		HP		SSC		SMC		W		Z		PC	
MF																							
SA																							
KL																							
HP																							
SSC																							
SMC																							
W																							
Z																							
PC																							
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome																					

Image	Part Code	Pack	Unit	Application	Colour																		
	PAS24 Multi-Point Keeps ACSZ122 2170mm Full Height Keep for ACSZ024 ACSZ124 2770mm Full Height Keep for ACSZ024 ACSZ126 1970mm Full Height Keep for ACSZ025 ACSZ128 2570mm Full Height Keep for ACSZ025 ACSZ130 2370mm Full Height Keep for ACSZ026 ACSZ132 2970mm Full Height Keep for ACSZ026	1	Each	VG520	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
	ACSZ400 Security Escutcheon	1	Each	ACSZ007-9 ACSZ827 ACSZ836 ACSZ837 ACSZ838 ACSZ839	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
 <small>T-BARS ACVG65=2.5mm ACVL66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black																					

Image	Part Code	Pack	Unit	Application	Colour																		
	ACSZ750 External Flush Finger Pull High Security Handle If installing a pair (ACSZ750 + ACSZ751), please order ACET133 machine screws in addition.	1	Each	ACSZ040 ACSZ041 ACSZ042	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
	ACSZ751 Internal Flush Finger Pull High Security Handle If installing a pair (ACSZ750 + ACSZ751), please order ACET133 machine screws in addition.	1	Each	ACSZ040 ACSZ041 ACSZ042	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
	ACSZ800 External Handle without Cylinder	1	Each	ACSZ007 ACSZ008 ACSZ009 ACSZ010	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
	ACSZ801 Internal Handle without Cylinder	1	Each	ACSZ007 ACSZ008 ACSZ009 ACSZ010	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
	ACSZ802 External Handle with Cylinder	1	Each	ACSZ007 ACSZ008 ACSZ009 ACSZ010	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td>✓</td></tr> <tr><td>KL</td><td>✓</td></tr> <tr><td>HP</td><td>✓</td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td>✓</td></tr> <tr><td>Z</td><td>✓</td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA	✓	KL	✓	HP	✓	SSC		SMC		W	✓	Z	✓	PC	
MF																							
SA	✓																						
KL	✓																						
HP	✓																						
SSC																							
SMC																							
W	✓																						
Z	✓																						
PC																							
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black																					

Image	Part Code	Pack	Unit	Application	Colour
	ACSZ803 Internal Handle with Cylinder	1	Each	ACSZ007 ACSZ008 ACSZ009 ACSZ010	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ823 External Pull Handle	1	Each		MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ827 Internal 'T' Handle with Short Backplate To be used on Internal Sash only	1	Each	ACSZ007 ACSZ008 ACSZ009 ACSZ010	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ830 Internal 'T' Handle with Cylinder Cover To be used on Internal Sash only	1	Each	ACSZ007 ACSZ008 ACSZ009 ACSZ010	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ833 Long Backplate	1	Each	ACSZ800 ACSZ802 ACSZ804 ACSZ835	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	 Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACSZ836 Internal Door Handle with Short Backplate	1	Each	ACSZ007-9 ACSZ837 ACSZ838	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ837 External Door Handle with Short Backplate	1	Each	ACSZ007-9 ACSZ836 ACSZ838	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ839 Escutcheon	1	Each	ACSZ836 ACSZ837	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ841 External Finger Pull Must be used with internal handle.	1	Each	ACSZ801 ACSZ803 ACSZ830	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ850 External Fixed Handle for Secondary Door	1	Each	ACSZ851	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
 ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACSZ851 Internal Fixed Handle for Secondary Door	1	Each	ACSZ850	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ860 External Lift & Slide Handle without Cylinder	1	Each	ACSZ861 ACVG277 ACVG278 ACVG279	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ861 Internal Lift & Slide Handle without Cylinder	1	Each	ACSZ860 ACSZ870 ACSZ871 ACVG277 ACVG278 ACVG279	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ862 External Lift & Slide Handle with Cylinder	1	Each	ACSZ863 ACVG277 ACVG278 ACVG279	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ863 Internal Lift & Slide Handle with Cylinder	1	Each	ACSZ862 ACSZ870 ACSZ871 ACVG277 ACVG278 ACVG279	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
	ACSZ865 M6 Spacing Bush	10	Pack	ACSZ860 ACSZ861 ACSZ862 ACSZ863	MF SA KL HP SSC SMC W Z PC
	ACSZ871 External Short Finger Pull Must Be Used With Internal Handle	1	Each	ACSZ861 ACSZ863 ACVG277 ACVG278 ACVG279	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ882 External Security Handle	1	Each	ACSZ024 ACSZ025 ACSZ026 ACET237	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ883 Internal Security Handle	1	Each	ACSZ024 ACSZ025 ACSZ026 ACET237	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACSZ895L/R Internal Handle with Cylinder Cut-out Note: SA version is RAL9006	1	Each	ACSZ841 ACZS898L/R	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
 R	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm 	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	







Image	Part Code	Pack	Unit	Application	Colour
 R	ACSZ896L/R Internal Handle without Cylinder Cut-out Note: SA version is RAL9006	1	Each	ACSZ841	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
 R	ACSZ897L/R Dummy Internal Handle Note: SA version is RAL9006	1	Each	ACSZ899L/R	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
 R	ACSZ898L/R External Handle with Cylinder Cut-out Note: SA version is RAL9006	1	Each	ACSZ895L/R	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
 R	ACSZ899L/R Dummy External Handle Note: SA version is RAL9006	1	Each	ACSZ897L/R	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACUG123L Sealing Piece	1	Each	UG050 VG516	MF SA KL HP SSC SMC W Z ✓ PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
ACUG123R Sealing Piece		1	Each	UG050 VG516	MF SA KL HP SSC SMC W Z PC
ACUG143 Shootbolt Keep		1	Each	VG581 VG580	MF SA KL HP SSC SMC W Z PC
ACUG160 Sealing Piece		100	Pack	VG516	MF SA KL HP SSC SMC W Z PC
ACUG221 Locking Point For Hautau Lift and Slide		1	Each	Hautau Gearing	MF SA KL HP SSC SMC W Z PC
	ACUG230 Connection Rod for Hautau Lift and Slide	1	Each	Hautau Gearing	MF SA KL HP SSC SMC W Z PC
T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		W = White Z = Black		

Image	Part Code	Pack	Unit	Application	Colour
	ACUG231 Connection Rod for Hautau Lift and Slide	1	Each	Hautau Gearing	MF SA KL HP SSC SMC W Z PC
	ACUG232 Connection Rod for Hautau Lift and Slide	1	Each	Hautau Gearing	MF SA KL HP SSC SMC W Z PC
	ACUG233 Connection Rod for Hautau Lift and Slide	1	Each	Hautau Gearing	MF SA KL HP SSC SMC W Z PC
	ACUG631 Mono Rail	10	Pack	VG610 VG618	MF SA KL HP SSC SMC W Z PC
	ACUG632 Closer Mono-Rail	10	Pack	VG610 VG618	MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	 		

Image	Part Code	Pack	Unit	Application	Colour
	ACUG830 Closer	10	Pack	UG050	MF SA KL HP SSC SMC W Z ✓ PC
	ACUG831 Closer	10	Pack	VG521N	MF SA KL HP SSC SMC W Z ✓ PC
	ACUN020 Rebate Support	10	Pack	VG520 VG521N VG610	MF SA KL HP SSC SMC W Z ✓ PC
	ACUN021 Rebate Support	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACUN033 Inner Glazing Gasket 3 - 5mm	100	Pack		MF SA KL HP SSC SMC W Z ✓ PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black		

Image	Part Code	Pack	Unit	Application	Colour
	ACUN036 Inner Glazing Gasket 6 - 8mm	100	Pack		MF SA KL HP SSC SMC W Z ✓ PC
	ACUN045 Weep Hole Cover	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACUN23X Screw Fixing Lug ACUN230: B = 160MM ACUN232: B = 240MM ACUN233: B = 280MM	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACUN348 Door Stop/Buffer Note: SA version is RAL9006	1	Each	VG520	MF ✓ SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACUN500 Cover Plate	1	Each	UN500 UN510	MF ✓ SA ✓ KL ✓ HP ✓ SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black	 		

Image	Part Code	Pack	Unit	Application	Colour
	ACUN3205 Black Woolpile	100	m	VG551R	MF SA KL HP SSC SMC W Z PC
	ACUN3502 No.8 x 19mm Pan Head Self Tapper	100	Pack		MF SA KL HP SSC SMC W Z PC
	ACUN3523 M6 x 50 CSK Pozi Machine Screw Pack contains 2 screws.	1	Pack	ACSZ750 ACSZ751	MF SA KL HP SSC SMC W Z PC
	ACUN3524 M5 x 30 CSK Pozi Machine Screw	100	Pack	ACSZ040 ACSZ041 ACSZ042	MF SA KL HP SSC SMC W Z PC
	ACUN3610 Single Component Adhesive	1	Each	VG534 VG535 VG536 VG539	MF SA KL HP SSC SMC W Z PC
	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACUN3612 Surface Activator (1L)	1	Each	VG534 VG535 VG536 VG539	MF SA KL HP SSC SMC W Z PC
	ACVG22 Grey Woolpile with Fin Order ACVG22BL for black	100	m	VG511 VG513	MF SA KL HP SSC SMC W Z PC
	ACVG31 3mm Outer Glazing Gasket Note: Order ACVG31S for silicone coating.	200 2400 200	m m m	VG520 VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG31N 3mm Outer Glazing Gasket	200 3600 7200	m m m	VG520 VG521N ...	MF SA KL HP SSC SMC W Z PC
	ACVG32 3mm Inner Glazing Gasket	100 1800 3600	m m m	VG520 VG521N ...	MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm		MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG32N 3mm Inner Glazing Gasket	100 2400	m m	VG520 VG521N	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG33 4mm Inner Glazing Gasket	100 1800 3600	m m m	VG520 VG521N ...	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG33N 4mm Inner Glazing Gasket	100 3000	m m	VG520 VG521N ...	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG34 5mm Inner Glazing Gasket	100 1800 3600	m m m	VG520 VG521N ...	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG34N 5mm Inner Glazing Gasket	100 1800 3600	m m m	VG520 VG521N ...	MF SA KL HP SSC SMC W Z ✓ PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG42 Woolpile H = 5mm	100	m		MF SA KL HP SSC SMC W Z PC
	ACVG45N Weep Hole Cover	100 2500	Pack Pack		MF SA KL HP SSC SMC W ✓ Z ✓ PC
	ACVG81 Fixation Plates For Lock	1	Each	Keeps VG540 VG541 VG542	MF SA KL HP SSC SMC W Z PC
	ACVG131 4mm External Glazing Gasket	100	m	VG520 VG521N	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG131N 4mm External Glazing Gasket	100 5400	m m	VG520 VG521N	MF SA KL HP SSC SMC W Z ✓ PC
Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACVG134 Set Screws For Handle 4 per Pack	1	Pack	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG140 Buffer	1	Pack	ACVG277 ACVG278 ACVG279	MF SA KL HP SSC SMC W Z PC
	ACVG231 2mm Standard External Gasket	200	m	VG520 VG521N ...	MF SA KL HP SSC SMC W Z PC
	ACVG231N 2mm External Glazing Gasket	200 3600	m m	VG520 VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG240 Basic Set Lift & Sliding Door 4 Door	1	Pack	VG542	MF SA KL HP SSC SMC W Z PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
A black metal bracket with a central slot and two side supports.	ACVG268 Connecting Rod Guide Bracket	1	Each	ACVG269 ACVG270 ACVG271 ACVG272 ACVG273	MF SA KL HP SSC SMC W Z PC
A long, thin, straight connecting rod.	ACVG269 Connecting Rod 702mm<W<1278mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
A long, thin, straight connecting rod.	ACVG270 Connecting Rod 1206mm<W<1782mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
A long, thin, straight connecting rod.	ACVG271 Connecting Rod 1710mm<W<2286mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
A long, thin, straight connecting rod.	ACVG272 Connecting Rod 2214mm<W<2790mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
A small T-shaped metal bar. <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	A small screw with a grub slot head.	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		An X-shaped metal bracket. A Y-shaped metal bracket.	

Image	Part Code	Pack	Unit	Application	Colour
	ACVG273 Connecting Rod 2718mm<W<3294mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
	ACVG277 Lock Lift & Sliding Door 1718mm<H<2218mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
	ACVG278 Lock Lift & Sliding Door 2118mm<H<2618mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
	ACVG279 Lock Lift & Sliding Door H<2418mm	1	Each	ACVG280N	MF SA KL HP SSC SMC W Z PC
	ACVG280N Basic Set Lift & Sliding Door <200KG	1	Each	VG521N	MF SA KL HP SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			 	

Image	Part Code	Pack	Unit	Application	Colour
	ACVG281N Double Door Locking Point (Bottom)	1	Each	VG521N ACVG280N	MF SA KL HP SSC SMC W Z PC
	ACVG290 Soft Close Mechanism for Sash Weights ≤ 200KG	1	Each		MF SA KL HP SSC SMC W Z PC
	ACVG291 Fixing Block for Soft Close Mechanism	1	Each	ACVG290 ACVG292	MF SA KL HP SSC SMC W Z PC
	ACVG292 Soft Close Mechanism for Sash Weights ≤ 300KG	1	Each		MF SA KL HP SSC SMC W Z PC
	ACVG300 Support Gasket	25	m	VG510	MF SA KL HP SSC SMC W Z PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
A small, thin, L-shaped metal strip with a serrated edge.	ACVG318 Support Gasket	25	M	VG518	MF SA KL HP SSC SMC W Z ✓ PC
A U-shaped metal strip with a serrated edge, designed for 6mm glazing.	ACVG340 Internal Glazing Gasket 6mm	200 1800	m m	VG520 VG521N	MF SA KL HP SSC SMC W Z ✓ PC
A U-shaped metal strip with a serrated edge, designed for 6mm glazing.	ACVG340N Internal Glazing Gasket 6mm	100 3600	m m	VG520 VG521N	MF SA KL HP SSC SMC W Z ✓ PC
A U-shaped metal cleat with crimped ends for corner applications.	ACVG509 Crimp Corner Cleat	24	Pack	VG510 VG511N	MF SA KL HP SSC SMC W Z PC
A U-shaped metal cleat with integrated mechanical locking features for corner applications.	ACVG510 Mechanical Corner Cleat	24	Pack	VG510 VG511N VG512 VG513	MF SA KL HP SSC SMC W Z PC
ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG515 T-Bracket	4	Pack	VG510 VG516	MF SA KL HP SSC SMC W Z PC
	ACVG515N T-Bracket	4	Pack	VG516 VG518	MF SA KL HP SSC SMC W Z PC
	ACVG516 Supporting Piece	1	Pack	VG510 VG516	MF SA KL HP SSC SMC W Z PC
	ACVG516N Supporting Piece	1	Pack	VG516 VG518	MF SA KL HP SSC SMC W Z PC
	ACVG518 End Part	1	Pack	VG530 VG516	MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG519 End Pieces Floor Profile	1	Pair	VG554	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG520 Stainless Steel Chevron	100	Pack	VG510 VG511N VG512 VG513 VG520	MF ✓ SA KL HP SSC SMC W Z PC
	ACVG521N Crimp Corner Cleat	24	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG521NS Mechanical Corner Cleat	24	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG523 M4 Fixing plate.	50	Pack	VG520	MF SA KL HP SSC SMC W Z PC
	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG524 M5 Fixing Plate.	50	Pack	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG528 Sash Guide	50	Pack	VG520 VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG529 Sash Guide/Anti-Lift Block/Buffer	4	Pack	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG530 Interlock Cover Cap	2	Pack	VG530	MF SA KL HP SSC SMC W Z PC
	ACVG531 Lift & Slide Interlock Cover Cap Black only	2	Pack	VG530	MF SA KL HP SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
ACVG532 Cover Plate		1	Each	VG532 VG533	MF ✓ SA KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
ACVG533 VG533 End Cap with Screws		2	Pack	VG532 VG533	MF SA KL HP SSC SMC W ✓ Z ✓ PC
ACVG534 Sash Drainage Spout Black Only		10	pack	VG520 VG521N	MF SA KL HP SSC SMC W Z ✓ PC
ACVG535 End Cap with Upstand		1	Pair	VG534 VG536	MF SA KL HP SSC SMC W ✓ Z ✓ PC
ACVG536 VG536 Slim Interlock End Cap		1	Pair	VG534 VG536	MF SA KL HP SSC SMC W ✓ Z ✓ PC
T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		W = White Z = Black	 	

Image	Part Code	Pack	Unit	Application	Colour
	ACVG537 30 x 4mm Adhesive Foam Tape Store at room temperature away from direct sun light	20M	each	VG534 VG535 VG536 VG539	MF SA KL HP SSC SMC W Z PC
	ACVG539 VG539 End Cap	1	Pair	VG539	MF SA KL HP SSC SMC W ✓ Z ✓ PC
	ACVG540 Meeting Stile End Cap with Brush Pile	2	Pack	VG540 VG541	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG541 End Cap for VG541 2 Per Set	1	Pair	VG541 ACVG540	MF SA KL HP SSC SMC W ✓ Z ✓ PC
	ACVG542 Low Friction Gasket	100	m	VG520 VG521N	MF SA KL HP SSC SMC W Z ✓ PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			







Image	Part Code	Pack	Unit	Application	Colour
	ACVG543 End Part Double Casement Profile	2	Pack	VG542	MF SA KL HP SSC SMC W Z PC
	ACVG544 Support Block for Sash	10	Pack	VG520	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG545 Security Device	2	Pack	VG520 VG540 VG541	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG546 Top Guide/Anti-Lift Block for Slim Interlock	4	Pack	VG535 VG536 VG539	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG547 Slim Interlock Fixing Bracket	8	Pack	VG520 VG535 VG536 VG539	MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG548 Slim Interlock Fixing Bracket for Lift & Slide	8	Pack	VG521N VG534 VG535 VG536 VG539	MF SA KL HP SSC SMC W Z PC
	ACVG550 Adjustable Full Height Keep for ACSZ007 only Available in powder coated or silver anodised finish. Not covered by Kitemark.	1	Each	ACSZ007	MF SA ✓ KL ✓ HP ✓ SSC SMC W ✓ Z ✓ PC
	ACVG555 Adjustable Roller Max Weight 250kg / pair	1	Each	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG556 End Cap for VG556	10	Pairs	VG556	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG557N Glass support	50	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
 Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG558 Head Extension Packer	10	Pack	VG558 VG559 VG570	MF SA KL HP SSC SMC W Z PC
	ACVG559 Bridge Packer	20	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG560 Foam Infill for VG520 1250mm Lengths	1	Each	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG561 Foam Infill for Glass Perimeter	100	m	VG520 VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG562 Foam Infill for VG530 1250mm Lengths	1	Each	VG530	MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black	 		

Image	Part Code	Pack	Unit	Application	Colour
x 2	ACVG563 VG519 Interlock Seal	1	Pair	VG519	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG565 Fixed Double Roller Max Weight 250kg / pair	1	Each	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG569 End Caps for VG549 Contains: 1 pair End Caps 2 Self Adhesive Brushes 4 Screws	1	pair	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG571 Lock Fixing Support	1	Each	VG520	MF SA KL HP SSC SMC W Z ✓ PC
	ACVG575 Support For VG575	20	Pack	VG575 UG050	MF ✓ SA KL HP SSC SMC W Z PC
T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG576 Gasket for Floating Corner	150	m	VG580 VG581	MF ✓ SA KL HP SSC SMC W Z PC
	ACVG580 Keep Fixing Plates	1	Pack	VG540 VG542	MF SA KL HP SSC SMC W Z PC
	ACVG581 Cast End Caps for VG580 & VG581	1	Pack	VG580 VG581	MF SA KL HP SSC SMC W ✓ Z ✓ PC
	ACVG582 VG539 End Cap with Upstand	1	Pair	VG539	MF SA KL HP SSC SMC W Z PC
	ACVG590 90° Corner Cleat Pack Contains: 4 x Corner Cleats 16 x Screws	1	Pack		MF SA KL HP SSC SMC W Z PC
 ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG610 Crimp Corner Cleat	24	Pack	VG610	MF SA KL HP SSC SMC W Z PC
	ACVG610S Mechanical Corner Cleat	24	Pack	VG610	MF SA KL HP SSC SMC W Z PC
	ACVG617 Crimp Corner Cleat	24	Pack	VG518	MF SA KL HP SSC SMC W Z PC
	ACVG617S Mechanical Corner Cleat	24	Pack	VG610 VG518	MF SA KL HP SSC SMC W Z PC
	ACVG618 Crimp Corner Cleat	24	Pack	VG618	MF SA KL HP SSC SMC W Z PC
 	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	 			

Image	Part Code	Pack	Unit	Application	Colour
ACVG618S Mechanical Corner Cleat		24	Pack	VG618	MF SA KL HP SSC SMC W Z PC
ACVG644 Vent Support		10	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
ACVG645N Vent Support Add-on For ACVG644		2	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
ACVG740 VG521N Fixings		20	Pack	VG521N VG542	MF SA KL HP SSC SMC W Z PC
ACVG752 Corner Shootbolt		2	Pack	ACSZ007 ACSZ008 ACSZ009 ACSZ024 ACSZ025 ACSZ026 VG520	MF SA KL HP SSC SMC W Z PC
T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG873 Hook Lock & Keep	1	Each	VG520	MF SA KL HP SSC SMC W Z PC
	ACVG900 Punch Unit	1	Each		MF SA KL HP SSC SMC W Z PC
	ACVG905 Punch Tool (Modified ACGS160A tools may also be used)	1	Each		MF SA KL HP SSC SMC W Z PC
	ACVG950 Drill Jig T-Connection	1	Each	VG516	MF SA KL HP SSC SMC W Z PC
	ACVG951 Drill Jig Drainage	1	Each	VG510	MF SA KL HP SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black	 		
Screw (Grub)					

Image	Part Code	Pack	Unit	Application	Colour
	ACVG952 Drill Jig - Downward Drainage	1	Each	VG510 VG511N VG512 VG513 VG518 VG612	MF SA KL HP SSC SMC W Z PC
	ACVG953 Drill Jig Drainage	1	Each	VG510 VG511N VG618	MF SA KL HP SSC SMC W Z PC
	ACVG1220 Additional Hautau Lift And Slide keep	1	Each	VG510 VG511	MF SA KL HP SSC SMC W Z PC
	ACVG1222 Additional Hautau Lift And Slide night ventilation keep	1	Each	VG510 VG511	MF SA KL HP SSC SMC W Z PC
	ACVG1240 Basic Hautau Lift And Slide Sash to Sash lock set.	1	Each	VG542	MF SA KL HP SSC SMC W Z PC
 ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACVG1274 Additional Double Roller Set.	1	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG1275 Fixing Plate Hautau Lift and Slide	20	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
					MF SA KL HP SSC SMC W Z PC
Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			

Image	Part Code	Pack	Unit	Application	Colour																		
	ACVG1277 Hautau Lock for Sash Height 1877 - 2176mm	1	Each	VG521N	<table border="1"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td></td></tr> <tr><td>KL</td><td></td></tr> <tr><td>HP</td><td></td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td></td></tr> <tr><td>Z</td><td></td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA		KL		HP		SSC		SMC		W		Z		PC	
MF																							
SA																							
KL																							
HP																							
SSC																							
SMC																							
W																							
Z																							
PC																							
	ACVG1278 Hautau Lock for Sash Height 2177 - 2476mm																						
	ACVG1279 Hautau Lock for Sash Height 2477 - 2776mm																						
 	T-BARS ACVG66=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 																			

Image	Part Code	Pack	Unit	Application	Colour
	ACVG1280 Basic Lift And Slide kit (Max 250KG)	1	Pack	VG521N	MF SA KL HP SSC SMC W Z PC
	ACVG1282N Roller Support Block	10	Pack	VG521N VG516	MF SA KL HP SSC SMC W Z PC
	ACVL029 Strengthening Piece For T-Connection	1 2500 5000	Each Pack Pack	VG620 VG621	MF SA KL HP SSC SMC W Z PC
					MF SA KL HP SSC SMC W Z PC
					MF SA KL HP SSC SMC W Z PC
					MF SA KL HP SSC SMC W Z PC
	Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			

Image	Part Code	Pack	Unit	Application	Colour																		
	ACUG230 Hautau Lift And Slide Connecting Rod. For ACVG1280 with sash width 650 - 1360 and ACVG1280 + ACVG1274 with Sash Width 1120 - 1800	1	Each	ACVG1280 ACVG1274	<table border="1" style="float: right;"> <tr><td>MF</td><td></td></tr> <tr><td>SA</td><td></td></tr> <tr><td>KL</td><td></td></tr> <tr><td>HP</td><td></td></tr> <tr><td>SSC</td><td></td></tr> <tr><td>SMC</td><td></td></tr> <tr><td>W</td><td></td></tr> <tr><td>Z</td><td></td></tr> <tr><td>PC</td><td></td></tr> </table>	MF		SA		KL		HP		SSC		SMC		W		Z		PC	
MF																							
SA																							
KL																							
HP																							
SSC																							
SMC																							
W																							
Z																							
PC																							
	ACUG231 Hautau Lift And Slide Connecting Rod. For ACVG1280 with sash width 1361 - 1860 and ACVG1280 + ACVG1274 with Sash Width 1801 - 2300																						
	ACUG232 Hautau Lift And Slide Connecting Rod. For ACVG1280 with sash width 1861 - 2360 and ACVG1280 + ACVG1274 with Sash Width 2301 - 2800																						
	ACUG233 Hautau Lift And Slide Connecting Rod. ACVG1280 + ACVG1274 with Sash Width 2801 - 3235																						
 	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			 																			

Image	Part Code	Pack	Unit	Application	Colour
A grey rectangular woolpile component.	ACVL033 Woolpile H = 8mm	50	m		MF SA KL HP SSC SMC W Z PC
A cylindrical metal clip.	ACVL058 Clip	50	Pack	VL70	MF SA KL HP SSC SMC W Z PC
Two white plastic end caps.	ACVL059 End Cap for VL72	1	Pair	VL72	MF SA KL HP SSC SMC W ✓ Z ✓ PC
A rivet with a hexagonal head and a threaded shank.	ACVL061 Rivet For VL72	100	Pack		MF SA KL HP SSC SMC W Z PC
A grey metal T-jig with two mounting holes.	ACVL162 Drill Jig T-Connection	1	Each	VG510 VG515 ACVG515N	MF SA KL HP SSC SMC W Z PC
A small image of a T-bar. <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black	A diagram showing an X-shaped bracket.	A diagram showing a Y-shaped bracket.	
A small image of a grub screw.					

Image	Part Code	Pack	Unit	Application	Colour	
	ACVS033 Woolpile With Fin Black or White H = 9mm W = 4.8mm	150	m	VG520 VG521N	MF SA KL HP SSC SMC W ✓ Z ✓ PC	
	ACVS034 Woolpile With Fin Black or White H = 6.5mm W = 4.8mm	150	m	VG551R	MF SA KL HP SSC SMC W ✓ Z ✓ PC	
	ACVS061 M5 x 40 Countersunk Screw	100	pack		MF SA KL HP SSC SMC W Z PC	
	ACVS062 Countersunk Polyamide Sash Screw	1000	pack		MF SA KL HP SSC SMC W Z PC	
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm		Screw (Grub)		MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	

Visoglide Plus

Image	Part Code	Pack	Unit	Application	Colour
	ACMX09700 Alu-Polish Cleaning emulsion for aluminium oxide.	1	each		MF ✓ SA KL HP SSC SMC W Z PC
	ACMX09761 Maxi Gloss Protection for painted and anodised surfaces.	1	each		MF SA KL HP SSC SMC W Z PC
	ACMX09762 Alu. Bright Cleaner for rough, anodised or enamelled aluminium frames.	1	each		MF SA KL HP SSC SMC W Z PC
	ACMX09763 Teflon Spray Lubricant	1	each		MF SA KL HP SSC SMC W Z PC
	ACMX09764 Maxi Cleaner For cleaning oily surfaces.	1	each		MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm Screw (Grub)	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome	W = White Z = Black			



Visoglide Plus

Image	Part Code	Pack	Unit	Application	Colour
	ACMX09765 Glue Cleaner De-grease and silicone remover.	1	each		MF SA KL HP SSC SMC W Z PC
	ACMX09770 Roll & Wrap 100mm	1	each		MF SA KL HP SSC SMC W Z PC
	ACMX09775 Grip Handwrap	1	each		MF SA KL HP SSC SMC W Z PC
	ACMX09801 Protective Tape 50mm	1	each		MF SA KL HP SSC SMC W Z PC
	ACMX09802 Protective Tape 70mm	1	each		MF SA KL HP SSC SMC W Z PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome			 	

Visoglide Plus

Image	Part Code	Pack	Unit	Application	Colour
	ACMX09803 Protective Tape 100mm	1	each		MF SA KL HP SSC SMC W Z PC
	ACSIL05 Rubber Sealant	1	each		MF SA KL HP SSC SMC W Z PC
	ACSIL04 Sealing Glue Order with suffix of KL colour (eg. ACSIL04KL005) or BL=Black/WP=White/ CL=Clear	1	each		MF SA KL ✓ HP SSC SMC W ✓ Z ✓ PC
	ACSIL08 Silicon Gun	1	each		MF SA KL HP SSC SMC W Z PC
	ACSIL013 Glue for Mitre	1	each		MF SA KL HP SSC SMC W Z PC
	T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm		MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		

Visoglide Plus

Image	Part Code	Pack	Unit	Application	Colour
	ACSL014 Anti-Corrosion Coating	1	each		MF ✓ SA KL HP SSC SMC W Z PC
	ACUN3900 Gasket Roller	1	Each	Wedge Gaskets	MF SA KL HP SSC SMC W Z PC
					MF SA KL HP SSC SMC W Z PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	 Screw (Grub)	MF = Mill Finish W = White SA = Silver Anodised Z = Black KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome		 	


Section C

Sections

Scale Elevations



Section C

Scale Elevations




Do Not Scale From This Drawing

Detail 1A




Do Not Scale From This Drawing

Detail 1B




Do Not Scale From This Drawing

Detail 1C




Do Not Scale From This Drawing

Detail 1D




Do Not Scale From This Drawing

Detail 1E




Do Not Scale From This Drawing

Detail 2A




Do Not Scale From This Drawing

Detail 2B



Do Not Scale From This Drawing



Detail 2C



Do Not Scale From This Drawing



SECTIONS

Detail 3A



Do Not Scale From This Drawing



Detail 3B



Do Not Scale From This Drawing



SECTION

Detail 3C





Do Not Scale From This Drawing

Detail 3D




Do Not Scale From This Drawing

Detail 4A



Do Not Scale From This Drawing


Detail 4B



Do Not Scale From This Drawing


SECTION

Detail 4C




Do Not Scale From This Drawing

Detail 4D




Do Not Scale From This Drawing

Detail 4E



Do Not Scale From This Drawing



Detail 4F



Scale 1:0.8


Do Not Scale From This Drawing

Detail 5A




Do Not Scale From This Drawing

Detail 5B




Do Not Scale From This Drawing

Detail 5C




Important Note:
VG549 can only be used with BT Lock



Do Not Scale From This Drawing


Detail 5D



Do Not Scale From This Drawing


SECTIONS

Detail 5E



Do Not Scale From This Drawing


Detail 5F



Important Note:
VG549 can only be used with BT Lock


Do Not Scale From This Drawing

Detail 6




Do Not Scale From This Drawing

Detail 7A




Do Not Scale From This Drawing

Detail 7B




Do Not Scale From This Drawing

Detail 7C




Do Not Scale From This Drawing

Detail 7D




Do Not Scale From This Drawing

Detail 8A



Do Not Scale From This Drawing


Detail 8B



Do Not Scale From This Drawing


SECTIONS

Detail 8C




Do Not Scale From This Drawing

Detail 9A




Do Not Scale From This Drawing

Detail 9B





Do Not Scale From This Drawing

Detail 9C




Do Not Scale From This Drawing

Detail 10



Do Not Scale From This Drawing


Detail 11



Do Not Scale From This Drawing





SECTION

Detail 12




Do Not Scale From This Drawing

Scale Elevations




Do Not Scale From This Drawing

Detail 13A





Do Not Scale From This Drawing

Detail 13B





Do Not Scale From This Drawing

Detail 14




Do Not Scale From This Drawing

Detail 15A




Do Not Scale From This Drawing

Detail 15B




Do Not Scale From This Drawing

Detail 15C



Do Not Scale From This Drawing


Detail 15D



Scale 1:0.8


Do Not Scale From This Drawing

Detail 16




Do Not Scale From This Drawing

Detail 17




Do Not Scale From This Drawing

Detail 18





Do Not Scale From This Drawing

Detail 19




Do Not Scale From This Drawing

Detail 20



Do Not Scale From This Drawing


Scale Elevations



Sloped Cill Mono Rail


Do Not Scale From This Drawing

Detail 21




Do Not Scale From This Drawing

Detail 22




Do Not Scale From This Drawing

Detail 23




Do Not Scale From This Drawing

Detail 24




Do Not Scale From This Drawing

Detail 25




Do Not Scale From This Drawing

Detail 26



Do Not Scale From This Drawing


Scale Elevations



Mono Rail with Glazed Outer Frame


Do Not Scale From This Drawing

Detail 27




Do Not Scale From This Drawing

Detail 28




Do Not Scale From This Drawing

Detail 29




Do Not Scale From This Drawing

Detail 30




Do Not Scale From This Drawing

Detail 31




Do Not Scale From This Drawing

Detail 32



Do Not Scale From This Drawing

Detail 33



Do Not Scale From This Drawing



Do Not Scale From This Drawing

Section D

Statics


General Size Limitations are shown on Page A07.

**If in doubt, please contact
the technical department - T: 01934 876100**

STATICS

Section D


GENERAL INFORMATION - STATICS



The position of the axes is an indication for the use and application of the moments of inertia (I_x and I_y) and the section modulus (W_x and W_y). We always choose the values of the axis perpendicular to the load to resist it.

- To resist the wind loads we use the values I_x and W_x .

EXAMPLE



$$H = 250\text{cm}$$

$$W_1 = 100\text{cm}$$

$$W_2 = 100\text{cm}$$

$$P = 1000 \text{ Pa (wind pressure)}$$

- 1) Determine I_{xx} value for the interlock and meeting stile (if required) using the Specification Wizard

$$I_{xx} = 58.1 \text{ cm}^4$$

- 2) Determine profile combinations

OK


			52 cm ⁴		88.5 cm ⁴		111 cm ⁴	
			88 cm ⁴	*	124 cm ⁴		147 cm ⁴	

Do Not Scale From This Drawing

STATICS

Section D

PROFILE COMBINATIONS - IX SLIDE : STATICS




	VG530 VG520 VG551R	VG530 VG520 VG551R	VG532 VG533 VG520 VG551R	UN500 UN510 VG520 VG551R	UN500 UTL080 VG530 VG520 VG551R
VG551R VG520 VG530	52 cm4	88.5 cm4	111 cm4	147 cm4	
VG551R VG520 VG533 VG532	88 cm4	124 cm4	147 cm4	183 cm4	
VG551R VG520 VG530 UN510 UN500	111 cm4	147 cm4	171 cm4	206 cm4	
VG551R VG520 VG530 UN510 UTL080 UN500	147 cm4	183 cm4	206 cm4	242 cm4	

See Page D.07 for Slim Interlock Mass Properties

Do Not Scale From This Drawing

Section D

PROFILE COMBINATIONS - IX LIFTSIDE : STATICS



	VG530 VG521N VG533N	VG532 VG530 VG521N VG533N	UN500 VG530 VG521N VG533N	UTL080 VG530 VG521N VG533N
VG553N VG521N VG530	67 cm4	102 cm4	125 cm4	169 cm4
VG553N VG521N VG532 VG530 VG533	102 cm4	137 cm4	160 cm4	204 cm4
VG553N VG521N VG530 UN510 UN500	125 cm4	160 cm4	184 cm4	227 cm4
VG553N VG521N UTL080 VG530 UN510 UN500	169 cm4	204 cm4	227 cm4	271 cm4


See Page D.07 for Slim Interlock Mass Properties

Do Not Scale From This Drawing

STATICS

Section D

PROFILE COMBINATIONS - IX-MONO-SLIDE : STATICS





	VG630	VG532 VG630 VG620 VG551R	VG533 VG630 VG620 VG551R	UN500 UN510 VG630 VG620 VG551R	UTL080 VG630 UN510 VG620 VG551R
VG551R VG520 VG530	92 cm4	156 cm4	191 cm4	253 cm4	
VG551R VG520 VG533 VG532	128 cm4	192 cm4	227 cm4	289 cm4	
VG551R VG520 VG530 UN510 UN500	151 cm4	215 cm4	251 cm4	312 cm4	
VG551R VG520 UN510 UTL080 UN500	187 cm4	251 cm4	286 cm4	348 cm4	

Do Not Scale From This Drawing

Section D

PROFILE COMBINATIONS - IX-SLIM INTERLOCKS : STATICS



49 cm4


73 cm4

182 cm4

Do Not Scale From This Drawing

Section D

PROFILE COMBINATIONS - IX MONO-LIFTSIDE : STATICS




	VG630 VG621 VG53N	VG630 VG621 VG53N	UN500 UN510 VG630 VG621 VG53N	UTL080 VG630 VG621 VG53N
VG521N VG530	109 cm4	176 cm4	214 cm4	287 cm4
VG521N VG530 VG532 VG533	144 cm4	211 cm4	249 cm4	322 cm4
VG521N VG530 UN510 UN500	168 cm4	235 cm4	273 cm4	346 cm4
VG521N VG530 UN510 UN500 UTL080	211 cm4	278 cm4	316 cm4	389 cm4

Do Not Scale From This Drawing

Section D

PROFILE COMBINATIONS - IX-DOUBLE CASEMENT : STATICS



	VG542	59 cm4		VG549
	VG542 UN510 UN500	142 cm4		VG549 UN510 UN500
	VG542 UN510 UTL080 UN500	210 cm4		VG549 UN510 UTL080 UN500
		209 cm4		


	VG540	48 cm4
	VG541	127 cm4

Do Not Scale From This Drawing

STATICS

Section D

PROFILE COMBINATIONS - IX-DOUBLE CASEMENT : STATICS



 VG521N VG542	70 cm4
 VG521N VG542 UN510 UN500	157 cm4
 VG521N VG542 UN510 UTL080 UN500	230 cm4

Do Not Scale From This Drawing


Section E

Construction Drawings

E VG+

Punch Tool Details.....	E03 - E04
Drainage Details.....	E05 - E08
Sash Transom Details.....	E09
Roller Preparation & Fixing.....	E10 - E11
Multi-Point Lock Preparation & Installation.....	E12 - E14
BT Lock Preparation & installation.....	E15 - E17
Lock & Handle Overview.....	E18 - E20
Interlock Details.....	E21 - E27
Sash to Sash Locking Stile.....	E28 - E32
VG632 Locking Detail.....	E33
Sash Installation.....	E34
ACVG528 Position Details.....	E35
Fixed Sash Installation.....	E36
ACUG830 Fixing Detail.....	E37
VG514 & VG515 Cutting & Fitting.....	E38
VG519 Assembly.....	E39 - E40
Sobinco Lift & Slide Hardware Overview.....	E41
Sobinco Lift & Slide Lock & Handle Preparation Details.....	E42 - E47
Hautau Lift & Slide Hardware Overview.....	E48
Hautau Lift & Slide Lock & Handle Preparation Details.....	E49 - E52
Hautau Soft Close Mechanism.....	E53 - E55
Lift & Slide Slim Interlock Preparation.....	E56
VG516/VG518 Details & Installation.....	E57 - E59
Monorail Assembly.....	E60 - E62
Head Extension Fitting Details.....	E63
Glazing Chart.....	E64 - E68
PAS24:2016 Overview	E69
ACUN348 Buffer.....	E70
Floating Corner Assembly.....	E71 - E74
VG651 - VG655 Bay Pole Adapters.....	E75

ACVG905 Punch Tool Sections




Do Not Scale From This Drawing

Visoglide Plus


ACVG900 Punch Tool Details

Position 5





VG521N

VG521N




Please Note: ACVG900 will not punch the 25 X 14.5mm cut out in VG630.

Position 4




VG610
VG618







Position 1, 2 & 3




Notch VG551R to clear end prep of VG530




Outer Frame Drainage Details




Alternative Drainage Method








Do Not Scale From This Drawing

Visoglide Plus**Cill Drainage Details**

VG575 Drainage Track Infill Detail




Ensure at least 1 x Ø8mm drainage hole between ACVG575 supports





Do Not Scale From This Drawing

Visoglide Plus




Vent Drainage & Decompression



Decompression




Drainage



Do Not Scale From This Drawing

VG538 Sash Transom




Do Not Scale From This Drawing

VG520 Roller Preparation & Fixing


ACVG555 Adjustable Roller

Max Sash Weight: 250kg



ACVG565 Fixed Roller

Max Sash Weight: 250kg




Do Not Scale From This Drawing

VG521N Roller Preparation & Fixing

**ACVG555 Adjustable Roller (shown) or
ACVG565 Fixed Roller**


Max Sash Weight: 250kg



Do Not Scale From This Drawing





Visoglide Plus

Multi-Point Lock Preparation & Installation



Do Not Scale From This Drawing

ACSZ024, 025 & 026 with ACSZ882 & ACSZ883 Preparation & Installation





Note:
ACVG529 cannot be used with
PAS24 locks & keeps. Use ACVG528
to centralise the head of sash.



ACVG752 Shootbolt

Note:


ACVG529 cannot be used with
ACVG752 shootbolts. Use ACVG528
to centralise the head of sash.




ACVG752



Sash Routing Detail




Route 45mm x 11mm of the
polyamide in sash at both head and
cill to allow for shootbolt to operate.



Important Note:

ACVG752 shootbolts cannot be used on sash heights over 2423mm or under 1824mm.


ACVG752 shootbolts should be fitted before
fitting the lock.



Do Not Scale From This Drawing

ACSZ040, ACSZ041 & ACSZ042 Details


Diagram below shows VG520 sash only.



Do Not Scale From This Drawing


Visoglide Plus

ACSZ040, ACSZ041 & ACSZ042 Details




Lock Kit	L	A	B
ACSZ040	2300	300	240
ACSZ041	2700	400	340
ACSZ042	3100	500	440

1. The lock is cut to size together with the rods without removing any parts.
2. The cylinder height can be reduced by cutting up to 741mm from the bottom of the lock.



ACSZ046 - Fixing Kit Contents

2 No. Tapping plates.	1.No Lock body* (Includes cylinder screw)
1 Each Fixing brackets.	13.No No.8 x 1"CSK stainless steel screw.
4.No Machine screws for fixing brackets.	9.No 3mm Spacer.
1 Each Plastic keeps.	2.No Threaded end for shootbolt rods.
2.No Stainless steel adjustment plate.	2.No Plastic shoot bolt rods.




BT Lock Meeting Stile Detail


Important Note:

Fix ACSZ040, ACSZ041 or ACSZ042 to the sash using detail on previous page before fixing the meeting stile in place.

Outer Frame Prep Top & Bottom



See page E32 for VG549 End Prep Details



Do Not Scale From This Drawing

Sash to Outer Frame Locking


VG510 (VG511N) (VG518) - VG520

SASH HEIGHT	LOCKS	KEEPS			
		INDIVIDUAL KEEPS		FULL HEIGHT KEEP	FULL HEIGHT KEEP + 600mm
MIDDLE	TOP / BOTTOM				
2024 - 2223	ACSZ024			ACSZ122	ACSZ124
1824 - 2023	ACSZ025			ACSZ126	ACSZ128
2224 - 2423	ACSZ026			ACSZ130	ACSZ132
2024 - 2223	ACSZ007	ACSZ100	ACSZ101	ACSZ103	ACSZ105
1824 - 2023	ACSZ008			ACSZ107	ACSZ109
2224 - 2500*	ACSZ009			ACSZ111	ACSZ113
	ACSZ10				
≤ 2366mm	ACSZ040				
≤ 2766mm	ACSZ041				
≤ 3166mm	ACSZ042				
EXT.	INT.	ACSZ046	ACMX209		
Lever Handles	ACSZ800 X	ACSZ801 X	ACMX009		
		ACSZ803 Ø			
		ASCZ802 TØ			
'D' Handles	ACSZ898 Ø (L/R)	ACSZ895 Ø (L/R)	ACMX009	ACIM442	
		ACSZ899 X (L/R)		ACMX0040	
		ACSZ896 X (L/R)			
No External Handle	ACSZ400 + 2 x ACVS061	ACSZ803 Ø	ACMX009	ACIM442	ACVS061 & ACMX867
		ACSZ830 TØ			
		ACSZ895 Ø (L/R)			
Pull Handle without External Cylinder	ACSZ823	ACSZ801 X	ACMX009	ACMX0040	ACSG070
		ACSZ803 Ø			
		ACSZ830 TØ			
Flush Pull Handle without External Cylinder	ACSZ841	ACSZ801 X	ACMX009	ACMX0040	ACET220
		ACSZ803 Ø			
		ACSZ830 TØ			


* ACVG752 shootbolts cannot be used on sash heights over 2423mm.

	2 x ACVS061		2 x WCA134		
EXT.		INT.			
External Lever Handle with Internal Lever Handle	ACSZ837	ACSZ400		ACMX209	ACIM442
				ACMX3040	ACSG070
		ACSZ400		ACMX009	ACIM442
				ACMX3040	ACVS061
External Lever Handle with Internal 'T' Handle	ACSZ837	ACSZ400		ACMX209	ACIM442
				ACMX3040	ACSG070
		ACSZ400		ACMX009	ACIM442
				ACMX3040	ACVS061

*To be used on Internal Sash only



For full details to achieve PAS24:2016,
please see page E68 & Test Report
8247857




Shootbolt Lock Only.

With Cylinder
Without Cylinder
T Handle With Cylinder

LIFT & SLIDE


LIFT & SLIDE					
EXT.	INT.				
ACSZ860 X	ACSZ861 X	ACMX1138* (SOBINCO LOCK)	ACMX0040		ACET235
		ACSZ863 Ø	ACIM442		
ACSZ862 Ø	ACSZ861 X	ACMX1130* (HAUTAU LOCK)			
		ACSZ863 Ø			
ACSZ871	ACSZ861 X	ACMX1070 (SOBINCO LOCK)	ACMX0040		
		ACSZ863 Ø	ACIM442		
ACSZ871 & ACSZ400		ACMX1075 (HAUTAU LOCK)			

* Spindles need to be cut down. See details below.




Do Not Scale From This Drawing

(VG511N)
(VG510)
VG518




ACMX1138 - 138mm Spindle



Notch to outside
Cut down spindle by 25mm from side indicated above.

ACMX1130 - 130mm Spindle



Notch to outside
Cut down spindle by 17mm from side indicated above.

Sash to Sash Locking

VG520 + VG540 - VG520

SASH HEIGHT	LOCKS	KEEPS			
		INDIVIDUAL KEEPS		FULL HEIGHT KEEP	FULL HEIGHT KEEP + 600mm
		MIDDLE	TOP / BOTTOM	ACSZ122	ACSZ124
2024 - 2223	ACSZ024			ACSZ122	ACSZ124
1824 - 2023	ACSZ025			ACSZ126	ACSZ128
2224 - 2423	ACSZ026			ACSZ130	ACSZ132
2024 - 2223	ACSZ007	ACSZ100	ACSZ101	ACSZ103	ACSZ105
1824 - 2023	ACSZ008			ACSZ107	ACSZ109
2224 - 2500*	ACSZ009			ACSZ111	ACSZ113
	ACSZ010				
		EXT.	INT.		3 x
Lever Handles	ACSZ800 X	ACSZ801 X	ACMX209		
		ACSZ803 Ø	ACIM442		
		ACSZ830 TØ			
'D' Handles	ACSZ898 (L/R)	ACSZ895 (L/R)	ACMX209	ACIM442	
		ACSZ896 (L/R) X	ACMX0040		
No External Handle	ACSZ400 + 2 x ACVS061	ACSZ803 Ø	ACMX009	ACIM442	ACVS061 & ACMX867
Pull Handle without External Cylinder	ACSZ823	ACSZ801 X	ACMX009	ACMX0040	ACSG070
Flush Pull Handle without External Cylinder	ACSZ841	ACSZ803 Ø	ACMX009	ACMX0040	ACET220
		ACSZ830 TØ			

* ACVG752 shootbolts cannot be used on sash heights over 2423mm.


EXT.	2 x ACVS061	2 x WCA134	INT.	ACCSZ836	ACCSZ839	ACCSZ827
	ACSZ837	ACSZ400				
	ACSZ837	ACSZ400				
External Lever Handle with Internal Lever Handle	ACSZ837	ACSZ400	ACCSZ836	ACCSZ839	ACCSZ827	ACCSZ827
External Lever Handle with Internal 'T' Handle	ACSZ837	ACSZ400				
	ACSZ837	ACSZ400				

For full details to achieve PAS24:2016, please see page E68 & Test Report 8247857


- With Cylinder
- X Without Cylinder
- T Handle With Cylinder

PAS24:2016


PAS24:2016




PAS24:2016




ACSZ851
ACSZ897 (L/R)




ACSZ850
ACSZ899 (L/R)



ACMX1138 - 138mm Spindle



ACMX1130 - 130mm Spindle



Sash to VG632 Locking

VG520 + VG632 - VG520


SASH HEIGHT	LOCKS	KEEPS			
		INDIVIDUAL KEEPS		FULL HEIGHT KEEP	FULL HEIGHT KEEP + 600mm
		MIDDLE	TOP / BOTTOM	ACSZ103	ACSZ105
2024 - 2223	ACSZ007			ACSZ103	ACSZ105
1824 - 2023	ACSZ008			ACSZ107	ACSZ109
2224 - 2500*	ACSZ009			ACSZ111	ACSZ113
	ACSZ010				
	EXT.	INT.			3 x
Lever Handles		ACSZ801 X			
		ACSZ803 T			
		ACSZ830 T			
'D' Handles		ACSZ895 (L/R)		ACVS061 & ACMX867	
		ACSZ896 (L/R) X			

* ACVG752 shootbolts cannot be used on sash heights over 2423mm.

	2 x ACVS061	2 x WCA134			
Internal Lever Handle			ACSZ836		
Internal 'T' Handle			ACSZ839	ACMX009	ACMX0040


ACSG070 & ACMX867

Not Security Tested



Do Not Scale From This Drawing

Interlock Reinforcement Details




Do Not Scale From This Drawing


Visoglide Plus

Slim Interlock Details


VG520 Preparation



Slim Interlock Stile Preparation





Slim Interlock Cover Cap Preparation



Do Not Scale From This Drawing



VG537 Preparation with VG536 or VG539



Do Not Scale From This Drawing


Visoglide Plus

VG537 Preparation with VG536 or VG539 (Continued)




Do Not Scale From This Drawing

Slim Interlock Assembly




Do Not Scale From This Drawing

Slim line Interlock Bonding Method



ACUN3610 is a high quality single component adhesive that provides a strong bond between the Butyl sealed unit and frame.

We recommend glazing the sash in the workshop at least a day before installation so it can be allowed to set.




Bonding:

After preparation, apply ACUN3610 single component sealant into gap between frame and glass as detailed below (Detail A)

ACUN3610 must be applied to the full height of the unit.

Pack glass to ensure it is positioned correctly within the sash. A sash clamp should be used to ensure the interlock is held flat while ACUN3610 sets.

Leave to set overnight.



Do Not Scale From This Drawing

Slim line Interlock Tape Method

It is strongly recommended that where possible the bonding method on page E25 is used as this provides a stronger bond.

Where workshop glazing is not possible ACVG537 30 x 4mm adhesive glazing tape must be used.

ACVG537 needs be applied to the full height of the glazing chamber of any of the slim interlocks (VG534*, VG535, VG536 or VG539). The adhesion between the glass and the frame prevents any visible deflection of the profile.


*Where VG534 is used on both sides of a sash, it must be factory glazed. The VG534 jambs need to be bonded and assembled around the unit.



It is advised that ACMX09765 Aluminum cleaner is used to clean the area of adhesion prior to tape application with a clean non abrasive cloth.

IMPORTANT NOTES



- Under no circumstances should taped or foil edged glass units be used for this application.
- The polyamide strip to the glazing side must be free from paint to ensure the a strong bond.





Do Not Scale From This Drawing

Visoglide Plus

VG540 Cutting & VG540/VG541 Fitting





Note:
ACVG529 is not required on the locking side of the secondary door sash.
ACVG545 must be used instead.



Important Note:
VG540 & VG541 are
not suitable for lift &
slide doors.
Please use VG542
instead.

Do Not Scale From This Drawing

VG541 Cutting & End Prep



Do Not Scale From This Drawing


Visoglide Plus

VG542 Fitting Details


ACVG543 End Caps




Slide without VG514



Slide with VG514




Lift & Slide with VG514




Do Not Scale From This Drawing

VG542 Fitting Details with VG516 Threshold

Lift & Slide without VG514




Lift & Slide with VG514



Do Not Scale From This Drawing


VG549 Fitting Details

ACVG569 End Caps




Important Note:
Suitable for BT Lock only


Slide without VG514




Slide with VG514




Slide with VG515




VG632 Fitting Details




Sash Installation




ACVG528 Position Details




Fixed Sash Installation




Please note that for improved weather performance the fixed pane should be positioned on the outer track so VG514/VG515 may be fitted.



Fix 100mm in from each end
& then at 1000mm centres



ACET076





ACET066


ACET066

ACET076
ACVG559


ACVG544
ACET066



ACVG644




ACVG645N



ACVG544




Do Not Scale From This Drawing

ACUG830 Fitting Detail





Do Not Scale From This Drawing

VG514 & VG515 Cutting & Fitting



Use ACVS033 with VG514 & VG515










Steps:

1. Fit VG515 to the head & cill (notch leg over ACUG830)
2. Fit VG514 to the head & cill (notch leg over ACUG830)
3. Fit VG515 to the jamb
4. Fit VG514 to the jamb

Do Not Scale From This Drawing




VG519 Details





Do Not Scale From This Drawing

Visoglide Plus


VG519 Details with Slim Interlock



Use with details on previous page




Punch using ACVG955
Position 1 & 2




Do Not Scale From This Drawing


Sobinco Lift & Slide Door Hardware Selection




SCHEME A - 2 RAIL-1F-20




SCHEME B - 2 RAIL-10-20




SCHEME C - 2 RAIL-1F-20X20-1F




SCHEME D - 2 RAIL-1F-20-1F



SCHEME E - 2 RAIL-20-1F-20



SCHEME F - 3 RAIL-1F-20-30



(*) OPTIONAL

QUANTITY


A	B	C	D	E	F	G		DESCRIPTION	PART NUMBER
1	2	2	1	2	2	4	LOCK		
							VENT HEIGHT		
							1718mm - 2218mm	ACVG277	
							2118mm - 2518mm	ACVG278	
							2418mm ...	ACVG279	
							STANDARD: 4-POINT LOCK	ACVG280N	
							MAX:200 KG		
1	2	2	1	2	2	4	CONNECTING ROD		
							WIDTH SASH		
							702mm - 1278mm	ACVG269	
							1206mm - 1782mm	ACVG270	
							1710mm - 2286mm	ACVG271	
							2214mm - 2790mm	ACVG272	
							2718mm - 3294mm	ACVG273	
							LOCKING POINT (BOTTOM)	ACVG281N	
							GUIDE BRACKET	ACVG268	
							BASIC SET LIFT & SLIDING DOOR 4 DOOR	ACVG240	

SCHEME G - 2 RAIL-1F-20-30X30-20-1F



Do Not Scale From This Drawing

Visoglide Plus



Sobinco Lift & Slide Door with Standard Track



Do Not Scale From This Drawing

Sobinco Lift & Slide Bottom Locking Point (ACVG281N) Fixing Detail

⚠ Support Pieces from ACDV280N kit are required for ACVG281N to work correctly.




⚠ Support Pieces from ACDV280N kit are required for ACVG281N to work correctly.

Important Note
ACVG281N is NOT compatible
with VG516 Outer Frame.



Do Not Scale From This Drawing

Sobinco Lift & Slide Single Door Locking Details




Vent Height	X (mm)	Y (mm)
1718 mm - 2218 mm	ACVG277	204.5
2118 mm - 2518 mm	ACVG278	604.5
2418 mm - ...	ACVG279	1004.5

With Cylinder
 Without Cylinder




Do Not Scale From This Drawing

Sobinco Lift & Slide Double Door Lock Details




Do Not Scale From This Drawing

Sobinco Lift & Slide Gearing with VG516 Threshold




Do Not Scale From This Drawing

Sobinco Lift & Slide Lock with VG516 Threshold




Vent Height	X (mm)	Y (mm)
1718 mm - 2218 mm	ACVG277	204.5 314.5
2118 mm - 2518 mm	ACVG278	604.5 714.5
2418 mm - ...	ACVG279	1004.5 1114.5

With Cylinder
 Without Cylinder



Do Not Scale From This Drawing

Hautau Lift & Slide Door Hardware Selection




DESCRIPTION	PART NUMBER	QUANTITY						
		A	B	C	D	E	F	G
LOCK		1	2	2	1	2	2	4
VENT HEIGHT								
1877mm - 2176mm	ACVG1277							
2177mm - 2476mm	ACVG1278							
2477mm - ...	ACVG1279							
BASIC LIFT AND SLIDE KIT	ACVG1280	1	2	2	1	2	2	4
MAX: 250KG								
1(*) 2(*) 1(*) 1(*) 2(*) 1(*) 1(*)	ADDITIONAL KEEP							
1(*) 2(*) 1(*) 1(*) 2(*) 1(*) 1(*)	ADDITIONAL KEEP WITH NIGHT VENTILATION							
1							1	
BASIC SASH TO SASH LOCK SET	ACVG1240							
1							1	
LOCKING POINT	ACUG221							
1	2	2	1	2	2	2	4	
CONNECTING ROD								
MAX 250KG								
WIDTH SASH								
650mm - 1360 mm	MAX 300KG							
1120mm - 1800mm	WIDTH SASH							
1361mm - 1860mm	ACUG230							
1801mm - 2300mm	ACUG231							
1861mm - 2360mm	ACUG232							
2301mm - 2800mm								
2801mm - 3235mm	ACUG233							
1	2	2	1	2	2	2	4	ADDITIONAL ROLLERS
								ACVG1274(**)

(*) OPTIONAL
(**) ≤ 300KG SASH WEIGHT

Do Not Scale From This Drawing




Hautau Lift & Slide Gearing For Sash 250Kg and below

Milling Detail
Scale 1:2




Important Fabrication note
If sash weight exceeds the 250Kg maximum, additional rollers can be used. This requires a minimum sash width of 1120mm. please refer to Page E49 in the manual for more information.

Connecting Rod Requirement based on Sash Width	
650 mm - 1360 mm	ACUG230
1361 mm - 1860 mm	ACUG231
1861 mm - 2360mm	ACUG232





Hautau Lift & Slide Gearing For Sash 300Kg and below



Hautau Lift & Slide Lock



Milling Detail For
Lock Back set
Scale 1:2



Sash Height	A (mm)	B (mm)
1877 mm - 2176 mm	ACVG1277	292
2177 mm - 2476 mm	ACVG1278	592
2418 mm - 2500mm	ACVG1279	892




With Cylinder
Without Cylinder

ext.	int.			2x	2 x
ACSZ860	ACSZ861	ACMX1130	ACMX0040	ACET235	ACSZ865
	ACSZ863		ACMX0040		
	ACSZ861		ACIM442		
ACSZ862	ACSZ861	ACMX1075	ACMX0040		
	ACSZ863		ACMX3040		
	ACSZ871 + ACSZ400		ACMX4050		
ACSZ871	ACSZ863				




Hautau Lift & Slide Double Door Lock


Milling Detail For Lock Back set Scale 1:2




Hautau Soft Close mechanism





Hautau Soft Close Mechanism for Slim Interlock








Compatible with VG521N sash Only




**ACVG290 For Sash Weights ≤200Kg
ACVG292 For Sash Weights ≤300Kg**




Catch Position for Hautau Soft Close Mechanism








Lift & Slide Slim Interlock on Standard Track



Important Fabrication Note:
Use ACSIL04 sealant to ensure the bottom rail is fully sealed against the interlock to prevent water egress.



VG516 & VG518 Joint Detail





Do Not Scale From This Drawing

Visoglide Plus



ACUG123 Fitting Detail into VG518

VG514 End Prep Detail



Do Not Scale From This Drawing



VG516 Fixed Sash Installation



Do Not Scale From This Drawing






Visoglide Plus

Monorail Assembly












Do Not Scale From This Drawing

Monorail Interlock Sealing








Do Not Scale From This Drawing

Monorail Assembly



Do Not Scale From This Drawing


Head Extension Fitting Details




Do Not Scale From This Drawing

Glazing Options

Single Glazing




VG430




VG430

24-26mm Glazing



VG416



VG416

Low Profile Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
10	ACET841	ACW20038
11	ACET842	ACW20038
12	ACET843	ACW20038

Standard Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
8	ACVG131	ACVG340
9	ACVG131	ACVG34
10	ACVG31	ACVG34
11	ACVG231	ACVG34
12	ACVG231	ACVG33



Low Profile Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
24	ACET841	ACW20038
25	ACET842	ACW20038
26	ACET843	ACW20038

Standard Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
24	ACVG31	ACVG34
25	ACVG231	ACVG34
26	ACVG231	ACVG33



Do Not Scale From This Drawing

Glazing Options

28-30mm Glazing



30-32mm Glazing




Low Profile Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
28	ACET841	ACW20038
29	ACET842	ACW20038
30	ACET843	ACW20038

Standard Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
28	ACVG31	ACVG34
29	ACVG231	ACVG34
30	ACVG231	ACVG33

Low Profile Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
30	ACET840	ACW20038
31	ACET841	ACW20038
32	ACET842	ACW20038

Standard Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
30	ACVG131	ACVG34
31	ACVG31	ACVG34
32	ACVG31	ACVG33

Do Not Scale From This Drawing

Visoglide Plus**Glazing Options****36-38mm Glazing**



Low Profile Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
36	ACET841	ACW20038
37	ACET842	ACW20038
38	ACET843	ACW20038

Standard Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
36	ACVG31	ACVG34
37	ACVG231	ACVG34
38	ACVG231	ACVG33



Do Not Scale From This Drawing

Glazing Options

28-30mm Glazing



36-38mm Glazing



Low Profile Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
28	ACET841	ACW20038
29	ACET842	ACW20038
30	ACET843	ACW20038

Standard Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
28	ACVG31	ACVG34
29	ACVG231	ACVG34
30	ACVG231	ACVG33


Low Profile Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
36	ACET841	ACW20038
37	ACET842	ACW20038
38	ACET843	ACW20038

Standard Gaskets		
Glazing Thickness	External Gasket	Internal Gasket
36	ACVG31	ACVG34
37	ACVG231	ACVG34
38	ACVG231	ACVG33

Do Not Scale From This Drawing

Visoglide Plus

Glazing Options




Standard Gaskets			
Glazing Thickness	Bead	External Gasket	Internal Gasket
24	GL740	ACVG31	ACVG34
25	GL740	ACVG231	ACVG34
26	GL740	ACVG231	ACVG33
28	GL736	ACVG31	ACVG34
29	GL736	ACVG231	ACVG34
30	GL736	ACVG231	ACVG33
32	GL732	ACVG31	ACVG34
33	GL732	ACVG231	ACVG34
34	GL732	ACVG231	ACVG33
36	GL728	ACVG231	ACVG34
37	GL728	ACVG231	ACVG33
38	GL724	ACVG131	ACVG34
39	GL724	ACVG31	ACVG34
40	GL724	ACVG231	ACVG34


Do Not Scale From This Drawing

PAS24:2016 Overview

Lock & Keep Fixing Details for Multi Point Lock




Lock Fixing Details for BT Lock



The details on this page show the specific hardware required to achieve PAS24:2016.
Hardware not shown is standard.

ACVG752 to Top & Bottom



Not Required For BT Lock

Multi-Point Locking Hardware


SASH HEIGHT	LOCKS	KEEPS	
		FULL HEIGHT KEEP	FULL HEIGHT KEEP + 600mm
2024 - 2223	ACSZ024	ACSZ122	ACSZ124
1824 - 2023	ACSZ025	ACSZ126	ACSZ128
2224 - 2423	ACSZ026	ACSZ130	ACSZ132

EXT.	INT.	ACMX209	ACIM442	3 x ACET237
ACSZ882	ACSZ883			

BT Locking Hardware


SASH HEIGHT	LOCKS	KEEPS
≤ 2366mm	ACSZ040	ACSZ046
≤ 2766mm	ACSZ041	ACSZ046
≤ 3166mm*	ACSZ042	ACSZ046

ACSZ400	Or...	EXT.	INT.
	ACSZ750	ACSZ751	ACCY3030S1







Do Not Scale From This Drawing


ACUN348 Location




VG510 Corner Assembly



VG581 Shootbolt Details




ACSZ015 Lock Preparation & Shootbolt Details



Do Not Scale From This Drawing

Visoglide Plus


VG580 & VG581 Assembly




Do Not Scale From This Drawing

VG651 - VG655 Bay Pole Adapters


VG651 + VG652



VG651 + VG655



VG653 + VG654



ANGLE	DIM X	DIM Y
90°	10	10.5
95°	10.5	11
100°	10.5	11.5
105°	11	11.5
110°	11	12
115°	11	12
120°	11.5	12.5
125°	11.5	12.5
130°	11.5	13
135°	12	13
137°	12	13.5

ANGLE	DIM X	DIM Y
133°	12	12.5
135°	12.5	12.5
140°	12.5	13
145°	12.5	13
150°	13	13.5
155°	13	13.5
160°	13	14

Do Not Scale From This Drawing

Do Not Scale From This Drawing

Section F


Sawing Tables

Sliding Doors.....	F03 - F14
Sobinco Lift and Slide Doors.....	F15 - F22
Hautau Lift and Slide Doors.....	F23 - F27
Vanishing Corner.....	F28

Section F

Visoglide Plus

Cutting Information - Sliding



PROFILES

VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG520		4		W/2 - 11
VG520		4		H - 87
VG530		2		H - 87
VG551R		2		H - 87
VG586		2		H - 87
BEAD		4		W/2 - 119
BEAD		4		H - 235
VG53		1		W - 94
VG52		1		W - 104
VG52		2		W/2 - 62.5
VG52		3		H - 92
VL72		1		W - 9
VG575		1		W/2 - 89
*VG514		1		H - 108
*VG514		2		W/2 - 93.5


*Optional

GLASS SIZE		
2x	W/2 - 129	H - 205

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACSG012		16	Sash Cleat
ACUG830		2	Interlock Seal
ACUN348		2	Buffer
ACVG520		32	Chevron
ACVG523		13	Lock Fixing Plates
ACVG528		4+	Sash Top Guide
ACVG529		1 Set of 4	Anti Lift Block/Guide
ACVG530		2 Pairs	Interlock Cover Cap
ACVG534		4+	Sash Drainage Spout
ACVG544		6	Fixed Sash Support
ACVG555		2	Adjustable Rollers
ACVG559		8	Bridge Packer
ACVG575		2+	Support for VG575
ACVG617(S)		8	Outer Frame Cleat
ACVL059		1 Pair	VL72 End Cap
ACVL061		W/300 + 2	VL72/VL76 Rivet
ACVS033		9H + 5W	Woolpile
ACVS034		2H	VG551R Woolpile
Ext. Glazing Gasket		4H + 2W - 1300	'E' Gasket
Int. Glazing Gasket		4H + 2W - 1300	Wedge Gasket

*See section E for lock & handle selection






Do Not Scale From This Drawing

IMPORTANT NOTE:

Maximum Sash Weights:
Sliding Sashes = 250kg

Visoglide Plus

Cutting Information - Sliding



IMPORTANT NOTE:

Maximum Sash Weights:
Sliding Sashes = 250kg

PROFILES




VG510 (with UG050)		2		W
VG510 (with UG050)		2		H
VG520		4		W/2 - 11
VG520		4		H - 87
VG530		2		H - 87
VG551R		2		H - 87
VG586		2		H - 87
BEAD		4		W/2 - 119
BEAD		4		H - 235
VG52		2		W - 104
VG52		4		H - 104
VG53		2		W - 94
VL72		1		W - 9
VG575		2		W/2 - 89

GLASS SIZE		
2x	W/2 - 129	H - 205

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACSG012		16	Sash Cleat
ACUG830		2	Interlock Seal
ACUN348		4	Buffer
ACVG510		8	Outer Frame Cleats
ACVG520		32	Chevron
ACVG523		26	Lock Fixing Plates
ACVG528		8+	Sash Top Guide
ACVG529		1 Set of 4	Anti Lift Block/Guide
ACVG530		2 Pairs	Interlock Cover Cap
ACVG534		4+	Sash Drainage Spout
ACVG555		4	Adjustable Rollers
ACVG559		4	Bridge Packer
ACVG575		4+	Support for VG575
ACVL059		1 Pair	VL72 End Cap
ACVL061		W/300 + 2	VL72/VL76 Rivet
ACVS033		8H + 4W	Woolpile
ACVS034		2H	VG551R Woolpile
Ext. Glazing Gasket		4H + 2W - 1300	'E' Gasket
Int. Glazing Gasket		4H + 2W - 1300	Wedge Gasket



*See section E for lock & handle selection



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sliding with Slim Interlock



PROFILES


VG510 (with UG050)		2		W
VG510 (with UG050)		2		H
VG520		2		W/2 - 48.5
VG520		2		W/2 - 48.5
VG520		1		H - 87
VG535		1		H - 87
VG536		1		H - 87
VG537		2		H - 87
VG552N		2		H - 87
BEAD		4		W/2 - 114.5
BEAD		2		H - 235
VG565/VG566		2		H - 195
VG52		2		W - 104
VG52		4		H - 104
VG53		2		W - 94
VL72		1		W - 9
VG575		2		W/2 - 89

GLASS SIZE		
2x	W/2 - 109.5	
	H - 205	

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACSG012		8	Sash Cleat
ACUG830		2	Interlock Seal
ACUN348		4	Buffer
ACVG510		8	Outer Frame Cleats
ACVG520		32	Chevron
ACVG523		26	Lock Fixing Plates
ACVG528		8+	Sash Top Guide
ACVG529		1 Set of 4	Anti Lift Block/Guide
ACVG530		2 Pairs	Interlock Cover Cap
ACVG534		4+	Sash Drainage Spout
ACVG536		1 Pair	End Caps
ACVG546		2	Interlock Anti-Lift Block
ACVG547		8	Fixing Bracket
ACVG555		4	Adjustable Rollers
ACVG559		4	Bridge Packer
ACVG575		4+	Support for VG575
ACVL059		1 Pair	VL72 End Cap
ACVL061		W/300+2	VL72/VL76 Rivet
ACVS033		6H + 4W	Woolpile
Ext. Glazing Gasket		4H + 2W - 1300	'E' Gasket
Int. Glazing Gasket		4H + 2W - 1300	Wedge Gasket


*See section E for lock & handle selection



Do Not Scale From This Drawing


Visoglide Plus

Cutting Information - Mono Rail with Slider



IMPORTANT NOTE:

Maximum Sash Weights:
Slide = 250kg




PROFILES

VG618	2	W
VG618	2	H
VG520	2	W/2 - 11
VG520	2	H - 87
VG620	1	H - 56
VG530	1	H - 87
VG630	1	H - 56
VG551R	2	H - 87
VG586	2	H - 87
VG615	1	H - 56
VG615	1	W/2 - 69.5
VG616	2	W/2 - 83
VG5XX	2	W/2 - 119
VG5XX	2	H - 235
GL7XX	2	W/2 - 44.5
GL7XX	2	H - 106
VG53	1	W - 94
VG52	1	W - 104
VG52	2	H - 104
VL72	1	W - 9

GLASS SIZE

Fixed 1x	W/2 - 58.5
	H - 70
Sash 1x	W/2 - 131
	H - 207




ACCESSORIES

ACEF010B	4	VG610/618 Corner Cleat
ACSG611B	(H + W - 200) / 300	Clip-In Adaptor
ACFT171	2	Storm Valve
ACGSL057	H + W - 200	VG610/618 Interlock Seal
ACSG631	4	VG610/618 Glass Support
ACSP057	2	VG610/618 Interlock Seal
ACUG631	1	VG610/618 Interlock Seal
ACUG632	2	VG610/618 Interlock Seal
ACUN348	1	Buffer
ACVG45N	MAX 800 mm	Drainage Cap
ACVG520	16	Chevron
ACSG012	8	VG520 Corner Cleat
ACVG528	4+	Top Guides
ACVG531	1 Pair	Interlock Cover Cap
ACVG534	2+	Sash Drainage Spout
ACVG555	2	Adjustable Roller
ACVG557N	3	Bridge Packer
ACVG618(S)	4	VG618 Corner Cleat
ACVL020(B)	4	Chevron
ACVL029	6	Anti-Twist Clip
ACVL059	1	VL72 End Cap
ACVL061	W/300 + 2	Rivet
ACVS033	7H + 5W	Woolpile
ACVS034	2H	VG551R Woolpile
Ext. Glazing Gasket	(1) 2H + W - 200 (2) 2H + W - 700	E-Gasket
Int. Glazing Gasket	(1) 2H + W - 200 (2) 2H + W - 700	Wedge Gasket

*See section B for connecting rod and lock length requirements


*See section E for lock & handle selection



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sliding



PROFILES

VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG520		6		W/3 + 14.3
VG520		6		H - 87
VG530		3		H - 87
VG551R		3		H - 87
VG586		3		H - 87
VG632		1		H - 87
BEAD		6		W/3 - 93.7
BEAD		6		H - 235
VG53		1		W - 94
VG52		1		W - 104
VG52		2		W/3 - 71.5
VG52		3		H - 92
VL72		1		W - 9
VG575		2		W/3 - 63.5
*VG514		2		W/3 - 133.5


*Optional

GLASS SIZE		
3x	W/3 - 103.5	H - 205

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACSG012	24		Sash Cleat
ACUG830	4		Interlock Seal
ACUN348	2		Buffer
ACVG520	44		Chevron
ACVG523	13		Lock Fixing Plates
ACVG528	4+		Sash Top Guide
ACVG529	1 Set of 4		Anti Lift Block/Guide
ACVG530	3 Pairs		Interlock Cover Cap
ACVG534	6+		Sash Drainage Spout
ACVG544	12		Fixed Sash Support
ACVG555	2		Adjustable Rollers
ACVG559	14		Bridge Packer
ACVG575	4+		Support for VG575
ACVG617(S)	8		Outer Frame Cleat
ACVL059	1 Pair		VL72 End Cap
ACVL061	W/300 + 2		VL72/VL76 Rivet
ACVS033	13H + 6W		Woolpile
ACVS034	2H		VG551R Woolpile
Ext. Glazing Gasket	6H + 2W - 1300		'E' Gasket
Int. Glazing Gasket	6H + 2W - 1300		Wedge Gasket

*See section E for lock & handle selection




Do Not Scale From This Drawing

IMPORTANT NOTE:

Maximum Sash Weights:
Sliding Sashes = 250kg

Visoglide Plus

Cutting Information - Sliding




PROFILES				
VG510 (with UG050)		2		W
VG510 (with UG050)		2		H
VG520		6		W/3 - 10
VG520		6		H - 87
VG551R		2		H - 87
VG586		2		H - 87
VG530		2		H - 87
VG540		1		H - 125
BEAD		6		W/3 - 118
BEAD		6		H - 235
VG52		2		W - 104
VG52		4		H - 104
VG53		1		W - (W1 + 47)
VL72		1		W - 9
VG575		1		W/3 - 88
*VG514		2		W - (W3 + 93)
*VG514		1		H - 108

* Options

GLASS SIZE	
3x	W/3 - 128 H - 205


ACCESSORIES			
ACGSL045		MAX 800 mm	Drainage Cap
ACSG012	24		Sash Cleat
ACUG830	2		Interlock Seal
ACUN348	2		Buffer
ACVG510	8		Outer Frame Cleats
ACVG520	44		Chevron
ACVG523	26		Lock Fixing Plates
ACVG528	4+		Sash Top Guide
ACVG529	1 Set of 4		Anti Lift Block/Guide
ACVG530	2 Pairs		Interlock Cover Cap
ACVG534	6+		Sash Drainage Spout
ACVG540	1		VG540 End Cap
ACVG544	12		Fixed Sash Support
ACVG545	2		Sash Guide
ACVG555	2		Adjustable Rollers
ACVG559	14		Bridge Packer
ACVG571	4		Lock Fixing Support
ACVG575	2+		Support for VG575
ACVG580	1		Fixation Plate
ACVG81	1		Fixation Plate
ACVL059	1 Pair		VL72 End Cap
ACVL061	W/300 + 2		VL72/VL76 Rivet
ACVS033	11H + 6W		Woolpile
ACVS034	2H		VG551R Woolpile
Ext. Glazing Gasket	6H + 2W - 1100		'E' Gasket
Int. Glazing Gasket	6H + 2W - 1100		Wedge Gasket

***See section E for lock & handle selection**




IMPORTANT NOTE:

Maximum Sash Weights:



Do Not Scale From This Drawing

Cutting Information - Sliding with Slim Interlock



PROFI


VG510 (with UG050)		2		W
VG510 (with UG050)		2		H
VG520		1		W2 - 9
VG520		1		W3 - 48.5
VG520		1		W2 - 10
VG520		1		W3 - 48.5
VG520		2		W1 - 47.5
VG520		4		H - 87
VG535		1		H - 87
VG536		1		H - 87
VG537		2		H - 87
VG552N		2		H - 87
VG540		1		H - 125
BEAD		2		W/3 - 105
BEAD		4		W/3 - 108
BEAD		4		H - 235
VG565/VG566		4		H - 195
VG52		2		W - 104
VG52		2		H - 104
VG53		1		W - 94
VL72		1		W - 9
VG575		1		W/3 - 94.5
*VG514		2		W - (W3 + 69.5)
VG514		1		W - 100

* Optional

GLASS SIZE

3x	W/3 - 115 H - 205
----	----------------------

ACCESSORIES


ACGSL045		Drainage Cap
ACSG012	16	Sash Cleat
ACUG830	2	Interlock Seal
ACUN348	2	Buffer
ACVG510	8	Outer Frame Cleats
ACVG520	32	Chevron
ACVG523	26	Lock Fixing Plates
ACVG528	4+	Sash Top Guide
ACVG529	1 Set of 4	Anti Lift Block/Guide
ACVG530	2 Pairs	Interlock Cover Cap
ACVG534	6+	Sash Drainage Spout
ACVG536	1 Pairs	End Caps
ACVG540	1	VG540 End Cap
ACVG544	12	Fixed Sash Support
ACVG545	2	Sash Guide
ACVG546	4	Interlock Anti-Lift Block
ACVG547	8	Fixing Bracket
ACVG555	2	Adjustable Rollers
ACVG559	14	Bridge Packer
ACVG571	4	Lock Fixing Support
ACVG575	2+	Support for VG575
ACVG580	1	Fixation Plate
ACVG81	1	Fixation Plate
ACVL059	1 Pair	VL72 End Cap
ACVL061	W/300 + 2	VL72/VL76 Rivet
ACVS033	9H + 6W	Woolpile
Ext. Glazing Gasket	6H + 2W - 1100	'E' Gasket
Int. Glazing Gasket	6H + 2W - 1100	Wedge Gasket

The diagram illustrates a 3D scene representation within a rectangular frame. The vertical dimension is labeled **H** and the horizontal dimension is labeled **W**. The scene is divided into three vertical sections by two internal vertical boundaries. The leftmost section contains several geometric shapes: two white triangles at the top, one black triangle below them, and two white triangles near the bottom. The middle section is mostly empty, with only two black triangles located at the bottom. The rightmost section contains several white triangles at the top, one black triangle below them, and two white triangles near the bottom. To the right of the middle section, there is a label **←→**. Below the rightmost section, there are two labels: **ACVG544** next to a white triangle and **ACVG559** next to a black triangle.

IMPORTANT NOTE:

Maximum Sash Weights:


***See section E for lock & handle selection**



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sliding with Slim Interlock




PROFILES

VG512 (with UG050)	2	W
VG512 (with UG050)	2	H
VG520	2	W1 - 48.5
VG520	2	W1 - 48.5
VG520	2	W2 - 10
VG520	2	H - 87
VG535	2	H - 87
VG536	2	H - 87
VG537	4	H - 87
VG552N	4	H - 87
*VG556	1	W
*VG557	1	W
BEAD	4	W/3 - 103
BEAD	2	W2 - 10
BEAD	2	H - 235
VG565/VG566	4	H - 195
VG52	3	W - 104
VG52	6	H - 104
VG53	3	W - 94
VL72	1	W - 9
VG575	1	2W/3 - 121
VG575	1	W/3 - 188.5
*VG514	2	2W/3 - 102
*VG514	1	H - 108
*VG515	2	W/3 - 38
*VG515	1	H - 112

* Optional


118



ACCESSORIES

ACGSL045	MAX 800 mm	Drainage Cap
ACSG012	8	Sash Cleat
ACUG830	4	Interlock Seal
ACUN348	4	Buffer
ACVG510	8	Outer Frame Cleats
ACVG520	24	Chevron
ACVG523	13	Lock Fixing Plates
ACVG528	8+	Sash Top Guide
ACVG529	2 Set of 4	Anti Lift Block/Guide
ACVG530	4 Pairs	Interlock Cover Cap
ACVG534	6+	Sash Drainage Spout
ACVG535	1 Pair	End Cap with Upstand
ACVG536	1 Pair	Flat End Caps
ACVG544	6	Fixed Sash Support
ACVG546	8	Interlock Anti-Lift Block
ACVG547	16	Fixing Bracket
ACVG555	4	Adjustable Rollers
ACVG556	1 Pair	VG556 End Cap
ACVG559	10	Bridge Packer
ACVG575	4+	Support for VG575
ACVL059	1 Pair	VL72 End Cap
ACVL061	W/300 + 2	VL72/VL76 Rivet
ACVS033	8H + 6W	Woolpile
Ext. Glazing Gasket	6H + 2W - 1300	'E' Gasket
Int. Glazing Gasket	6H + 2W - 1300	Wedge Gasket

[†]Deductions for different sized glass




GLASS SIZE

3x	W/3 - 77.5
	H - 205

IMPORTANT NOTE:


Maximum Sash Weights:
Sliding Sashes = 250kg



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sliding



PROFILES


VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG520		8		W/4 + 8.75
VG520		8		H - 87
VG530		4		H - 87
VG551R		4		H - 87
VG586		4		H - 87
VG542		1		H - 87
BEAD		8		W/4 - 99.25
BEAD		8		H - 235
VG53		1		W - 94
VG52		1		W - 104
VG52		2		W/2 - 60
VG52		3		H - 92
VL72		1		W - 9
VG575		2		W/4 - 69
*VG514		2		W/2 - 122.5

* Optional



ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACSG012		32	Sash Cleat
ACUG830		4	Interlock Seal
ACUN348		4	Buffer
ACVG520		56	Chevron
ACVG523		26	Lock Fixing Plates
ACVG528		8+	Sash Top Guide
ACVG529		2 Set of 4	Anti Lift Block/Guide
ACVG530		4 Pairs	Interlock Cover Cap
ACVG534		8+	Sash Drainage Spout
ACVG543		1 Pair	VG542 End Caps
ACVG544		12	Sash Supports
ACVG545		2	Meeting Stile Guide
ACVG555		4	Adjustable Rollers
ACVG559		16	Bridge Packer
ACVG571		4	Lock Fixing Support
ACVG575		4+	Support for VG575
ACVG580		1	Fixation Plate
ACVG617(S)		8	Outer Frame Cleat
ACVG81		1	Fixation Plate
ACVL059		1 Pair	VL72 End Cap
ACVL061		W/300 + 2	VL72/VL76 Rivet
ACVS033		15H + 5W - 500	Woolpile
ACVS034		4H	VG551R Woolpile
Ext. Glazing Gasket		8H + 2W - 1300	'E' Gasket
Int. Glazing Gasket		8H + 2W - 1300	Wedge Gasket

*See section E for lock & handle selection



GLASS SIZE		
4x	W/4 - 109	H - 205




IMPORTANT NOTE:

Maximum Sash Weights:
Sliding Sashes = 250kg

Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sliding with Slim Interlock



PROFI

VG510 (with UG050)		2		W
VG510 (with UG050)		2		H
VG520		4		W/4 - 29
VG520		4		W/4 - 29
VG520		4		H - 87
VG535		2		H - 87
VG536		2		H - 87
VG537		4		H - 87
VG552N		4		H - 87
VG540		1		H - 125
BEAD		8		W/4 - 83
BEAD		4		H - 235
VG565/VG566		4		H - 195
VG52		2		W - 104
VG52		2		H - 104
VG53		1		W - 94
VL72		1		W - 9
VG575		2		W/4 - 69.
*VG514		2		W/2 - 73


* Opti

GLASS SIZE	
4x	W/4 - 90
	H - 205

ACCESSORIES

ACGSL045		Drainage Cap
ACSG012	16	Sash Cleat
ACUG830	4	Interlock Seal
ACUN348	4	Buffer
ACVG510	8	Outer Frame Cleats
ACVG520	32	Chevron
ACVG523	26	Lock Fixing Plates
ACVG528	8+	Sash Top Guide
ACVG529	2 Set of 4	Anti Lift Block/Guide
ACVG530	4 Pairs	Interlock Cover Cap
ACVG534	8+	Sash Drainage Spout
ACVG536	2 Pairs	End Caps
ACVG540	1	VG540 End Cap
ACVG544	12	Fixed Sash Support
ACVG546	8	Interlock Anti-Lift Block
ACVG547	16	Fixing Bracket
ACVG555	4	Adjustable Rollers
ACVG559	16	Bridge Packer
ACVG575	4+	Support for VG575
ACVL059	1 Pair	VL72 End Cap
ACVL061	W/300 + 2	VL72/VL76 Rivet
ACVS033	10H + 6W	Woolpile
Ext. Glazing Gasket	8H + 2W - 1300	'E' Gasket
Int. Glazing Gasket	8H + 2W - 1300	Wedge Gasket



***See section E for lock & handle selection**



IMPORTANT NOTE:


Maximum Sash Weights:

Sliding Sashes = 250kg




Do Not Scale From This Drawing

Cutting Information - Sliding




PROFILES				
VG612 (with UG050)		2		W
VG612 (with UG050)		2		H
VG520		12		W/6 + 27.5
VG520		12		H - 87
VG530		8		H - 87
VG551R		8		H - 87
VG586		8		H - 87
VG542		1		H - 87
BEAD		12		W/6 - 80.5
BEAD		12		H - 235
VG53		2		W - 94
VG52		2		W - 104
VG52		2		2W/3 - 97.6
VG52		4		H - 92
VL72		1		W - 9
VG575		2		W/3 - 88
VG575		2		W/6 - 50.5
*VG514		2		2W/3 - 160
*VG515		2		W/3 - 85

* Optional



IMPORTANT NOTE:

Maximum Sash Weights:
Sliding Sashes = 250kg





ACCESSORIES		
ACGSL045	MAX 800 mm	Drainage Cap
ACSG012	48	Sash Cleat
ACUG830	8	Interlock Seal
ACUN348	8	Buffer
ACVG520	80	Chevron
ACVG523	26	Lock Fixing Plates
ACVG528	16+	Sash Top Guide
ACVG529	4 Set of 4	Anti Lift Block/Guide
ACVG530	8 Pairs	Interlock Cover Cap
ACVG534	12+	Sash Drainage Spout
ACVG543	1 Pair	VG542 End Caps
ACVG544	12	Sash Supports
ACVG545	2	Meeting Stile Guide
ACVG555	8	Adjustable Rollers
ACVG559	20	Bridge Packer
ACVG571	4	Lock Fixing Support
ACVG575	8+	Support for VG575
ACVG580	1	Fixation Plate
ACVG617(S)	8	Outer Frame Cleat
ACVG81	1	Fixation Plate
ACVL059	1 Pair	VL72 End Cap
ACVL061	W/300 + 2	VL72/VL76 Rivet
ACVS033	23H + 6W	Woolpile
ACVS034	8H	VG551R Woolpile
Ext. Glazing Gasket	12H + 2W - 1300	'E' Gasket
Int. Glazing Gasket	12H + 2W - 1300	Wedge Gasket

***See section E for lock & handle selection**

Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sliding with Slim Interlock



PROFILES

VG512 (with UG050)		2		W
VG512 (with UG050)		2		H
VG520 (W_1)		4		$W/6 - 3.5$
VG520 (W_2)		4		$W/6 - 60.5$
VG520 (W_3)		4		$W/6 - 3.5$
VG520		4		$H - 87$
VG537		8		$H - 87$
VG535		4		$H - 87$
VG536		4		$H - 87$
VG552N		8		$H - 87$
VG540		1		$H - 87$
BEAD (W_1)		4		$W/6 - 57.5$
BEAD (W_2)		4		$W/6 - 60.5$

PROFILES (Continued)

BEAD (W_3)		4		$W/6 - 57.5$
BEAD		12		$H - 235$
VG53		2		$W - 94$
VG52		2		$W - 104$
VG52		2		$2W/3 - 97.6$
VG52		4		$H - 92$
VL72		1		$W - 9$
VG575		2		$W/3 - 94.5$
VG575		2		$W/6 - 44$
*VG514		2		$2W/3 - 126$
*VG515		2		$W/3 - 25$

* Optional

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACSG012	16		Sash Cleat
ACUG830	8		Interlock Seal
ACUN348	8		Buffer
ACVG509/510	8		Outer Frame Cleats
ACVG520	36		Chevron
ACVG523	26		Lock Fixing Plates
ACVG528	16+		Sash Top Guide
ACVG529	4 Set of 4		Anti Lift Block/Guide
ACVG530	8 Pairs		Interlock Cover Cap
ACVG534	12+		Sash Drainage Spout
ACVG535	2 Pairs		End Cap with Upstand
ACVG536	2 Pairs		Flat End Cap

W

ACCESSORIES (Continued)


ACVG540	1 Pair	End Cap for VG540
ACVG544	12	Sash Supports
ACVG545	2	Meeting Stile Guide
ACVG546	16	Interlock Anti-Lift Block
ACVG547	32	Fixing Bracket
ACVG555	8	Adjustable Rollers
ACVG559	20	Bridge Packer
ACVG571	4	Lock Fixing Support
ACVG575	8+	Support for VG575
ACVG580	1	Fixation Plate
ACVG81	1	Fixation Plate
ACVL059	1 Pair	VL72 End Cap
ACVL061	$W/300 + 2$	VL72/VL76 Rivet
ACVS033	$14H + 6W$	Woolpile
Ext. Glazing Gasket	$12H + 2W - 1300$	'E' Gasket
Int. Glazing Gasket	$12H + 2W - 1300$	Wedge Gasket

*See section E for lock & handle selection

IMPORTANT NOTE:


Maximum Sash Weights:
Sliding Sashes = 250kg

GLASS SIZE		
6x	$W/6 - 65$	$H - 205$



Do Not Scale From This Drawing

Cutting Information - Sabinco Lift and Slide



PROFILES				
VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG521N		4		W/2 - 3
VG521N		4		H - 87
VG530		2		H - 87
VG553N		2		H - 87
UG852		2		H - 87
BEAD		4		W/2 - 143
BEAD		4		H - 267
VG53		1		W - 94
VG52		1		W - 104
VG52		2		W/2 - 70.5
VG52		2		H - 92
VL72		1		W - 9
VG575		1		W/2 - 89
*VG514		1		H - 108
*VG514		2		W/2 - 93.5

***Optional**

GLASS SIZE	
2x	W/2 - 153 H - 237



ACCESSORIES		
ACGSL045	MAX 800 mm	Drainage Cap
ACUG830	1	Interlock Seal
ACUG831	1	Interlock Seal
ACUN348	2	Buffer
ACVG269...273*	1	Connecting Rods
ACVG277...279*	1	Lift and Slide Lock
ACVG280N	1	Basic Lift and Slide Kit
ACVG520	32	Chevrons
ACVG521N(S)	16	VG521N Corner Cleat
ACVG528	4+	Top Guides
ACVG531	2 Pairs	Interlock Cover Cap
ACVG534	4+	Sash Drainage Spout
ACVG557N	8	Bridge Packer
ACVG575	2+	Support for VG575
ACVG617(S)	8	Outer Frame Cleat
ACVG644	6	VG521N Vent Support
ACVL059	1 Pair	VL72 End Cap
ACVL061	W/300 + 2	VL72/VL76 Rivet
ACVS033	9H + 5W	Woolpile
Ext. Glazing Gasket	4H + 2W - 1500	'E' Gasket
Int. Glazing Gasket	4H + 2W - 1500	Wedge Gasket

***See Section B for connecting rod and lock length requirements**

***See section E for lock & handle selection**

IMPORTANT NOTE:


Maximum Sash Weights: Lift & Slide = 200kg



Do Not Scale From This Drawing


Visoglide Plus

Cutting Information - Sabinco Lift and Slide



IMPORTANT NOTE:

Maximum Sash Weights:
Lift & Slide = 200kg




PROFILES

VG618	2	W
VG618	2	H
VG521N	2	W/2 - 3
VG521N	2	H - 87
VG621	1	H - 56
VG530	1	H - 87
VG630	1	H - 56
VG553N	2	H - 87
UG852	2	H - 87
VG615	1	W/2 - 77.5
VG615	1	H - 56
VG616	1	W/2 - 91
VG5XX	2	W/2 - 143
VG5XX	2	H - 267
GL7XX	2	W / 2 - 52.5
GL7XX	2	H - 106
VG53	1	W - 94
VG52	1	W - 104
VG52	2	H - 92
VL72	1	W - 9

GLASS SIZE

Fixed	W/2 - 66.5
1x	H - 70
Sash	W/2 - 153
1x	H - 237



ACCESSORIES


ACEF010B	4	VG610/618 Corner Cleat
ACSG611B	(H + W - 200) / 300	Clip-In Adaptor
ACFT171	2	Storm Valve
ACGSL057	H + W - 200	VG610/618 Interlock Seal
ACSP057	4	VG610/618 Glass Support
ACUG631	1	VG610/618 Interlock Seal
ACUG632	1	VG610/618 Interlock Seal
ACUN348	2	Buffer
ACVG269...273*	1	Connecting Rods
ACVG277...279*	1	Lift and Slide Lock
ACVG280N	1	Basic Lift and Slide Kit
ACVG45N	MAX 800 mm	Drainage Cap
ACVG520	16	Chevron
ACVG521N(S)	8	VG521N Corner Cleat
ACVG528	4+	Top Guides
ACVG531	1 Pair	Interlock Cover Cap
ACVG534	4+	Sash Drainage Spout
ACVG557N	1	Bridge Packer
ACVG618(S)	4	VG618 Corner Cleat
ACVL020(B)	4	Chevron
ACVL029	6	Anti-Twist Clip
ACVL059	1	VL72 End Cap
ACVL061	W/300 + 2	Rivet
ACVS033	7H + 5W	Woolpile
Ext. Glazing Gasket	(1) 2H + W - 200 (2) 2H + W - 700	E-Gasket
Int. Glazing Gasket	(1) 2H + W - 200 (2) 2H + W - 700	Wedge Gasket

*See section B for connecting rod and lock length requirements

*See section E for lock & handle selection

Do Not Scale From This Drawing


Cutting Information - Sabinco Lift and Slide



IMPORTANT NOTE:

Maximum Sash Weights:

ACVG280N = 
ACVG280N & ACVG1282N = 
ACVG557N = 
ACVG644 = 
ACVG644 & ACVG645N = 



GLASS SIZE	
2x	W/2 - 153
	H - 238.5

PROFILES				
Part Number	Image	Quantity	Dimensions	Notes
VG518 (with UG050)		1		W
VG518 (with UG050)		1		H - 40
VG518 (with UG050)		1		H - 40
VG516		1		W
UG054		1		W
VG554		1		W/2 - 15.5
VG521N		4		W/2 - 3
VG521N		4		H - 88.5
VG530		1		H - 70.5
VG530		1		H - 88.5
VG553N		1		H - 73.5
VG553N		1		H - 88.5
UG852		1		H - 73.5
UG852		1		H - 88.5
VG660		2		W/2 - 18
BEAD		4		W/2 - 143
BEAD		4		H - 268.5
VG53		1		W - 94
VG52		1		W/2 - 52
VG52		2		W - 104
VG52		1		H - 104
VL72		1		W - 9
*VG514		1		H - 80.7
		1		W/2 - 101.5


***Optional**

ACCESSORIES

ACUG123L/R	1	VG516/UG050 Seal Piece
ACUG831	1	Interlock Seal
ACUN348	2	Buffer
ACVG269...273*	1	Connecting Rods
ACVG277...279*	1	Lift and Slide Lock
ACVG280N	1	Basic Lift and Slide Kit
ACVG1282N	2	Vent Support
ACVG515N	4	T. Bracket
ACVG516N	1	Support Pieces
ACVG518	1	VG516/530 End Cap
ACVG519	1	VG554 End Cap
ACVG520	28	Chevron
ACVG521N(S)	16	VG521N Corner Cleat
ACVG528	4+	Top Guides
ACVG531	1 Pair	Interlock Cover Cap
ACVG557N	8	Bridge Packer
ACVG617(S)	4	Outer Frame Cleat
ACVG644	6	VG521N Vent Support
ACVG645N	2	Vent Support
ACVL059	1	End Caps
ACVL061	W/300 + 2	Rivet
ACVS033	9H + (5 x W/2) - 150	Woolpile
Ext. Glazing Gasket	4H + 2W - 1300	'E' Gasket
Int. Glazing Gasket	4H + 2W - 1300	Wedge Gasket

***See section B for connecting rod and lock length requirements**


***See section E for lock & handle selection**



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sabinco Lift and Slide



PROFILES

VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG521N		4		W/2 - 48.5
VG521N		4		H - 87
VG537		2		H - 87
VG552N		2		H - 87
UG852		2		H - 87
BEAD		4		W/2 - 150.5
BEAD		4		H - 267
VG53		1		W - 94
VG52		1		W - 104
VG52		2		W/2 - 70.5
VG52		2		H - 92
VL72		1		W - 9
VG575		1		W/2 - 89
*VG514		1		H - 108
*VG514		2		W/2 - 69


*Optional

GLASS SIZE	
2x	W/2 - 125.5
	H - 236




ACCESSORIES

ACUG830	1	Interlock Seal
ACUG831	1	Interlock Seal
ACUN348	2	Buffer
ACVG269...273*	1	Connecting Rods
ACVG277...279*	1	Lift and Slide Lock
ACVG280N	1	Basic Lift and Slide Kit
ACVG1282N	2	Vent Support
ACVG515N	4	T. Bracket
ACVG516N	1	Support Pieces
ACVG518	1	VG516/530 End Cap
ACVG519	1	VG554 End Cap
ACVG520	28	Chevron
ACVG521N(S)	8	VG521N Corner Cleat
ACVG528	4+	Top Guides
ACVG531	2 Pairs	Interlock Cover Cap
ACVG534	4+	Sash Drainage Spout
ACVG536	1 Pair	Flat End Caps
ACVG548	8	Fixing Bracket
ACVG557N	8	Bridge Packer
ACVG575	2+	Support for VG575
ACVG617(S)	8	Outer Frame Cleat
ACVG644	6	VG521N Vent Support
ACVG645N	2	Vent Support
ACVL059	1	End Caps
ACVL061	W/300 + 2	Rivet
ACVS033	6H + 4W	Woolpile
Ext. Glazing Gasket	4H + 2W - 1485	'E' Gasket
Int. Glazing Gasket	4H + 2W - 1485	Wedge Gasket

*See section B for connecting rod and lock length requirements
*See section E for lock & handle selection




IMPORTANT NOTE:
Maximum Sash Weights:
Lift & Slide = 200kg



Do Not Scale From This Drawing

Cutting Information - Sobicco Lift and Slide



PROFILES				
VG612 (with UG050)		2		W
VG612 (with UG050)		2		H
VG521N		6		W/3 + 25
VG521N		6		H - 87
VG530		4		H - 87
VG53N		4		H - 87
UG852		4		H - 87
BEAD		6		W/3 - 135
BEAD		6		H - 267
VG53		2		W - 94
VG52		2		W - 104
VG52		2		2W/3 - 98.5
VG52		5		H - 92
VL72		1		W - 9
VG575		1		2W/3 - 117
VG575		1		W/3 - 61
*VG514		2		2W/3 - 129.5
*VG514		1		H - 108
*VG515		2		W/3 - 73.5
*VG515		1		H - 108

***Options**


GLASS SIZE	
3x	W/3 - 125
	H - 237

ACCESSORIE

ACUG830	2	Bottom Interlock Seal
ACUG831	2	Top Interlock Seal
ACUN348	4	Buffer
ACVG269...273*	2	Connecting Rods
ACVG277...279*	2	Lift and Slide Lock
ACVG280N	2	Basic Lift and Slide Kit
ACVG520	48	Chevron
ACVG521N(S)	24	VG521N Corner Cleat
ACVG528	8+	Top Guides
ACVG531	4 Pairs	Interlock Cover Cap
ACVG534	6+	Sash Drainage Spout
ACVG557N	8	Bridge Packer
ACVG575	4+	Support for VG575
ACVG617(S)	8	Outer Frame Cleat
ACVG644	6	VG521N Vent Support
ACVL059	1	End Caps
ACVL061	W/300 + 2	Rivet
ACVS033	12H + 4W	Woolpile
Ext. Glazing Gasket	6H + 2W - 2000	'E' Gasket
Int. Glazing Gasket	6H + 2W - 2000	Wedge Gasket

*See section B for connecting rod and lock length requirements

***See section E for lock & handle selection**





Do Not Scale From This Drawing

ISSUED : JULY 2019

Visoglide Plus

Cutting Information - Sabinco Lift and Slide



IMPORTANT NOTE:

Maximum Sash Weights:
Lift & Slide = 200kg

PROFILES


VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG521N		8		W/4 + 17
VG521N		8		H - 87
VG530		4		H - 87
VG553N		4		H - 87
VG542		1		H - 87
UG852		4		H - 87
BEAD		8		W/4 - 123.5
BEAD		8		H - 267
VG52		2		W - 104
VG52		2		H - 94
VG53		1		W - 94
VL72		1		W - 9
VG575		2		W/4 - 69.5
*VG514		2		W/2 - 138.5

* OPTIONAL

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACUG830	2		EPDM Plug
ACUG831	2		Interlock Seal
ACUN348	4		Buffer
ACVG240	1		Basic 4 Door L&S Kit
ACVG268	2		Guide Bracket
ACVG269...273*	2		Connecting Rods
ACVG277...279*	2		Lift and Slide Lock
ACVG280N	2		Basic Lift & Slide Kit
ACVG281N	1		Locking Point
ACVG520	56		Chevron
ACVG521N(S)	32		VG521N Corner Cleat
ACVG528	8+		Top Guides
ACVG531	4 Pairs		Interlock Cover Cap
ACVG534	8+		Sash Drainage Spout
ACVG543	1 Pair		VG542 End Caps
ACVG557N	16		Bridge Packer
ACVG575	4+		Support for VG575
ACVG617(S)	8		Outer Frame Cleat
ACVG644	12		VG521N Vent Support
ACVL059	1 Pair		VL72 End Cap
ACVL061	W/300 + 2		VL72/VL76 Rivet
ACVS033	15H + 6W		Woolpile
Ext. Glazing Gasket	8H + 2W - 1300		'E' Gasket
Int. Glazing Gasket	8H + 2W - 1300		Wedge Gasket


*See section B for connecting rod and lock length requirements
*See section E for lock & handle selection



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sabinco Lift and Slide



PROFILES

VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG521N		4		W/4 - 28.5
VG521N		4		W/4 - 28.5
VG521N		4		H - 87
VG542		1		H - 87
VG537		4		H - 87
VG552N		4		H - 87
BEAD		4		W/4 - 98.5
BEAD		4		W/4 - 99
BEAD		8		H - 267
VG53		1		W - 94
VG52		1		W - 104
VG52		2		W/2 - 70.5
VG52		2		H - 92
VL72		1		W - 9
VG575		2		W/4 - 69.5
*VG514		2		W/2 - 74

*Optional

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACUG830		2	EPDM Plug
ACUG831		2	Interlock Seal
ACUN348		4	Buffer

W

ACCESSORIES Continued

ACVG240	1	Basic 4 Door L&S Kit
ACVG268	2	Guide Bracket
ACVG269...273*	2	Connecting Rods
ACVG277...279*	2	Lift and Slide Lock
ACVG280N	2	Basic Lift & Slide Kit
ACVG281N	1	Locking Point
ACVG520	24	Chevron
ACVG521N(S)	16	VG521N Corner Cleat
ACVG528	4+	Top Guides
ACVG531	4 Pairs	Interlock Cover Cap
ACVG534	8+	Sash Drainage Spout
ACVG536	2 Pairs	Slim Interlock End Cap
ACVG543	1 Pair	VG542 End Caps
ACVG548	16	Fixing Bracket
ACVG557N	16	Bridge Packer
ACVG575	4+	Support for VG575
ACVG617(S)	8	Outer Frame Cleat
ACVG644	12	VG521N Vent Support
ACVL059	1 Pair	VL72 End Cap
ACVL061	W/300 + 2	VL72/VL76 Rivet
ACVS033	13H + 4W	Woolpile
Ext. Glazing Gasket	8H + 2W	'E' Gasket
Int. Glazing Gasket	8H + 2W	Wedge Gasket




IMPORTANT NOTE:

Maximum Sash Weights:
Lift & Slide = 200kg

Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Sabinco Lift and Slide



PROFILES

VG18 (with UG050)		2		W
VG18 (with UG050)		2		H
VG521N		12		W/6 + 38
VG521N		12		H - 87
VG530		8		H - 87
VG553N		8		H - 87
VG542		1		H - 87
UG852		8		H - 87
BEAD		12		W/6 - 102
BEAD		12		H - 267
VG52		2		W - 104
VG52		4		H - 94
VG53		2		W - 94
VL72		1		W - 9
VG575		2		W/3 - 90.5
VG575		2		W/6 - 48
*VG514		1		2W/3 - 181
*VG515		1		W/3 - 96

* OPTIONAL


GLASS SIZE		
6x	W/6 - 116	H - 237

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACVG534		MAX 800 mm	Drainage Spout
ACUG830	8		EPDM Plug
ACUG831	2		Interlock Seal
ACUN348	8		Buffer
ACVG240	1		Basic Bi Parting L&S Kit
ACVG268	4		Guide Bracket
ACVG269...273*	4		Connecting Rods
ACVG277...279*	4		Lift and Slide Lock
ACVG280N	4		Basic Lift & Slide Kit
ACVG281N	1		Locking Point
ACVG520	84		Chevron
ACVG521N(S)	48		VG521N Corner Cleat
ACVG528		MAX 1000 mm	Top Guides
ACVG531	6 Pairs		Interlock Cover Cap
ACVG534	12+		Sash Drainage Spout
ACVG543	1 Pair		VG542 End Caps
ACVG557N	20		Bridge Packer
ACVG575	8+		Support for VG575
ACVG617(S)	8		Outer Frame Cleat
ACVG644	12		VG521N Vent Support
ACVL059	1 Pair		VL72 End Cap
ACVL061	W/300 + 2		VL72/VL76 Rivet
ACVS033	23H + 4W - 1157		Woolpile
Ext. Glazing Gasket	12H + 2W - 4344		'E' Gasket
Int. Glazing Gasket	12H + 2W - 4344		Wedge Gasket

*See section B for connecting rod and lock length requirements

W





IMPORTANT NOTE:

Maximum Sash Weights:
Lift & Slide = 200kg

Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Hautau Lift and Slide



PROFILES

VG518 (with UG050)		2		W
VG518 (with UG050)		2		H
VG521N		4		W/2 - 3
VG521N		4		H - 87
VG530		2		H - 87
VG553N		2		H - 87
UG852		2		H - 87
BEAD		4		W/2 - 143
BEAD		4		H - 267
VG53		1		W - 94
VG52		1		W - 104
VG52		2		W/2 - 70.5
VG52		2		H - 92
VL72		1		W - 9
VG575		1		W/2 - 89
*VG514		1		H - 108
*VG514		2		W/2 - 93.5

*Optional

GLASS SIZE		
2x	W/2 - 153	
	H - 237	

ACCESSORIES

ACGSL045		MAX 800 mm	Drainage Cap
ACUG830		1	Interlock Seal
ACUG831		1	Interlock Seal
ACUN348		2	Buffer
ACVG520		32	Chevrons
ACVG521N(S)		16	VG521N Corner Cleat
ACVG528		4+	Top Guides
ACVG531		2 Pairs	Interlock Cover Cap
ACVG534		4+	Sash Drainage Spout
ACVG557N		8	Bridge Packer
ACVG575		2+	Support for VG575
ACVG617(S)		8	Outer Frame Cleat
ACVG644		6	VG521N Vent Support
ACVL059		1 Pair	VL72 End Cap
ACVL061		W/300 + 2	VL72/VL76 Rivet
ACVS033		9H + 5W	Woolpile
Ext. Glazing Gasket		4H + 2W - 1500	'E' Gasket
Int. Glazing Gasket		4H + 2W - 1500	Wedge Gasket

FH	Vent Height	H - 87
FW	Vent Width	W/2 - 3

LOCK COMPONENTS

ACVG1280		-	1
ACVG1277*		1877 < FH < 2176	
ACVG1278*		2177 < FH < 2476	1
ACVG1279*		2477 < FH < ...	

* See Section E for lock preparation details.


≤ 250KG VENT WEIGHT

ACVG1275		-	14
ACUG230		650 < FW < 1360	
ACUG231		1361 < FW < 1860	1
ACUG232		1861 < FW < 2360	

≤ 300KG VENT WEIGHT

ACVG1274		-	1
ACVG1275		-	18
ACUG230		1120 < FW < 1800	
ACUG231		1801 < FW < 2300	1
ACUG232		2301 < FW < 2800	
ACUG233		2801 < FW < 3235	


See Section E for handle selection



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Hautau Lift and Slide



PROFILES

VG618	2		W
VG618	2		H
VG521N	2		W/2 - 3
VG521N	2		H - 87
VG621	1		H - 56
VG530	1		H - 87
VG630	1		H - 56
VG553N	2		H - 87
UG852	2		H - 87
VG615	1		W/2 - 69.5
VG615	1		H - 56
VG616	1		W/2 - 83
VG5XX	2		W/2 - 143
VG5XX	2		H - 267
GL7XX	2		W/2 - 52.5
GL7XX	2		H - 106
VG53	1		W - 94

VG52	1	W - 104
VG52	2	H - 92
VL72	1	W - 9

ACCESSORIES

ACEF010B ACSG611B	4	VG610/618 Corner Cleat
ACFT171	(H + W - 200) / 300	Clip-In Adaptor
ACGSL057	2	Storm Valve
ACSG631	H + W - 200	VG610/618 Interlock Seal
ACSP057	4	VG610/618 Glass Support
ACUG631	1	VG610/618 Interlock Seal
ACUG632	1	VG610/618 Interlock Seal
ACUN348	2	Buffer
ACVG45N	MAX 800 mm	Drainage Cap
ACVG520	16	Chevron
ACVG521N(S)	8	VG521N Corner Cleat
ACVG528	4+	Top Guides
ACVG531	1 Pair	Interlock Cover Cap
ACVG534	2+	Sash Drainage Spout
ACVG557N	1	Bridge Packer
ACVG618(S)	4	VG618 Corner Cleat
ACVL020(B)	4	Chevron
ACVL029	6	Anti-Twist Clip
ACVL059	1	VL72 End Cap
ACVL061	W/300 + 2	Rivet
ACVS033	7H + 6W	Woolpile
Ext. Glazing Gasket	(1) 2H + W - 200 (2) 2H + W - 700	E-Gasket
Int. Glazing Gasket	(1) 2H + W - 200 (2) 2H + W - 700	Wedge Gasket

GLASS SIZE		
1x	W1 - 66.5	
	H - 70	
1x	W2 - 153	
	H - 237	

IMPORTANT NOTE:

Maximum Sash Weights:
Lift & Slide = 300kg

FH	Vent Height	H - 87
FW	Vent Width	W/2 + 38

LOCK COMPONENTS

ACVG1280	-	1
ACVG1277*	1877 < FH < 2176	
ACVG1278*	2177 < FH < 2476	1
ACVG1279*	2477 < FH < ...	

* See Section E for lock preparation details.



≤ 250KG VENT WEIGHT

ACVG1275	-	1
ACUG230	650 < FW < 1360	
ACUG231	1361 < FW < 1860	1
ACUG232	1861 < FW < 2360	

≤ 300KG VENT WEIGHT


ACVG1274	-	1
ACVG1275	-	18
ACUG230	1120 < FW < 1800	
ACUG231	1801 < FW < 2300	1
ACUG232	2301 < FW < 2800	
ACUG233	2801 < FW < 3235	

See Section E for handle selection




Do Not Scale From This Drawing

Cutting Information - Hautau Lift and Slide



PROFILES				
VG518 (with UG050)		1		W
VG518 (with UG050)		1		H - 40
VG518 (with UG050)		1		H - 40
VG516		1		W
UG054		1		W
VG554		1		W/2 - 15.5
VG521N		4		W/2 - 3
VG521N		4		H - 88.5
VG530		1		H - 70.5
VG530		1		H - 88.5
VG553N		1		H - 73.5
VG553N		1		H - 88.5
UG852		1		H - 73.5
UG852		1		H - 88.5
VG660		2		W/2 - 18
BEAD		4		W/2 - 143
BEAD		4		H - 268.5
VG53		1		W - 94



VG52		1		W/2 - 52
VG52		2		W - 104
VG52		1		H - 104
VL72		1		W - 9
*VG514		1	$\angle 87^\circ$ 88°	H - 80.7
		1		W/2 - 101.5

***Optional**

ACCESSORIES		
ACUG123L/R	1	VG516/UG050 Seal Piece
ACUG831	1	Interlock Seal
ACUN348	2	Buffer
ACVG515N	4	T. Bracket
ACVG516N	1	Support Pieces
ACVG518	1	VG516/530 End Cap
ACVG519	1	VG554 End Cap
ACVG520	28	Chevron
ACVG521N(S)	16	VG521N Corner Cleat
ACVG528	4+	Top Guides
ACVG531	2 Pairs	Interlock Cover Cap
ACVG557N	8	Bridge Packer
ACVG617(S)	4	Outer Frame Cleat
ACVG644	6	VG521N Vent Support
ACVG645N	2	Vent Support
ACVL059	1	End Caps
ACVL061	W/300 + 2	Rivet
ACVS033	9H + 5W	Woolpile
Ext. Glazing Gasket	4H + 2W - 1300	'E' Gasket
Int. Glazing Gasket	4H + 2W - 1300	Wedge Gasket

See Section E for handle selection

GLASS SIZE	
2x	W/2 - 153 H - 238.5


FH	Vent Height	H - 88.5
FW	Vent Width	W/2 - 3

LOCK COMPONENTS		
ACVG1280	-	1
ACVG1277*	$1863.5 < FH < 2162.5$	
ACVG1278*	$2163.5 < FH < 2462.5$	1
ACVG1279*	$2463.5 < FH < ...$	

* See Section E for lock preparation details.

<u>≤ 250KG VENT WEIGHT</u>		
ACVG1275	-	14
ACVG1282N	-	3
ACUG230	650 < FW < 1360	
ACUG231	1361 < FW < 1860	1
ACUG232	1861 < FW < 2360	


<u>≤ 300KG VENT WEIGHT</u>		
ACVG1274	-	1
ACVG1275	-	18
ACVG1282N	-	5
ACUG230	1120 < FW < 1800	1
ACUG231	1801 < FW < 2300	
ACUG232	2301 < FW < 2800	
ACUG233	2801 < FW < 3235	



Do Not Scale From This Drawing


Visoglide Plus

Cutting Information - Hautau Lift and Slide




PROFILES				
VG612 (with UG050)		2		W
VG612 (with UG050)		2		H
VG521N		6		W/3 + 25
VG521N		6		H - 87
VG530		4		H - 87
VG553N		4		H - 87
UG852		4		H - 87
BEAD		6		W/3 - 135
BEAD		6		H - 267
VG53		2		W - 94
VG52		2		W - 104
VG52		2		2W/3 - 98.5
VG52		5		H - 92
VL72		1		W - 9
VG575		1		2W/3 - 117
VG575		1		W/3 - 61
*VG514		2		2W/3 - 129.5
*VG514		1		88° 88° H - 108
*VG515		2		W/3 - 73.5
*VG515		1		88° 88° H - 108

*Optional



GLASS SIZE	
3x	W/3 - 125
	H - 237



ACCESSORIES		
ACUG830	2	Bottom Interlock Seal
ACUG831	2	Top Interlock Seal
ACUN348	4	Buffer
ACVG520	48	Chevron
ACVG521N(S)	24	VG521N Corner Cleat
ACVG528	8+	Top Guides
ACVG531	4	Interlock Cover Cap
ACVG534	6+	Sash Drainage Spout
ACVG557N	8	Bridge Packer
ACVG575	4+	Support for VG575
ACVG617(S)	8	Outer Frame Cleat
ACVG644	6	VG521N Vent Support
ACVL059	1	End Caps
ACVL061	W/300 + 2	Rivet
ACVS033	12H + 4W	Woolpile
Ext. Glazing Gasket	6H + 2W - 2000	'E' Gasket
Int. Glazing Gasket	6H + 2W - 2000	Wedge Gasket

IMPORTANT NOTE:

Maximum Sash Weights: Lift & Slide = 300kg

FH	Vent Height	H - 87
FW	Vent Width	W/3 + 25

LOCK COMPONENTS

LOCK COMPONENTS		
ACVG1280	-	2
ACVG1277*	1877 < FH < 2176	2
ACVG1278*	2177 < FH < 2476	2
ACVG1279*	2477 < FH <	2

* See Section E for lock preparation details.


≤ 250KG VENT WEIGHT

ACVG1275	-	2
ACUG230	650 < FW < 1360	
ACUG231	1361 < FW < 1860	2
ACUG232	1861 < FW < 2360	

≤ 300KG VENT WEIGHT

ACVG1274	-	2
ACVG1275	-	3
ACUG230	1120 < FW < 1800	
ACUG231	1801 < FW < 2300	
ACUG232	2301 < FW < 2800	
ACUG233	2801 < FW < 3235	



See Section E for handle selection



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Hautau Lift and Slide



ACCESSORIES

ACGSL045	MAX 800 mm	Drainage Cap
ACUG830	2	Sash Cleat
ACUG831	2	Interlock Seal
ACUN348	4	Buffer
ACVG268	2	Guide Bracket
ACVG520	56	Chevron
ACVG521N(S)	32	VG521N Corner Cleat
ACVG528	8+	Top Guides
ACVG531	4 Pairs	Interlock Cover Cap
ACVG534	8+	Sash Drainage Spout
ACVG543	1 Pair	VG542 End Caps
ACVG557N	16	Bridge Packer
ACVG575	4+	Support for VG575
ACVG617(S)	8	Outer Frame Cleat
ACVG644	12	VG521N Vent Support
ACVL059	1 Pair	VL72 End Cap
ACVL061	W/300 + 2	VL72/VL76 Rivet
ACVS033	15H + 6W	Woolpile
Ext. Glazing Gasket	8H + 2W - 1300	'E' Gasket
Int. Glazing Gasket	8H + 2W - 1300	Wedge Gasket

GLASS SIZE		
4x	W/4 - 133	
	H - 237	

IMPORTANT NOTE:

Maximum Sash Weights:
 Lift & Slide = 300kg

FH	Vent Height	H - 87
FW	Vent Width	W/4 + 17


LOCK COMPONENTS		
ACUG221	-	1
ACVG1240	-	1
ACVG1280	-	2
ACVG1277*	1877 < FH < 2176	2
ACVG1278*	2177 < FH < 2476	
ACVG1279*	2477 < FH < ...	

* See Section E for lock preparation details.

≤ 250KG VENT WEIGHT		
ACVG1275	-	28
ACUG230	650 < FW < 1360	
ACUG231	1361 < FW < 1860	2
ACUG232	1861 < FW < 2360	

≤ 300KG VENT WEIGHT		
ACVG1274	-	2
ACVG1275	-	36
ACUG230	1120 < FW < 1800	
ACUG231	1801 < FW < 2300	2
ACUG232	2301 < FW < 2800	
ACUG233	2801 < FW < 3235	


See Section E for handle selection



Do Not Scale From This Drawing

Visoglide Plus

Cutting Information - Vanishing Corner



ACCESSORIE

ACDV313	2	Shootbolt Ends
ACDV326	1	Finger Bolt
ACGSL045	MAX 800 mm	
ACSG012	32	Sash Cleat
ACUG143	2	Shootbolt Keep
ACUG830	4	Interlock Seal
ACUN348	4	Buffer
ACVG509/510	8	Outer Frame Cleat
ACVG520	56	Chevron
ACVG523	13	Lock Fixing Plates
ACVG528	8+	Top Guide
ACVG529	2 Set of 4	Anti Lift Block/Guide
ACVG530	4 Pairs	Interlock Cover Cap
ACVG534	8+	Sash Drainage Spout
ACVG544	12	Fixed Sash Support
ACVG545	1 Pair	Guide Block
ACVG555	4	Adjustable Rollers
ACVG559	16	Bridge Packer
ACVG576	2 x H - 87	Corner Gasket
ACVG581	1 Kit	VG580/581 End Cap
ACVG590	1 Pack	90° Corner Cleat
ACVL059	2 Pair	VL72 End Cap
ACVL061	W _a /300+W _b /300+4	VL72/VL76 Rivet
ACVL127	1 Pair	Shootbolt Rods
ACVS033	14H+4W _a +4W _b -750	Woolpile
Ext. Glazing Gasket	8H+2W _a +2W _b -1300	'E' Gasket
Int. Glazing Gasket	8H+2W _a +2W _b -1300	Wedge Gasket



***See section E for lock & handle selection**

PROFILES

VG510		2		W _a
VG510		2		W _b
VG510		2		H
VG520		4		(W _a /2) - 11
VG520		4		(W _b /2) - 11
VG520		8		H - 87
VG530		4		H - 87
VG551R		4		H - 87
VG586		4		H - 87
VG580		1		H - 130
VG581		1		H - 130
BEAD		4		(W _a /2) - 119.5
BEAD		4		(W _b /2) - 119.5
BEAD		8		H - 195
VG53		1		W _a - 66
VG53		1		W _b - 66
VG52		2		W _a - 66
VG52		2		W _b - 66
VG52		2		H - 96
VL72		1		W _a - 9
VL72		1		W _b - 9
*VG514		2		(W _a /2) - 84
*VG514		2		(W _b /2) - 84
*VG514		2		H - 104

† Mitred on Plan (one end only)

* Optional



Do Not Scale From This Drawing