

## Main Index



**Index**..... A01 - A02



### Profiles

Specification Pages..... A03 - A08  
Technical Information..... A09 - A12  
Scale Profile Drawings..... A13 - A26



### Accessories

Photos & Drawings..... B03 - B22



### Sections

Scale Elevations..... C03 - C56



### Statics

..... D01 - D04



### Construction Drawings

Crimping Details..... E03  
Drainage..... E04 - E05  
Transom/Mullion Details..... E06 - E09  
Friction Stay & Accessory Details..... E10 - E11  
Lock Details..... E12 - E13  
Glazing Details..... E14 - E15



### Sawing Tables

UL010 Cutting Information..... F03  
UL011 Cutting Information..... F04

**Updates**

DATE	PAGE	DESCRIPTION

## Specification

### GENERAL DESCRIPTION

The "Visotherm" window system described in this manual is suitable for domestic or commercial applications as replacement windows for existing buildings, and for installation into new buildings.

The system incorporates internally beaded vent frames suitable for cockspur and shootbolt locking.

The low line gaskets and extended polyamide thermal breaks help to provide excellent U Values and Window Energy Rating capable of achieving an 'A' Rating when used in conjunction with the correct double glazed unit. Please refer to the WER calculator for guidance.

Visotherm provides the option of mechanical joints using punch tooling on the outer frames & crimping corners on all sections.

#### Applications:

##### Windows:

- Fixed windows
- Side hung open out casements
- Top hung open out casements

### PROFILE SPECIFICATION

The window frame is constructed of aluminium alloy extrusion to BS EN 755-9 and BS EN 12020, extruded to 6063 T6 alloy. The internal and external extrusions are separated with a polyamide thermal break.

The external aluminium alloy extrusion is pre-treated and finished either:-

- a) Anodised to BS 3987: 1987, grade AA25 to a natural self colour.
- b) Polyester powder organic coating to BS 6496. Dual colour is available.

## Specification

### GENERAL MANUFACTURING

Outer and vent frames are made by cutting the frame profiles with accurate 45° mitred ends using Tungsten Carbide Tipped Saw Blades, operating at approximately 3000 rpm.

The outer frame corner joints can be made using mechanically fixed corner cleats by punching the corners using the relevant punch tooling shown in section E of this manual. Alternatively, all corners can be joined using the Visotherm crimping cleats to form a cold forged corner joint (made by deforming small slugs of metal into the groove of the corner cleat).

The ends of transoms and mullions are profiled to fit the frame and fixed using self-tapping screws with a small joint sealant.

On polyester powder coated finishes, great care should be taken to avoid getting gap sealer on visible surfaces and should be removed as soon as possible with a clean cloth.

Care should be exercised when using products not supplied by Smart Systems Ltd as no responsibility can be accepted.

### RECOMMENDED DESIGN LIMITATIONS

#### WINDOWS

	Top Hung Vents	Side Hung Vents
Minimum Width:	239mm	327mm
Maximum Width:	1400mm	838mm
Minimum Height:	315mm	239mm
Maximum Height:	2500mm	1400mm
Maximum Weight:	180kg	55kg

See page B15 & B16 for hardware limitations.

For advise on window sizes outside of the recommended design limitations, please contact the Technical Department at Smart Systems Ltd Tel: 01934 876100

## Specification

### WINDOW DRAINAGE

As with all dry glazed systems, it is recommended that the window system is adequately drained and ventilated. Refer to drainage details in manual, if in doubt ask The Technical Department.

### OUTER FRAME MANUFACTURING INFORMATION

The outer frame members are cut with 45° mitred ends to the overall size required, measured to the longest point of the metal.

Prior to corner crimping the centre line position of any transoms or mullions should be marked on the outer frame members. Where the transom/mullion runs right through, it should be marked out on both jambs or head and sill members in pairs to ensure accurate alignment of the sections.

Using the marked centre line, Drill the transom/mullion fixing holes using a 5mm dia. drill bit.

Corners are formed by coating the cut faces to be joined with a suitable small gap sealer. Into the mitred corner insert the cleat glue and the required corner cleats and, where required, the aluminium corner chevrons. The two mitred ends are then brought together and crimped. The small gap sealer ensures a permanent joint and guards against the ingress of moisture and joint movement. After crimping the corner joint, special care should be taken to ensure any excess sealer is removed from painted surfaces.

Transoms or mullions are cut with square ends to the sizes calculated on the cutting formula sheets. The ends are then profiled to allow them to fit into the outer frame. Special tooling is available on request to profile the end of transom/mullion.

Prior to fixing of transoms and mullions smear the cut ends with a suitable small gap sealer. After fixing, special care should be taken to ensure any excess is cleared from painted surfaces.

## Specification

### VENT

Corners are formed by coating the cut faces to be joined with a suitable gap sealer. In the mitred corner insert the cleat glue and the required corner cleats and chevrons. The mitred ends are then brought together and crimped. The small gap sealer ensures a permanent joint and guards against the ingress of moisture and joint movement. Care should be taken to ensure any excess sealer is removed from the surfaces.

The cutting sizes produce vent frames with a cavity of 17mm.

When fixing, the friction stays into both the outer and vent frame, care should be taken to ensure that holes are located on 'V' grooves in the aluminium extrusions.

### INTERNAL BEADED ADAPTOR FRAME

The internally beaded adaptor frame members are cut with 45° mitred ends to the overall size required, measured to the longest point of metal. Care should be taken when measuring and cutting the frame members as only nominal clearance is required when the assembled frame is fixed in the outer frame.

Corners are formed by coating the cut faces to be joined with a suitable small gap sealer. Into the mitred corner insert the cleat glue and a corner cleat and the required corner chevrons. The small gap sealer ensures a permanent joint and guards against the ingress of moisture and joint movements. Care should be taken to ensure any excess sealer is removed from painted surfaces.

### GLAZING

All beads are cut to suit the glazing aperture on the fully assembled window for glazing either at factory or on site as required.

### INTERNAL BEADED GLAZING

Glazing beads are fitted to openings by cutting the horizontal beads square to head and cill of each vent and reverse adaptor area. Vertical beads are cut square at both ends. Insert bottom beads and two setting blocks to ensure glass will be centralized in vertical dimension of opening (glazing blocks must be full width of cavity to fully support glass or sealed unit), then insert top bead followed by side beads. Finish glazing by insertion of internal gaskets all round.

## Specification

### Kitemark™ Certificate

No. KM 81580

BS 4873:2016 / PAS 24:2016

**Hardware - Eco Futural Aluminium Alloy System  
Casement Windows\***

Hardware Reference	Hardware Supplier	Fixing Specification	Fixing Supplier
Securistyle Defender Stays Nico Friction Hinges	Smart Systems	ACET070	Smart Systems
Securistyle Vector Hinge Protectors	Smart Systems	ACET066	Smart Systems
ERA Lock ACEF951-956	Smart Systems	Espagnolette & Keeps ACET066	Smart Systems
ACET081/ACET165 Key Locking Handles	Smart Systems	ACET069	Smart Systems
Run-Up Blocks 4 off Per Sash	*		

\*Glass retention as specified for the fixed windows.

#### Fixed Windows

Glass Retention: External: Glazing beads and Glaslok Securi-clip glazing clips  
Internal: Glazing beads

#### Multilight Windows Comprising Opening Light(s) and / or Dummy Vent(s) or Fixed Light(s)

Hardware / Fixing Requirements Are As Specified For Opening, Dummy Vent And Fixed Window Types.

## Kitemark™ Certificate

No. KM 81580










BS 4873:2016 / PAS 24:2016

### Size Limitations And Performance Characteristics Eco Futural Aluminium Alloy Window System

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area (m <sup>2</sup> ) - Maximum	Friction Stays (Up To & Incl.)	Transom / Mullion Length (mm) Inc. Frame - Maximum	Air Permeability Classification	Watertightness Classification	Resistance To Wind Classification	Exposure Category As Given In Table 1 Of BS6375-1:2009
Sash Dimensions For Windows With Approved Sash Profiles									
Projecting Top Hungs	1440	2500	-	24"	-	3	8A	A5	2000
Projecting Side Hungs	840	1440	-	16"	-	4	E1050	AE2400	2000+
Overall Dimensions For Windows With Approved Outer Frame Profiles									
Fixeds	2100	2100	4.2	-	-	3	E1050	AE	2000
Overall Dimensions For Approved Outer Frames & Transom / Mullion Profiles									
Transom / Mullion	2400	2100	3.1	-	1345	4	E1050	AE	2000

### Visotherm Window U Values

Please refer to the Smart Systems' Document L White Paper or contact the Technical Department.

Number	Picture	Page	Perim. mm	Mec. mm	I <sub>x</sub> (cm <sup>4</sup> ) wx(cm <sup>3</sup> )	I <sub>y</sub> (cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Length	Pack pr.	MF	SA	KL	HP	M
<b>UL010</b>		A13	320	75	36.76 — 8.32	3.92 — 2.56	6.5	1	✓	✓	✓	✓	✓
<b>UL011</b>		A13	336	83	40.04 — 9.12	5.52 — 3.15	6.5	1	✓	✓	✓	✓	✓
<b>UL020</b>		A14	463	114	49.58 — 10.64	10.61 — 3.03	6.5	1	✓	✓	✓	✓	✓
<b>UL023</b>		A14	486	117	50.33 — 10.64	12.49 — 3.53	6.5	1	✓	✓	✓	✓	✓
<b>UL030</b>		A15	381	108	42.83 — 8.89	8.2 — 2.38	6.5	1	✓	✓	✓	✓	✓
<b>UL031</b>		A15	381	108	48.34 — 10.26	8.22 — 2.38	6.5	1	✓	✓	✓	✓	✓
<b>UL032</b>		A16	480	207	117.87 — 16.13	12.39 — 3.59	6.5	1	✓	✓	✓	✓	✓
<b>UL033</b>		A16	480	207	129.25 — 18.36	12.41 — 3.6	6.5	1	✓	✓	✓	✓	✓
<b>UL040</b>		A17	292	50	33.0 — 7.53	2.88 — 1.77	6.5	1	✓	✓	✓	✓	✓
A = Outside B = Inside									MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour M = Dual Colour				

Number	Picture	Page	Perim. mm	Mec. mm	$I_x(\text{cm}^4)$ $wx(\text{cm}^3)$	$I_y(\text{cm}^4)$ $wy(\text{cm}^3)$	Length	Pack pr.	MF	SA	KL	HP	M
<b>UL043</b>		A17	315	54	33.97 — 7.53	3.82 — 2.18	6.5	1	✓	✓	✓	✓	✓
<b>UL045</b>		A17	345	87	31.78 — 6.49	3.59 — 1.58	6.5	1	✓	✓	✓	✓	✓
<b>UL048</b>		A18	428	161	67.01 — 14.96	67.01 — 17.59	6.5	1	✓	✓	✓	✓	✓
<b>UL050</b>		A24	423	184	168.01 — 21.16	6.22 — 3.42	6.5	1	✓	✓	✓	✓	✓
<b>UL051</b>		A24	503	224	330.03 — 32.58	8.14 — 4.55	6.5	1	✓	✓	✓	✓	✓
<b>UL055</b>		A18	224	37	26.65 — 6.66	1.29 — 1.13	6.5	1	✓	✓	✓	✓	✓
<b>UL056</b>		A23	300	71	38.49 — 9.62	5.74 — 3.15	6.5	1	✓	✓	✓	✓	✓
<b>UL063</b>		A19	143	64	- — -	- — -	6.5	1	✓	✓	✓	✓	
<b>UL064</b>		A19	136	60	- — -	- — -	6.5	1	✓	✓	✓	✓	



A = Outside  
B = Inside

MF = Mill Finish  
SA = Silver Anodised  
KL = Basic Colour  
HP = Special Colour  
M = Dual Colour

Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	Iy(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Length	Pack pr.	MF	SA	KL	HP	M
<b>UL065</b>		A19	129	57	-	-	6.5	1	✓	✓	✓	✓	
<b>UL066</b>		A19	118	51	-	-	6.5	1	✓	✓	✓	✓	
<b>UL067</b>		A20 & A21	111	46	-	-	6.5	1	✓	✓	✓	✓	
<b>UL068</b>		A20 & A21	102	41	-	-	6.5	1	✓	✓	✓	✓	
<b>UL069</b>		A22	87	37	-	-	6.5	1	✓	✓	✓	✓	
<b>UL074</b>		A22	137	59	-	-	6.5	1	✓	✓	✓	✓	
<b>UL075</b>		A23	134	51	-	-	6.5	1	✓	✓	✓	✓	
<b>UL076</b>		A22	124	51	-	-	6.5	1	✓	✓	✓	✓	
<b>UL077</b>		A23	122	45	-	-	6.5	1	✓	✓	✓	✓	

A = Outside  
B = Inside


MF = Mill Finish  
SA = Silver Anodised  
KL = Basic Colour  
HP = Special Colour  
M = Dual Colour

Number	Picture	Page	Perim. mm	Mec. mm	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	Iy(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Length	Pack pr.	MF	SA	KL	HP	M
<b>UN500</b>		A25	137.3	-	- -	- -	6.5	1	✓	✓	✓	✓	
<b>UN501</b>		A25	135.9	45	- -	- -	6.5	1	✓	✓	✓	✓	
<b>UN510</b>		A25	374.5	113	12.2 — 3.8	9.5 — 4.8	6.5	1	✓	✓	✓	✓	
<b>UN511</b>		A25	394.4	113.1	12.9 — 4.0	11.6 — 5.1	6.5	1	✓	✓	✓	✓	
<b>UTL080</b>		A25	139.2	139.2	8.2 — 4.1	5.1 — 3.4	6.5	1	✓				
									A = Outside B = Inside	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour M = Dual Colour			


Primary Visible Side

Secondary Visible Side

**UL010**  
Slim Outer Frame



**UL011**  
Outer Frame




Scale 1:1

Primary Visible Side

Secondary Visible Side


## UL020

Internally Beaded Sash



## UL023

Internally Beaded  
Chamfered Sash




Scale 1:1


Primary Visible Side

Secondary Visible Side

**UL030**  
Transom/Mullion



**UL031**  
Transom/Mullion  
with Screwport




Scale 1:1

Primary Visible Side

Secondary Visible Side


## UL032

### Reinforced Transom/Mullion



## UL033

### Reinforced Transom/Mullion with Screwport




Scale 1:1


Primary Visible Side

Secondary Visible Side


**UL040**  
Reverse Adaptor



**UL043**  
Chamfered Reverse  
Adaptor



**UL045**  
Reverse Adaptor For  
Opening Sash




Scale 1:1


Primary Visible Side

Secondary Visible Side


**UL048**  
**90° Corner Post**



**UL055**  
**Coupler**




Scale 1:1




Scale 1:1

Primary Visible Side


Secondary Visible Side



**UL067**  
40-43mm Glazing Bead




**UL068**  
45-48mm Glazing Bead



**UL069**  
49-52mm Glazing Bead


Scale 1:1




Scale 1:1

Primary Visible Side


Secondary Visible Side



**UL069**  
41-44mm Glazing Bead



**UL074**  
26-29mm Glazing Bead




**UL076**  
36-39mm Glazing Bead


Scale 1:1

Primary Visible Side

Secondary Visible Side




**UL075**  
28mm Glazing Bead




**UL077**  
34mm Glazing Bead

**UL056**  
35mm Head Extension




Scale 1:1




Primary Visible Side

Secondary Visible Side

**UN500**  
UN510 Cover Cap




**UN510**  
Reinforcement Profile




**UN510**  
End Cap:  
ACUN500

**UN501**  
UN511 Cover Cap




**UN511**  
Reinforcement Profile



**UN511**  
End Cap:  
ACUN501

**UTL080**  
Reinforcement Profile



Scale 1:1

Primary Visible Side


Secondary Visible Side

Scale 1:1


**Section B**

**Accessories**

**Photos & Drawings**



## Countersunk Screws




Gauge	'D' (mm)
No.6	3.5
No.7	3.8
No.8	4
No.10	5
No.12	6


Part Number	Gauge	X	Length	Description	Box Qty.
ACUN3530	No.6	X	5/8" (16mm)	Countersunk Pozi Self Tapper S/S	100
MUA025SSZ	No.6	X	1" (25mm)	Countersunk Pozi Self Tapper S/S	100
ACET067	No.7	X	1/2" (12mm)	Countersunk Pozi Self Tapper S/S	100
ACET060	No.7	X	1" (25mm)	Countersunk Pozi Self Tapper S/S	100
ACET066	No.7	X	1 1/2" (40mm)	Countersunk Pozi Self Tapper S/S	100
MUA067SSZ	No.7	X	2" (50mm)	Countersunk Pozi Self Tapper S/S	100
ACET064	No.8	X	5/8" (16mm)	Countersunk Pozi Self Tapper S/S	100
ACUN3512	No.8	X	1 1/4" (30mm)	Countersunk Pozi Self Tapper S/S	100
ACUN3513	No.8	X	1 3/4" (45mm)	Countersunk Pozi Self Tapper S/S	100
ACET072	No.8	X	2 1/2" (60mm)	Countersunk Pozi Self Tapper S/S	100
ACET048	No.10	X	3/8" (10mm)	Countersunk Pozi Self Tapper S/S	100
ACIM062	No.10	X	1 1/4" (30mm)	Countersunk Pozi Self Tapper S/S	100
ACET062	No.10	X	2" (50mm)	Countersunk Pozi Self Tapper S/S	100
ACET076	No.10	X	2 1/2" (60mm)	Countersunk Pozi Self Tapper S/S	100

## POLYAMIDE SCREWS

Part Number	Gauge	X	Length	Description	Box Qty.
ACET490	4.3mm	X	16mm	Countersunk PH2 Polyamide Screw	1000
ACET290	4.3mm	X	20mm	Countersunk PH2 Polyamide Screw	100
ACET390	4.3mm	X	25mm	Countersunk PH2 Polyamide Screw	200
ACET190	4.3mm	X	45mm	Countersunk PH2 Polyamide Screw	1000
ACVS062	4.3mm	X	65mm	Countersunk PH2 Polyamide Screw	1000

 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	 Screw (Grub)	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black	 

## Pan Head Screws




Gauge	'D' (mm)
No.6	3.5
No.7	3.8
No.8	4
No.10	5
No.12	6

Part Number	Gauge	X	Length	Description	Box Qty.
ACET068	No.8	X	3/8" (10mm)	Pozi Flange AB	100
ACET063	No.8	X	1/2" (12mm)	Pan Head Self Tapper	100
ACET070	No.8	X	1/2" (12mm)	Pozi Flange Self Tapper S/S	100
ACUN3535	No.8	X	5/8" (16mm)	Pan Head Pozi S/S	100
ACET099	No.8	X	3/4" (20mm)	Pozi Flange Self Tapper S/S	100
ACDR050	4.8mm	X	32mm	Pan Head Pozi S/S	200
PUA028	No.10	X	1" (25mm)	Pan Head Pozi S/S	100
ACDR052	No.10	X	2" (50mm)	Pan Head Self Tapper S/S	200
ACET079	No.10	X	2 1/2" (60mm)	Pan Head Pozi S/S	100
ACW20160	No.12	X	1" (25mm)	Flange Head Self Tapper S/S	100
ACMC109	6.3mm	X	38mm	DIN7981 - Pan Head Self Tapper	200

 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	 Screw (Grub)	<b>MF</b> = Mill Finish <b>WP</b> = White <b>SA</b> = Silver Anodised <b>BL</b> = Black <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	

## Machine Screws



Thread	'D' (mm) Nominal
M4	4
M5	5
M6	6
M8	8
M10	10

Part Number	Thread	X	Length	Description	Box Qty.
ACET122	M4	X	10	CSK Pozi Machine Screw	100
ACET123	M4	X	20	CSK Pozi Machine Screw	100
ACDV264	M4	X	35	CSK Pozi Machine Screw	100
ACSG071	M4	X	40	CSK Pozi Machine Screw	100
ACDV266	M4	X	45	CSK Pozi Machine Screw	100
ACDV262	M4	X	50	CSK Pozi Machine Screw	100
ACDV265	M4	X	60	CSK Pozi Machine Screw	100
ACDR051	M5	X	10	CSK Pozi Machine Screw	100
ACET069	M5	X	12	CSK Pozi Machine Screw	100
HEA132	M5	X	16	CSK Pozi Machine Screw	100
WCA134	M5	X	20	CSK Pozi Machine Screw	100
WCA143	M5	X	25	CSK Pozi Machine Screw	50
ACVS061	M5	X	40	CSK Pozi Machine Screw	100
ACET133	M5	X	50	CSK Pozi Machine Screw	100
ACET220	M5	X	60	CSK Pozi Machine Screw	100
ACET238	M5	X	70	CSK Pozi Machine Screw	100
ACMX861	M5	X	80	DIN965 - CSK Machine Screw	10
ACMX862	M5	X	90	DIN965 - CSK Machine Screw	10
ACUN3503	M6	X	10	CSK Socket Machine Screw	24
ACUN3501	M6	X	13	CSK Flange Socket Machine Screw	48
ACMX852	M6	X	16	DIN965 - CSK Machine Screw	10
HEA390	M6	X	16	CSK Socket Machine Screw	32
ACET235	M6	X	60	CSK Pozi Machine Screw	100
ACET237	M6	X	70	CSK Pozi Machine Screw	100

T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black	

## Glazing Gaskets

### Retaining Gasket

Commonly known as an E Gasket.  
Retaining gaskets create a seal between the Glass and the Aluminium Profile.

Thickness	Low Line			High Line			Part number
	5mm	4mm	4mm	2mm	3mm	4mm	
							ACVG231
							200m
							BL
							ACVG31
							200m
							BL
							ACVG131
							100m
							BL
							ACET843
							200m
							BL
							ACET842
							200m
							BL
							ACET841
							200m
							BL
							ACET835
							200m
							BL
							ACVG131N
							100m
							BL
							ACUN3065
							100m
							BL

Thickness	Drawing 1:1	Part number		
		Coil length		
		Available Colours		

### Wedge Gasket

Wedge Gaskets help to hold the bead in place by providing tension between the bead and the glazing unit.

Thickness	Low Line			High Line			Part number
	5mm	5mm - 4mm	4mm - 3mm	6mm	6mm	5mm	
							ACVG32
							100m
							BL
							ACVG32N
							100m
							BL
							ACVG33
							100m
							BL
							ACVG33N
							100m
							BL
							ACVG34
							100m
							BL
							ACVG34N
							100m
							BL
							ACVG340
							100m
							BL
							ACVG340N
							100m
							BL
							ACW20038
							50m
							BL
							ACET848
							200m
							BL
							ACET840N
							200m
							BL

Image	Part Code	Pack	Unit	Application	Colour
	<b>ACET045</b> Stainless Steel Chevrons	100	pack	<b>UL020</b> <b>UL023</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACET050</b> Internal Coner Cleat	24	pack	<b>UL040</b> <b>UL043</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACET131</b> PVC Drainage Cap	100	pack		MF SA KL HP SSC SMC WP ✓ BL ✓ PC
	<b>ACET432</b> Colour Match Drainage Cover Cap	8	pack		MF SA KL ✓ HP ✓ SSC SMC WP ✓ BL ✓ PC
	<b>ACET461</b> Inline Espag Handle with 15mm Spindle	1	Each	<b>ACUL001-6</b>	MF SA KL ✓ HP ✓ SSC ✓ SMC ✓ WP ✓ BL ✓ PC ✓
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm		<b>MF</b> = Mill Finish <b>WP</b> = White <b>SA</b> = Silver Anodised <b>BL</b> = Black <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome		 	






Image	Part Code	Pack	Unit	Application	Colour
	<b>ACET466 L/R</b>  Cranked Espag Handle with 15mm Spindle	1	Each	<b>ACUL001-6</b>	MF SA KL ✓ HP ✓ SSC ✓ SMC ✓ WP ✓ BL ✓ PC ✓
	<b>ACET516</b>  16mm Cavity Hinge Protector  4 Per Set (2 pairs)	50	sets		MF SA KL HP SSC SMC WP BL PC
	<b>ACET616</b>  Crimping Cleat	24	pack	<b>UL045</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACET652</b>  Pull-In Blocks	50	pack		MF SA KL HP SSC SMC WP BL PC
	<b>ACET855</b>  Insulation	100	m		MF SA KL HP SSC SMC WP BL PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black			
					

Image	Part Code	Pack	Unit	Application	Colour
	ACGT062 5mm Flipper Gasket	150	m	UL020 UL023	MF SA KL HP SSC SMC WP BL PC
	ACINS09 Cam adjustment device for sterling hinge	25	pairs		MF SA KL HP SSC SMC WP BL PC
	ACSM022SS L/R 15mm Spindle Espag Handle. Spindle & fixings provided Includes M4 Long Ball Point Allen Key for locking	1	each	ACUL001-6	MF SA KL HP SSC SMC WP BL PC
	ACSM050 Inline Architectural Espag Handle with 15mm Spindle	1	Each	ACUL001-6	MF SA KL HP SSC SMC WP ✓ BL ✓ PC ✓
	ACUL011 Outer Frame Crimping Cleat	24	pack	UL010	MF SA KL HP SSC SMC WP BL PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	Screw (Grub)	<b>MF</b> = Mill Finish <b>WP</b> = White <b>SA</b> = Silver Anodised <b>BL</b> = Black <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome		 	

# Visotherm Window

ACCESSORIES : PHOTOS & DRAWINGS

Image	Part Code	Pack	Unit	Application	Colour
	ACUL013 Outer Frame Crimping Cleat	24	pack	UL011	MF SA KL HP SSC SMC WP BL PC
	ACUL020 Sash Outer Crimping Cleat	24	pack	UL020 UL023	MF SA KL HP SSC SMC WP BL PC
	ACUL021 Sash Inner Crimping Cleat	24	pack	UL020 UL023	MF SA KL HP SSC SMC WP BL PC
	ACUL025 Anti-Twist Clip	100	pack	UL030 UL031 UL032 UL033	MF SA KL HP SSC SMC WP BL PC
	ACUL030A External Transom/Mullion Bracket	24	pack	UL030 UL032	MF SA KL HP SSC SMC WP BL PC
	MF = Mill Finish SA = Silver Anodised KL = Basic Colour HP = Special Colour SSC = Smooth Satin Chrome SMC = Smokey Chrome PC = Polished Chrome				

Image	Part Code	Pack	Unit	Application	Colour
	<b>ACUL030B</b>  Internal Transom/Mullion Bracket	24	pack	<b>UL030</b> <b>UL032</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL032</b>  End Cap (Black Only)	20	pack	<b>UL032</b> <b>UL033</b>	MF SA KL HP SSC SMC WP BL ✓ PC
	<b>ACUL040</b>  External Crimping Cleat	24	pack	<b>UL040</b> <b>UL043</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL050</b>  Cast Cill End Cap	10	pair	<b>UL050</b>	MF SA KL ✓ HP ✓ SSC SMC WP ✓ BL ✓ PC
	<b>ACUL051</b>  Cast Cill End Cap	10	pair	<b>UL051</b>	MF SA KL ✓ HP ✓ SSC SMC WP ✓ BL ✓ PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	<b>ACUL050</b> <b>ACUL051</b> Screw (Grub)	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome		 	

# Visotherm Window

ACCESSORIES : PHOTOS & DRAWINGS

Image	Part Code	Pack	Unit	Application	Colour
	<b>ACUL057</b> <b>Sash Guide</b>	100	pack	<b>UL020</b> <b>UL023</b>	MF SA KL HP SSC SMC WP ✓ BL ✓ PC
	<b>ACUL058</b> <b>Bridge Packer</b>	12	pack	<b>UL010</b> <b>UL011</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL059</b> <b>Bridge Packer</b>	12	pack	<b>UL020</b> <b>UL023</b> <b>UL040</b> <b>UL043</b>	MF SA KL HP SSC SMC WP BL ✓ PC
	<b>ACUL060</b> <b>Foam</b>	1	each	<b>UL010</b> <b>UL030</b> <b>UL031</b> <b>UL032</b> <b>UL033</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL061</b> <b>Foam</b>	1	each	<b>UL011</b>	MF SA KL HP SSC SMC WP BL PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black	 		


Image	Part Code	Pack	Unit	Application	Colour
	<b>ACUL062</b> Glazing Foam	1	each	<b>UL020</b> <b>UL023</b> <b>UL040</b> <b>UL043</b> <b>UL030</b> <b>UL031</b> <b>UL032</b> <b>UL033</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL063</b> Foam	1	each	<b>UL020</b> <b>UL023</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL901</b> Vee Block	1	Each	<b>UL010</b> <b>UL011</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL902</b> Crimping Punches	1	Pair	<b>UL010</b> <b>UL011</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL903</b> Vee Block	1	Each	<b>UL020</b>	MF SA KL HP SSC SMC WP BL PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black			

Image	Part Code	Pack	Unit	Application	Colour
	<b>ACUL904</b> <b>Crimping Punches</b>	1	Pair	<b>UL020</b> <b>UL023</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL906</b> <b>Vee Block</b>	1	Each	<b>UL040</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL907</b> <b>Crimping Punches</b>	1	Pair	<b>UL040</b> <b>UL043</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL908</b> <b>Vee Block</b>	1	Each	<b>UL043</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL909</b> <b>Packer for ACUL908</b>	1	Each	<b>UL043</b>	MF SA KL HP SSC SMC WP BL PC
 	<b>MF</b> = Mill Finish <b>WP</b> = White <b>SA</b> = Silver Anodised <b>BL</b> = Black <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome				

Image	Part Code	Pack	Unit	Application	Colour
	<b>ACUL910</b> Packer for ACUL911	1	Each	<b>UL023</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL911</b> Vee Block	1	Each	<b>UL020</b> <b>UL023</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL990</b> Friction Hinge Drill Jig	1	Each	<b>UL020</b> <b>UL023</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUL992</b> Transom/Mullion Drill Jig	1	Each	<b>ACUL030A</b> <b>ACUL030B</b> <b>UL030</b> <b>UL031</b> <b>UL032</b> <b>UL033</b>	MF SA KL HP SSC SMC WP BL PC
	<b>WCA106</b> Stainless Steel Chevrons	50	pack	<b>UL020</b> <b>UL023</b> <b>UL040</b> <b>UL043</b>	MF SA KL HP SSC SMC WP BL PC
 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black			


Image	Part Code	Pack	Unit	Application	Colour
	<b>WUT024HSZA</b>  <b>Manual Crimper</b>  <b>Note: Vee blocks &amp; punches are sold separately</b>	1	Each		MF SA KL HP SSC SMC WP BL PC
	<b>ACUN500</b>  <b>Cover plate</b>	1	each	<b>UN500</b> <b>UN501</b>	MF SA KL HP SSC SMC WP BL PC
	<b>ACUN501</b>  <b>Cover plate</b>	1	each	<b>UN500</b> <b>UN511</b>	MF SA KL HP SSC SMC WP BL PC
					MF ✓ SA KL HP SSC SMC WP BL PC
					MF SA KL HP SSC SMC WP BL PC
					MF SA KL HP SSC SMC WP BL PC
  T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	<b>Screw (Grub)</b>  <b>MF = Mill Finish</b> <b>SA = Silver Anodised</b> <b>KL = Basic Colour</b> <b>HP = Special Colour</b> <b>SSC = Smooth Satin Chrome</b> <b>SMC = Smokey Chrome</b> <b>PC = Polished Chrome</b>				

## Locking



Part Code	Rod Length (mm)	Number of Keeps	Sash Rebate Size ('A')	
			Minimum	Maximum
ACUL001	200	1	200	400
ACUL002	400	2	400	600
ACUL003	600	2	600	800
ACUL004	800	3	800	1000
ACUL005	1000	3	1000	1200
ACUL006	1200	3	1200	1400


Please Note: ACUL001-006 Locks require handles with a 15mm spindle length.



For more information refer to Section E

 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>	 <small>Screw (Grub)</small>	<b>MF</b> = Mill Finish <b>WP</b> = White <b>SA</b> = Silver Anodised <b>BL</b> = Black <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	

## Friction Hinge Stays



Hinge Code Top Hung	Hinge Length (mm)	Max Vent Weight (kg)	Min Vent Height (mm)	Max Vent Height (mm)	Opening Angle (+/-2.5°)
<b>ACINS10</b>	262	40	315	640	50
<b>ACINS12</b>	313	50	640	800	50
<b>ACINS16</b>	415	65	800	1100	50
<b>ACINS22</b>	567	100	1090	1500	45
<b>ACINS22W</b>	567	100	1500	2000	20
<b>ACINS26</b>	680	180	2000	2500	20
Side Hung	Hinge Length (mm)	Max Vent Weight (kg)	Min Vent Width (mm)	Max Vent Width (mm)	Opening Angle (+/-2.5°)
<b>ACINSSH10</b>	262	38	327	660	85
<b>ACINSSH16</b>	415	55	450	838	60

**Please Note:**

- Dimensions shown in table are sash sizes - not rebate sizes.
- The minimum sash sizes for ACINS10 & ACINSSH10 can both be reduced to 281mm where cockspur handles are used.
- Top hung height & side hung width sizes to be reduced by 2mm where size is 450mm or smaller.
- Vents of 100kg must be fitted with ACINS09 cam adjustment devices, which are optional on lighter vents
- Separate restrictors (ACINS30 & ACINS31) vent holding devices may be required to hold large vents in a selected ventilation position against variable wind pressure.

 <small>T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm</small>		<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black	 

# Visotherm Window

Image	Part Code	Pack	Unit	Application	Colour
	ACMX09700 <b>Alu. Polish</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09761 <b>Maxi Gloss</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09762 <b>Alu. Bright</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09763 <b>Teflon Spray</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09764 <b>Maxi Clean</b>	1	each		MF SA KL HP SSC SMC WP BL PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black		 	

# Visotherm Window

Image	Part Code	Pack	Unit	Application	Colour
	ACMX09765 <b>Alu. Cleaner</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09770 <b>Roll &amp; Wrap 100mm</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09775 <b>Grip Handwrap</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09801 <b>Protective Tape 50mm</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACMX09802 <b>Protective Tape 70mm</b>	1	each		MF SA KL HP SSC SMC WP BL PC
 T-BARS ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>W</b> = White <b>BL</b> = Black		 	
	Screw (Grub)				

# Visotherm Window

Image	Part Code	Pack	Unit	Application	Colour
	<b>ACMX09803</b> <b>Protective Tape 100mm</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	<b>ACSL04</b> <b>Sealing Glue</b> <b>Order with suffix of KL colour (eg.ACSIL04KL005) or BL=Black/WP=White/ CL=Clear</b>	1	each		MF SA KL ✓ HP SSC SMC WP ✓ BL ✓ PC
	<b>ACSL05</b> <b>Rubber Sealant</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	<b>ACSL08</b> <b>Silicon Gun</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	<b>ACSL013</b> <b>Glue for Mitre</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	<b>T-BARS</b> ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm  <b>Screw (Grub)</b>	<b>MF</b> = Mill Finish <b>WP</b> = White <b>SA</b> = Silver Anodised <b>BL</b> = Black <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome		 	

Image	Part Code	Pack	Unit	Application	Colour
	ACSILO14 <b>Anti-Corrosion Coating</b>	1	each		MF SA KL HP SSC SMC WP BL PC
	ACUN3900 <b>Gasket Roller</b>	1	each		MF SA KL HP SSC SMC WP BL PC
					MF SA KL HP SSC SMC WP BL PC
	<b>T-BARS</b> ACVG65=2.5mm ACVG66=3.0mm ACVL150=4.0mm  <b>Screw (Grub)</b>	<b>MF</b> = Mill Finish <b>SA</b> = Silver Anodised <b>KL</b> = Basic Colour <b>HP</b> = Special Colour <b>SSC</b> = Smooth Satin Chrome <b>SMC</b> = Smokey Chrome <b>PC</b> = Polished Chrome	<b>WP</b> = White <b>BL</b> = Black		


**Section C**

**Sections**

**Scale Elevations**




**Detail**






**Do Not Scale From This Drawing**

**Detail 1A**




**Do Not Scale From This Drawing**

Detail 1B





Do Not Scale From This Drawing

Detail 1C




Do Not Scale From This Drawing

**Detail 1D**





**Do Not Scale From This Drawing**

Detail 1E




Do Not Scale From This Drawing

**Detail 1F**





**Do Not Scale From This Drawing**

**Detail 1G**




**Do Not Scale From This Drawing**

**Detail 1H**




**Do Not Scale From This Drawing**

**Detail 2A**




**Do Not Scale From This Drawing**

**Detail 2B**




**Do Not Scale From This Drawing**

Detail 2C





Do Not Scale From This Drawing

**Detail 2D**





**Do Not Scale From This Drawing**

Detail 2E





Do Not Scale From This Drawing

**Detail 3A**




**Do Not Scale From This Drawing**

Detail 3B






Do Not Scale From This Drawing

**Detail 3C**





**Do Not Scale From This Drawing**

Detail 3D





Do Not Scale From This Drawing

**Detail 3E**





**Do Not Scale From This Drawing**

**Detail 3F**




**Do Not Scale From This Drawing**

**Detail 4A**





**Do Not Scale From This Drawing**

**Detail 4B**




**Do Not Scale From This Drawing**

**Detail 4C**




**Do Not Scale From This Drawing**

Detail 4D





Do Not Scale From This Drawing

**Detail 4E**



**Do Not Scale From This Drawing**



**Detail 5A**



**Note: Transoms will also drain through the join to the outerframe**

**Do Not Scale From This Drawing**


**Detail 5B**



**Note: Transoms will also drain through the join to the outerframe**

**Do Not Scale From This Drawing**


Detail 6A



Note: Transoms will also drain through the join to the outerframe

Do Not Scale From This Drawing


**Detail 6B**



**Note: Transoms will also drain through the join to the outerframe**

**Do Not Scale From This Drawing**


Detail 6C



Note: Transoms will also drain through the join to the outerframe


Do Not Scale From This Drawing

**Detail 6D**



Do Not Scale From This Drawing


**Detail 7A**



**Note: Transoms will also drain through the join to the outerframe**

**Do Not Scale From This Drawing**


Detail 7B



Note: Transoms will also drain through the join to the outerframe


Do Not Scale From This Drawing

Detail 8A




Do Not Scale From This Drawing

**Detail 8B**




Do Not Scale From This Drawing

Detail 8C






Do Not Scale From This Drawing

Detail 8D






Do Not Scale From This Drawing

Detail 9A






Do Not Scale From This Drawing

**Detail 9B**






**Do Not Scale From This Drawing**

Detail 9C





Do Not Scale From This Drawing

**Detail 9D**




Do Not Scale From This Drawing

**Detail 9E**






**Do Not Scale From This Drawing**

**Detail 9F**




**Do Not Scale From This Drawing**

Detail 10A





Do Not Scale From This Drawing

**Detail 10B**






**Detail 10C**




**Do Not Scale From This Drawing**

**Detail 10D**




Do Not Scale From This Drawing

Detail 11A





Do Not Scale From This Drawing

**Detail 11B**




Do Not Scale From This Drawing

Detail 12A






Do Not Scale From This Drawing

Detail 12B






Do Not Scale From This Drawing

Detail 12C



Do Not Scale From This Drawing

**Detail 12D**



**Do Not Scale From This Drawing**

**Detail**


**Do Not Scale From This Drawing**

## **Section D**

### **Statics**

**General Size Limitations are shown on Page A02.**


**For Wind Loading Limitations, Please Contact  
The Technical Department - T: 01934 833100**



The position of the axes is an indication for the use and application of the moments of inertia ( $I_x$  and  $I_y$ ) and the section modulus ( $W_x$  and  $W_y$ ). We always choose the values of the axis perpendicular to the load to resist it.

- To resist the wind loads we use the values  $I_x$  and  $W_x$ .

## EXAMPLE



- 1) Determine  $I_{xx}$  value for the stiles (if required) using the Specification Wizard

$$I_{xx} = 47.5 \text{ cm}^4$$

- 2) Determine suitability


OK

Number	Picture	$I_x(\text{cm}^4)$ $w_x(\text{cm}^3)$	$I_y(\text{cm}^4)$ $w_y(\text{cm}^3)$
UL030		42.83 --- 8.89	8.2 --- 2.38
UL031		48.34 --- 10.26	8.22 --- 2.38

## Section D

### Moments of Inertia Table

Reinforcement profiles shall be fixed at a maximum of 300mm centres and 100mm in from each end




Please consider potential hardware clashes or access issues where using reinforcement profile.

Reinforcement Internally		Without Reinforcement		UN510		UN510 + UTL080		UN511		UN511 + UTL080	
Section		Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	Iy(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	Iy(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	Iy(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	Iy(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	Iy(cm <sup>4</sup> ) wy(cm <sup>3</sup> )
UL030		42.83 — 8.89	8.2 — 2.38	112.24 — 15.46	17.67 — 5.12	152.65 — 18.07	22.75 — 6.59	114.6 — 15.61	19.71 — 5.71	153.86 — 18.14	24.79 — 7.19
UL031		48.34 — 10.26	8.22 — 2.38	123.49 — 17.59	17.69 — 5.13	169.4 — 20.58	22.77 — 6.6	126.17 — 17.77	19.73 — 5.72	170.78 — 20.68	24.81 — 7.19

## Moments of Inertia Table

Reinforcement & coupled profiles shall be fixed at a maximum of 300mm centres and 100mm in from each end




Reinforcement Internally		Without Reinforcement		UN510		UN510 + UTL080		UN511		UN511 + UTL080	
Section		Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	ly(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	ly(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	ly(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	ly(cm <sup>4</sup> ) wy(cm <sup>3</sup> )	Ix(cm <sup>4</sup> ) wx(cm <sup>3</sup> )	ly(cm <sup>4</sup> ) wy(cm <sup>3</sup> )
UL010 & UL055		100.1 — 23.38	49.33 — 9.24	213.3 — 27.07	74.09 — 12.8	299.92 — 44.04	79.17 — 13.67	218.16 — 27.93	76.13 — 13.15	302.94 — 44.22	81.21 — 14.03
UL011 & UL055		106.7 — 24.95	64.62 — 11.16	204.98 — 26.28	58.8 — 11.01	288.49 — 41.75	63.88 — 11.96	209.69 — 27.13	60.84 — 11.39	291.35 — 41.92	65.92 — 12.34

**Section E****E** **UL****Construction Drawings**

Crimping Details.....	E03
Drainage.....	E04 - E05
Transom/Mullion Details.....	E06 - E09
Friction Stay & Accessory Details.....	E10 - E11
Lock Details.....	E12 - E13
Glazing Details.....	E14 - E15



Crimping Details





**Manual Crimper = WUT024HSZA**




Do Not Scale From This Drawing

## Visotherm Window


### Drainage Details





Transoms will also drain through the join to the outerframe



**Important Note:** All exposed aluminium should be coated using ACSIL014 or painted to match the frame.




**Note:** Transoms will drain through the join to the outerframe.



**Do Not Scale From This Drawing**

## Sub Cill Drainage



Do Not Scale From This Drawing


## Visotherm Window

### Mullion/Transom Detail


#### Important Fabrication Note:

When end milling, do NOT clamp directly onto the thermal break.


**UL030**




**ACUL992**



Clamp ACUL992 jig in position and drill 2 x 3mm holes. Remove jig and open holes to Ø5mm







**UL030**





Do Not Scale From This Drawing



Mullion/Transom Detail



Do Not Scale From This Drawing


**Visotherm Window****Mullion/Transom Detail****Do Not Scale From This Drawing**

Mullion/Transom Detail




## Visotherm Window

### Friction Stay Accessories



**Vent Sizes 450mm or Smaller  
to be Reduced by 2mm**



### Heavy Duty (Sterling) Stays

Hinge Code Top Hung	Hinge Length (mm)	Max Vent Weight (kg)	Min Vent Height (mm)	Max Vent Height (mm)	Opening Angle (+/-2.5°)
ACINS10	262	40	315	640	50
ACINS12	313	50	640	800	50
ACINS16	415	65	800	1100	50
ACINS22	567	100	1090	1500	45
ACINS22W	567	100	1500	2000	20
ACINS26	680	180	2000	2500	20



Hinge Code Side Hung	Hinge Length (mm)	Max Vent Weight (kg)	Min Vent Width (mm)	Max Vent Width (mm)	Opening Angle (+/-2.5°)
ACINSSH10	262	38	327	660	85
ACINSSH16	415	55	450	838	60

Please Note:

- Dimensions shown in table are sash sizes - not rebate sizes.
- The minimum sash sizes for ACINS10 & ACINSSH10 can both be reduced to 281mm where cockspur handles are used.
- Top hung height & side hung width sizes to be reduced by 2mm where size is 450mm or smaller.

Do Not Scale From This Drawing

## Hinge Protectors & Pull In Blocks





Top Hung

Side Hung


Please Note:

- 2 pairs per opening vent to be fitted to hinged side of window
- Each pair must be fitted with the hook centre within 100mm of each hinge



Please Note:








- 2 pairs per opening vent to be fitted to hinged side of window
- Each pair must be fitted with the wedge centre within 150mm of each hinge and in the centre of the window when sash height is greater than 800mm.



Do Not Scale From This Drawing

## Visotherm Window





### Lock Installation



- \*Handle Options:
  - ACET461
  - ACET466
  - ACSM022
  - ACM050


Do Not Scale From This Drawing

Lock Details



Part Code	Rod Length (mm)	Number of Keeps	Sash Rebate Size ('A')	
			Minimum	Maximum
ACUL001	200	1	200	400
ACUL002	400	2	400	600
ACUL003	600	2	600	800
ACUL004	800	3	800	1000
ACUL005	1000	3	1000	1200
ACUL006	1200	3	1200	1400


Note: To suit handles with 15mm spindles: ACET461, ACET466, ACET868, ACSM022 or ACSM050



Do Not Scale From This Drawing







## Visotherm Window

### Glazing Details



Glass Thickness	External Gasket	Internal Gasket	Glazing Bead
22	ACVG31N	ACUN036	UL063
23	ACVG31N	ACUN036	UL063
24	ACVG31N	ACUN033	UL063
25	ACVG31N	ACUN033	UL063
26	ACVG31N	ACUN036	UL064
27	ACVG31N	ACUN036	UL064
28	ACVG31N	ACUN033	UL064
29	ACVG31N	ACUN033	UL064
30	ACVG31N	ACUN036	UL065
31	ACVG31N	ACUN036	UL065
32	ACVG31N	ACUN033	UL065

Glass Thickness	External Gasket	Internal Gasket	Glazing Bead
36	ACVG31N	ACUN036	UL066
37	ACVG31N	ACUN033	UL066
38	ACVG31N	ACUN033	UL066
39	ACVG31N	ACUN033	UL066
40	ACVG31N	ACUN036	UL067
41	ACVG31N	ACUN036	UL067
42	ACVG31N	ACUN033	UL067
43	ACVG31N	ACUN033	UL067
45	ACVG31N	ACUN036	UL068
46	ACVG31N	ACUN033	UL068
47	ACVG31N	ACUN033	UL068
48	ACVG31N	ACUN033	UL068




#### Important Note

Outerframe and Transoms cannot be glazed directly. For fixed lights a reverse adaptor or dummy sash must be used.






**Do Not Scale From This Drawing**

Glazing Details



Glass Thickness	External Gasket	Internal Gasket	Glazing Bead
22	ACVG31N	ACUN036	UL065
23	ACVG31N	ACUN036	UL065
24	ACVG31N	ACUN033	UL065
25	ACVG31N	ACUN033	UL065
28	ACVG31N	ACUN036	UL066
29	ACVG31N	ACUN033	UL066
30	ACVG31N	ACUN033	UL066

Glass Thickness	External Gasket	Internal Gasket	Glazing Bead
32	ACVG31N	ACUN033	UL067
33	ACVG31N	ACUN033	UL067
34	ACVG31N	ACUN033	UL067
35	ACVG31N	ACUN033	UL067
37	ACVG31N	ACUN036	UL068
38	ACVG31N	ACUN036	UL068
39	ACVG31N	ACUN033	UL068
40	ACVG31N	ACUN033	UL068
41	ACVG31N	ACUN036	UL069
42	ACVG31N	ACUN036	UL069
43	ACVG31N	ACUN033	UL069
44	ACVG31N	ACUN033	UL069



**Important Note**

Outerframe and Transoms cannot be glazed directly. For fixed lights a reverse adaptor or dummy sash must be used.

Do Not Scale From This Drawing

## Visotherm Window

**Do Not Scale From This Drawing**

**Section F**



**Sawing Tables**

- |                                |     |
|--------------------------------|-----|
| UL010 Cutting Information..... | F03 |
| UL011 Cutting Information..... | F04 |

## Visotherm Window

## Visotherm Window

### Cutting Information


PART DESCRIPTIONS		TYPICAL STYLES															
Outer Frame	Head & Cill	W	W	W	W	W	W	W	W	W	W	W	W	W	W	W	
	Jambs	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	
	Transoms		W - 50		W - 50	W - 50	W - 50		OF to €M - 40	W - 50		OF to €M - 40	€M to €M - 30	W - 50	OF to €M - 40	W - 50	
	Mullions							H - 50	H - 50	OF to €T - 40	H - 50	H - 50	H - 50	OF to €T - 40	H - 50		
Vent (1)	Horizontal Members			W - 36	W - 36	W - 36	W - 36	OF to €M - 26	W - 36								
	Vertical Members			H - 36	OF to €T - 26	OF to €T - 26	€T to €T - 16	H - 36	H - 36	OF to €T - 26	H - 36	OF to €T - 26	H - 36	OF to €T - 26	OF to €T - 26	OF to €T - 26	
	Glass Width			W - 151	W - 151	W - 151	W - 151	OF to €M - 141	W - 151								
	Glass Height			H - 151	OF to €T - 141	OF to €T - 141	€T to €T - 131	H - 151	H - 151	OF to €T - 141	H - 151	OF to €T - 141	H - 151	OF to €T - 141	OF to €T - 141	OF to €T - 141	
Vent (2)	Horizontal Members					W - 36			OF to €M - 26				OF to €M - 26	€M to €M - 16	€M to €M - 16	OF to €M - 26	
	Vertical Members					OF to €T - 26			OF to €T - 26				OF to €T - 26				
	Glass Width					W - 151			OF to €M - 141				OF to €M - 141	€M to €M - 131	€M to €M - 131	OF to €M - 141	
	Glass Height					OF to €T - 141			OF to €T - 141				OF to €T - 141				
Fixed Pane (1)	Horizontal Members	W - 39	W - 39		W - 39		W - 39	OF to €M - 29	OF to €M - 29	W - 39	€M to €M - 19	€M to €M - 19	€M to €M - 19	W - 39	OF to €M - 29	W - 39	
	Vertical Members	H - 39	OF to €T - 29		OF to €T - 29		OF to €T - 29	H - 39	OF to €T - 29	OF to €T - 29	H - 39	H - 39	OF to €T - 29	OF to €T - 29	H - 39	OF to €T - 29	
	Glass Width	W - 99	W - 99		W - 99		W - 99	OF to €M - 89	OF to €M - 89	W - 99	€M to €M - 79	€M to €M - 79	€M to €M - 79	W - 99	OF to €M - 89	W - 99	
	Glass Height	H - 99	OF to €T - 89		OF to €T - 89		OF to €T - 89	H - 99	OF to €T - 89	OF to €T - 89	H - 99	H - 99	OF to €T - 89	OF to €T - 89	H - 99	OF to €T - 89	

#### Legend

**W** = Outer Frame Width (Longest Leg)  
**H** = Outer Frame Height (Longest Leg)  
**€T** = Centre Line of Transom  
**€M** = Centre Line of Mullion  
**OF** = Edge of Outer Frame (Longest Leg)

#### Sections

Outer Frame: UL010  
 Sash: UL020, UL023  
 Fixed Light: UL040, UL043  
 Transom/Mullion: UL030, UL031, UL032, UL033



Do Not Scale From This Drawing

## Visotherm Window

### Cutting Information


PART DESCRIPTIONS		TYPICAL STYLES														
Outer Frame	Head & Cill	W	W	W	W	W	W	W	W	W	W	W	W	W	W	W
	Jambs	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H
	Transoms		W - 59		W - 59	W - 59		OF to £M - 44.5	W - 59		OF to £M - 44.5	£M to £M - 30	W - 59	OF to £M - 44.5		W - 59
	Mullions						H - 59	H - 59	OF to £T - 44.5	H - 59	H - 59	H - 59	OF to £T - 44.5	H - 59		
Vent (1)	Horizontal Members			W - 45	W - 45	W - 45	OF to £M - 30.5	W - 45								
	Vertical Members			H - 45	OF to £T - 30.5	OF to £T - 30.5	£T to £T - 16	H - 45	H - 45	OF to £T - 30.5	H - 45	OF to £T - 30.5	H - 45	OF to £T - 30.5	OF to £T - 30.5	OF to £T - 30.5
	Glass Width			W - 160	W - 160	W - 160	OF to £M - 145.5	W - 160								
	Glass Height			H - 160	OF to £T - 145.5	OF to £T - 145.5	£T to £T - 131	H - 160	H - 160	OF to £T - 145.5	H - 160	OF to £T - 145.5	H - 160	OF to £T - 145.5	OF to £T - 145.5	OF to £T - 145.5
Vent (2)	Horizontal Members					W - 45			OF to £M - 30.5			OF to £M - 30.5	£M to £M - 16	£M to £M - 16	OF to £M - 30.5	
	Vertical Members					OF to £T - 30.5			OF to £T - 30.5			OF to £T - 30.5				
	Glass Width					W - 160			OF to £M - 145.5			OF to £M - 145.5	£M to £M - 131	£M to £M - 131	OF to £M - 145.5	
	Glass Height					OF to £T - 145.5			OF to £T - 145.5			OF to £T - 145.5				
Fixed Pane (1)	Horizontal Members	W - 48	W - 48		W - 48		W - 48	OF to £M - 33.5	OF to £M - 33.5	W - 48	£M to £M - 19	£M to £M - 19	£M to £M - 19	W - 48	OF to £M - 33.5	W - 48
	Vertical Members	H - 48	OF to £T - 33.5		OF to £T - 33.5		OF to £T - 33.5	H - 48	OF to £T - 33.5	OF to £T - 33.5	H - 48	H - 48	OF to £T - 33.5	OF to £T - 33.5	H - 48	OF to £T - 33.5
	Glass Width	W - 108	W - 108		W - 108		W - 108	OF to £M - 93.5	OF to £M - 93.5	W - 108	£M to £M - 79	£M to £M - 79	£M to £M - 79	W - 108	OF to £M - 93.5	W - 108
	Glass Height	H - 108	OF to £T - 93.5		OF to £T - 93.5		OF to £T - 93.5	H - 108	OF to £T - 93.5	OF to £T - 93.5	H - 108	H - 108	OF to £T - 93.5	OF to £T - 93.5	H - 108	OF to £T - 93.5

#### Legend

**W** = Outer Frame Width (Longest Leg)  
**H** = Outer Frame Height (Longest Leg)  
**£T** = Centre Line of Transom  
**£M** = Centre Line of Mullion  
**OF** = Edge of Outer Frame (Longest Leg)

#### Sections

Outer Frame: UL011  
 Sash: UL020, UL023  
 Fixed Light: UL040, UL043  
 Transom/Mullion: UL030, UL031, UL032, UL033



Do Not Scale From This Drawing